

CHICAGO, MILWAUKEE, ST. PAUL AND PACIFIC RAILROAD CO.

IDAHO DIVISION

TIME TABLE NO. 6

Taking effect at 12:01 A. M.
Pacific Standard Time

Sunday, February 29, 1948

For the government and information
of employes only

C. A. NUMMERDOR,
Superintendent of Transportation.

J. L. BROWN,
General Superintendent of Transportation.

G. H. HILL,
Superintendent.

L. K. SORENSEN,
General Manager.

TABLE OF TRAIN SPEEDS

Seconds per Mile	Miles per Hour	Seconds per Mile	Miles per Hour
36	100	59	61
37.9	95	60	60
40	90	61	59
42.4	85	62	58.1
45	80	63	57.1
46	78.3	64	56.3
47	76.6	65	55.4
48	75	66	54.5
49	73.5	67	53.7
50	72	68	52.9
51	70.6	69	52.2
52	69.2	70	51.4
53	67.9	75	48
54	66.7	80	45
55	65.5	85	42.4
56	64.3	90	40
57	63.2	100	36
58	62.1	120	30

SHAW & BORDEN CO. 293656



WESTWARD FIRST SUBDIVISION

	SECOND CLASS		FIRST CLASS		Capacity in cars		Telegraph calls	Distance from Avery	TIME TABLE NO. 6 February 29, 1948	STATIONS
	63	263	15	17	Siding	Other tracks				
	Time Freight Daily	Time Freight Daily	Passenger Daily	Passenger Daily						
		L 1.00PM	L 10.35PM	L 6.03PM		Yard	NF	0.0	AVERY 5.3	
		1.15	10.44	6.12	67	20		5.3	ETHELTON 7.7	
					20			13.0	MARBLE CREEK 0.8	
		1.35	11.01	6.29	125	18		13.8	POCONO 8.8	
		1.55	11.16	f 6.44	125	20	CR	22.4	CALDER 10.9	
		2.15	11.34	f 7.01	125	20		33.3	ST. JOE 6.6	
		2.30	11.43	7.11	67			39.9	OMEGA 5.5	
	L 3.30PM	3.15	¹⁶ 11.58	s 7.25	180	500	CB	45.4	ST. MARIES 5.9	
	3.45	3.30	12.08AM	7.33	68	40		51.3	RAMSDELL 5.9	
	4.12	3.50	12.20	7.45	92	16		57.2	PEDEE 7.2	
	A 4.45PM	4.10	A ⁶⁴ 12.35AM	Af 8.01PM	125	80	WJ	64.4	PLUMMER JUNCTION 7.6	
		4.30			65	25		72.0	MOWRY 8.1	
		4.46			115	30	TK	80.1	TEKOA 7.2	
		5.01			30			87.3	SEABURY 5.0	
		5.11			115	20		93.2	PANDORA 6.5	
		5.23			57	20		99.7	ROSALIA 5.5	
		5.33				31		105.2	SQUAW CANYON 3.6	
	A 5.40PM					Yard	M	108.8	MALDEN	

MAXIMUM PERMISSIBLE SPEED—See Special Instruction G-33

	Trains 15 & 16	Other Psgr. trains	Freight trains
Between Avery and Calder.....	40 mph.	40 mph.	30 mph.
Between Calder and Ramsdell.....	70 mph.	70 mph.	45 mph.
Between Ramsdell and Plummer Jct.....	30 mph.	30 mph.	20 mph.
Between Plummer Jct. and Malden.....	50 mph.	40 mph.
Over Street crossings St. Maries.....	20 mph.	20 mph.	20 mph.
Over Bridge EE-44, 1 Mi. West Ramsdell.....	25 mph.	25 mph.	25 mph.
Trains handling logs except when loaded on staked cars.....	30 mph.

INDUSTRIAL TRACKS NOT SHOWN AS STATIONS

Name	Cap. In Cars	Miles	Direction	Station
Hoyts Spur.....	5	0.5	West	Ethelton
Sorrento.....	11	4.5	West	Plummer Jct.
Wallner.....	4	2.0	East	Tekoa
Lone Pine.....	17	2.0	West	Tekoa
Swan.....	8	3.3	East	Pandora
Williams.....	2	2.6	East	Rosalia

EASTWARD TRAINS ARE SUPERIOR TO WESTWARD TRAINS OF THE SAME CLASS

Automatic Block System is in use between Avery and a point 2902 ft. west of Sorrento Tunnel No. 41.

Manual Block System is in use between Plummer Jct. and Malden. Train Order Signals are also used as Block Signals.

Rule 319(A) applies at Malden.

The time of trains No. 15, 17, and 63 at Plummer Junction applies at the junction switch.

FIRST SUBDIVISION EASTWARD

3

TIME TABLE NO. 6 February 29, 1948 STATIONS	Distance from Malden	See Rule 6-A	Office open week days	FIRST CLASS		SECOND CLASS				
				18	16	64	264			
				Passenger	Passenger	Time Freight	Time Freight			
				Daily	Daily	Daily	Daily			
AVERY 5.3	108.8	BEHKORTWX	Continuous	As 11.15AM	As 1.20AM	A 10.10AM				
ETHELTON 7.7	103.5	P	No Office	11.01	1.08	9.34				
MARBLE CREEK 0.8	95.8	P	No Office							
POCONO 8.6	95.0	P	No Office	10.43	12.50	9.12				
CALDER 10.9	86.4	PW	7.00AM to 4.00PM	f 10.27	12.34	8.48				
ST. JOE 6.6	75.5	P	No Office	f 10.08	12.17	8.21				
OMEGA 5.5	68.9	P	No Office	9.57	12.07AM	8.01				
ST. MARIES 5.9	63.4	BEJKORWXYZ	Continuous	s 9.48	11.58 ¹⁵	A 1.30AM	7.45			
RAMSDELL 5.9	57.5	P	No Office	9.34	11.50	1.15	6.30			
PEDEE 7.2	51.6	P	No Office	9.24	11.37	1.00	6.10			
PLUMMER JUNCTION 7.6	44.4	JKRWXY	Continuous	L 9.10AM	L 11.21PM	L 12.35AM ¹⁵	5.50			
MOWRY 8.1	36.8	P	No Office			5.29				
TEKOA 7.2	28.7	PW	7.00 AM to 4.00PM			5.13				
SEABURY 5.9	21.5	P	No Office			4.46				
PANDORA 6.5	15.6	P	No Office			4.28				
ROSALIA 5.5	9.1	PV	No Office			4.10				
SQUAW CANYON 3.6	3.6	P	No Office			3.52				
MALDEN	0.0	BHKRWXY	Continuous			L 3.40AM				

MAXIMUM PERMISSIBLE SPEED—See Special Instruction G-33

	Trains 15 & 16	Other Psgr. trains	Freight trains
Avery—Passenger Station and approaching it.....	Restricted Speed	Restricted Speed	Restricted Speed
Between Avery and Calder.....	40 mph.	40 mph.	30 mph.
Between Calder and Ramsdell.....	70 mph.	70 mph.	45 mph.
Between Ramsdell and Plummer Jct.....	30 mph.	30 mph.	20 mph.
Between Plummer Jct. and Malden.....	50 mph.	50 mph.	40 mph.
Over Street crossings St. Maries.....	20 mph.	20 mph.	20 mph.
Over Bridge BE-44, 1 Mi. West Ramsdell....	25 mph.	25 mph.	25 mph.
Trains handling logs except when loaded on staked cars.....			30 mph.

EASTWARD TRAINS ARE SUPERIOR TO WESTWARD TRAINS OF THE SAME CLASS

Automatic Block System is in use between a point 2902 ft. west of Sorrento Tunnel No. 41 and Avery.

Rule 319(A) applies at Plummer Jct.

Manual Block System is in use between Malden and Plummer Jct. Train Order Signals are also used as Block Signals.

The time of Trains No. 16, 18 and 64 at Plummer Jct. applies at the junction switch.

WESTWARD SECOND SUBDIVISION

	SECOND CLASS			FIRST CLASS		Capacity in cars		Telegraph calls	Distance from Plummer Junction	TIME TABLE NO. 6 February 29, 1948 STATIONS
	63	463	391	17	15	Sidings	Other tracks			
	Time Freight Daily	Time Freight Daily Except Sunday	Way Freight Daily Except Sun.	Passenger Daily	Passenger Daily					
	L 4.50PM			L 8.01PM	L 12.35AM			WJ	0.0	PLUMMER JUNCTION 6.4
	5.08			f 8.11			27	WY	6.4	WORLEY 1.4
	5.12			8.13	12.46	101			7.8	MOZART 5.3
							27		18.1	SETTERS 2.4
	5.34			8.23	12.55	45	9		15.5	SAXBY 4.3
	A 5.45PM			A 8.33PM	A 1.01AM	71	10	MU	19.8	MANITO 15.2
			3.30PM					SP	35.0	DISHMAN 3.8
									38.8	EAST SPOKANE 0.8
									39.6	N. P. CROSSING 1.2
	7.30PM	11.00 AM	4.00PM				Yard		40.8	SPOKANE YARD 0.7
				9.15 PM 9.40 PM	1.45 AM 1.55 AM			BN	41.5	SPOKANE 31.2
		1.30 PM		11.10 PM	3.25 AM			RA	102.7	MARENGO

EASTWARD SECOND SUBDIVISION

TIME TABLE NO. 6 February 29, 1948 STATIONS	Distance from Marengo	See Rule 6-A	Office open week days	FIRST CLASS		SECOND CLASS		
				18	16	464	392	64
				Passenger Daily	Passenger Daily	Time Freight Daily Except Sun.	Way Freight Daily Except Sat.	Time Freight Daily
PLUMMER JUNCTION 6.4	102.7	JERWXY	Continuous	Af 9.10AM	A 11.21PM			A 12.30AM
WORLEY 1.4	96.3	P	8.00 AM to 5.00 PM	8.58				12.05
MOZART 5.3	94.9	P	No Office	8.54	11.10			12.01AM
SETTERS 2.4	89.6	P	No Office					
SAXBY 4.3	87.3	P	No Office	8.47	11.01			11.43
MANITO 15.2	82.9	JRVXY	Continuous	L 8.40AM	L 10.55PM			L 11.25PM
DISHMAN 3.8	87.7	K					9.30AM	
EAST SPOKANE 0.8	63.9							
N. P. CROSSING 1.2	68.1		Via U. P. R. R.					
SPOKANE YARD 0.7	61.9			8.00 AM 7.30 AM	10.15PM 9.55PM	4.30 PM	9.05AM	9.30PM
SPOKANE 31.2	61.2	BKORTVWZ						
MARENGO	0.0	JRVWXY	Continuous	5.55 AM	8.32 PM	2.30 PM		

MAXIMUM PERMISSIBLE SPEED—See Special Instruction G-33

	Trains 15 & 16	Other Psgr. trains	Freight trains
Between Plummer Jct. and Manito.....	70 mph.	70 mph.	60 mph.
Around curve ½ Mi. West of Plummer Jct....	30 mph.	30 mph.	20 mph.
Trains handling logs except when loaded on staked cars.....			30 mph.

EASTWARD TRAINS ARE SUPERIOR TO WESTWARD TRAINS OF THE SAME CLASS

This time-table confers no authority between Manito and Marengo.
Union Pacific R. R. time-table and rules govern.
Automatic Block System is in use between Manito and Plummer Jct.

The time of Trains No. 15, No. 17, No. 63, No. 16, No. 18,
and No. 64 at Plummer Jct. applies at the junction switch.
Trains cannot meet at Worley.

WESTWARD

THIRD SUBDIVISION

EASTWARD

SECOND CLASS 263	FIRST CLASS		Capacity in cars		Distance from Malden	Time Table No. 6 February 29, 1948	Distance from Othello	See Rule 6-A	Office open week days	FIRST CLASS		SECOND CLASS
	17	15	Sidings	Other tracks						18	16	264
	Time Freight	Passenger										Passenger
Daily	Daily	Daily				STATIONS				Daily	Daily	Daily
L 6.00PM				Yard	0.0	M MALDEN	103.4	BHKRWX	Continuous			A 3.20AM
6.10				25	3.6	3.6 PINE CITY	99.8		No Office			3.06
6.15			66	30	5.6	2.0 KENOVA	97.8	P	No Office			3.01
6.30			72	20	11.3	5.7 ROCK LAKE	92.1	P	No Office			2.50
6.45			110	20	17.0	2.2 LAVISTA	86.4	P	No Office			2.38
6.50			48	8	19.2	10.4 WNW EWAN	84.2	PW	7.00 AM to 4.00 PM			2.33
7.10			110	35	29.6	4.1 REVERE	73.8	P	No Office			2.15
7.20			68	16	33.7	10.3 PAXTON	69.7	P	No Office			2.05
8.05	L 11.13PM	L 3.25AM	96	50	44.0	5.9 RA MARENGO	59.4	JRVWXY	Continuous	As 5.50AM	A 8.32PM	1.45
10 8.25	11.22	3.35	67		49.9	3.6 HILLCREST	53.5	P	No Office	5.38	8.25	1.01
8.36	f 11.27	3.40	115	30	53.5	5.0 RALSTON	49.9	PW	No Office	f 5.33	8.22	12.55
				20	58.5	4.8 PIZARRO	44.9	P	No Office			
8.56	11.37	3.50	67	15	63.3	4.7 VASSAR	40.1	P	No Office	5.21	8.13	12.35
9.06	s 11.45	3.56	110	30	68.0	8.0 NE LIND	35.4	P	11.00PM to 7.00AM 8.00AM to 4.00PM	s 5.13	8.08	12.25AM
9.22	11.55	4.04	63	13	76.0	4.9 SERVIA	27.4	P	No Office	4.58	8.01	11.55
9.32	f 12.05AM	4.10	110	25	80.9	9.7 ROXBORO	22.5	P	No Office	f 4.52	7.56	11.40
9.52	s 12.20	4.20	124	25	90.6	8.8 WX WARDEN	12.8	JPWY	Continuous	s 4.42	7.48	11.26
10.10	12.33	4.32	67	30	99.4	4.0 NOVARA	4.0	P	No Office	4.32	7.40	11.10
A 10.30PM	As 12.45AM	As 4.45AM		Yard	103.4	SO OTHELLO	0.0	BHKORTWX	Continuous	L 4.27AM	L 7.35PM	L 11.00PM

MAXIMUM PERMISSIBLE SPEED—See Special Instruction G-33

	Trains 15 & 16	Other Psgr. trains	Freight trains
Between Malden and M.P. 1892.....	55 mph.	40 mph.
Between M.P. 1892 and 1899.....	30 mph.	30 mph.
Between M.P. 1899 and Marengo.....	50 mph.	35 mph.
Between Marengo and Hillcrest.....	70 mph.	65 mph.	50 mph.
Between Hillcrest and Othello.....	80 mph.	70 mph.	50 mph.
Othello—Passenger Station and approaching it.....	Restricted Speed	Restricted Speed	Restricted Speed

INDUSTRIAL TRACKS NOT SHOWN AS STATIONS

Name	Cap. In cars	Miles	Direction	Station
Carlmar.....	5.....	3.0.....	East.....	Marengo
East Lind.....	13.....	0.6.....	East.....	Lind
Hole Track.....	140.....	1.7.....	West.....	Lind

EASTWARD TRAINS ARE SUPERIOR TO WESTWARD TRAINS OF THE SAME CLASS

Manual Block System is in use between Malden and Marengo. Train Order Signals are also used as Block Signals.

Automatic Block System is in use between Marengo and Othello.

Rule 319(A) applies at Malden and Marengo.

The time of eastward trains departing from Othello applies at the east crossover, located 1275 feet east of depot.

Under train order meets or waits, westward trains entering Othello will take siding at this crossover unless otherwise designated in the orders.

SECOND CLASS		Capacity in cars				Telegraph calls	Distance from St. Maries	TIME TABLE NO. 6			Distance from Elk River	See Rule 6-A	Office open week days	THIRD CLASS	
103	Way Freight	Siding	Other tracks	Yard	CB			0.0	ST. MARIES	72.2				BHKORWXYZ	Continuous
Daily Except Sunday	Daily Except Sunday					As 4.15PM	Daily Except Sunday								
L 9.30AM						0.0	ST. MARIES 9.4	72.2	BHKORWXYZ	Continuous		As 4.15PM			
f 10.00		12				9.4	LOTUS 1.7	62.8	P	No Office		f 3.41			
f 10.10		43	20			11.1	ALDER CREEK 2.4	61.1	P	No Office		f 3.35			
f 10.25		25				13.5	ROVER 6.1	58.7	P	No Office		f 3.25			
f 10.50		47				19.6	MASHBURN 1.5	52.6	P	No Office		f 3.05			
10.55		43				21.1	WAYLAND 2.0	51.1	P	No Office		f 2.58			
f 11.05		10	15			23.1	SANTA 2.0	49.1	P	No Office		f 2.53			
f 11.12		30	35			25.1	TYSON CREEK 2.0	47.1	P	No Office		f 2.46			
s 11.20		24				27.1	FERNWOOD 2.0	45.1	PW	No Office		f 2.39			
		38				29.1	CARPENTER CREEK 2.6	43.1	PY	No Office					
f 11.35		36				31.7	EMERALD CREEK 5.2	40.5	P	No Office		f 2.23			
s 12.10PM		30	90		CA	36.9	CLARKIA 5.7	35.3	PX	7.00 AM to 4.00 PM		s 2.05			
f 12.25		12				42.6	KEELER 2.2	29.6	P	No Office		f 1.50			
f 12.40		16				44.8	SHERWIN 5.6	27.4	P	No Office		f 1.40			
As 12.58PM						50.4	PURDUE	21.8	JVX	No Office		Lf 1.20PM			
							PURDUE 2.0								
As 1.05PM							BOVILL			Via W. I. & M. R. R.		L 1.15PM			
		50	120		BO	52.4	BOVILL 8.7	19.8	JRVWXY	8.00 AM to 5.00 PM					
		11				61.1	NEVA 4.0	11.1	P	No Office					
		20				65.1	KAMERON 5.2	7.1		No Office					
		12				70.3	JERSEY 1.9	1.9		No Office					
		11	100			72.2	ELK RIVER	0.0	PRWXY	No Office					

MAXIMUM PERMISSIBLE SPEED

	Psg. trains	Freight trains
Between St. Maries and Elk River.....	30 mph.	25 mph.
Around sharp curves.....	20 mph.	15 mph.

Over bridges EE-504, EE-506 and EE-508 between Lotus section house and Rover, and EE-550 2½ miles west of Emerald Creek 15 miles per hour. Engines must not be doubleheaded over these bridges.

EASTWARD TRAINS ARE SUPERIOR TO WESTWARD TRAINS OF THE SAME CLASS

This time-table confers no authority between Purdue and Bovill. W. I. & M. Ry. time-table and rules govern.

Trains need not obtain Clearance Form A at Elk River.

Trains No. 102 and 103 will carry passengers.

INDUSTRIAL TRACKS NOT SHOWN AS STATIONS

Name	Cap. In Cars	Miles	Direction	Station
Cardwell.....	14	1.0	West	Rover
Renfrew.....	19	0.5	West	Santa
Childs Creek.....	25	0.8	West	Emerald Creek
Jim's Spur.....	3	1.0	West	Emerald Creek
Owens.....	5	7.1	West	Bovill

WESTWARD

FIFTH SUBDIVISION

EASTWARD

SECOND CLASS		Capacity in cars		Telegraph calls	Distance from Dishman	TIME TABLE NO. 6 February 29, 1948	Distance from Metaline Falls	See Rule 6-A	Office open week days	SECOND CLASS	THIRD CLASS
95	291	Sidings	Other tracks							292	96
G.N. Freight Daily Exc. Sat. & Sun.	Way Freight Daily Except Sat.					Way Freight Daily Except Sun.	G.N. Freight Daily Exc. Sat. & Sun.				
	L 10.30AM	40	110	EP	0.0	DISHMAN 5.7	120.1	JRVWXY	Continuous	A 3.01PM	
	10.50		18		5.7	GREENACRES 6.0	114.4		No Office	2.40	
L 9.30AM	11.05	45	90		11.7	SPOKANE BRIDGE 3.3	108.4	P	No Office	2.25	A 4.10PM
A 9.40AM	11.30	44	22		18.0	McGUIRES (N. P. Crossing) (S. L. Crossing)	105.1 1.5 103.6 0.1	JPXVR	No Office	2.15	L 4.01PM
	11.40	29	5		16.6	GRAND JUNCTION 6.7	103.5	VX	No Office	1.45	
	11.55	30			23.3	RATHDRUM 11.4	96.8	PV	No Office	1.20	
	12.20PM	26			34.7	JENIDA 2.4	85.4	P	No Office	12.45	
	202 12.30	40	14		37.1	SPIRIT LAKE 7.0	83.0	PW	No Office	201 12.30	
	1.01	34			44.7	BLANCHARD 5.8	75.4		No Office	12.01PM	
	1.11		8		50.5	TWEEDIE 8.5	69.6	P	No Office	11.45	
	1.50	28	65	NR	59.0	NEWPORT 4.5	61.1	VWXZ	7.00AM to 4PM	11.30	
	1.59		62		63.5	SULLIVAN 7.6	56.6	P	No Office	10.15	
	2.12	20			71.0	DALKENA 5.2	49.1	P	No Office	9.55	
	2.27	36	20		76.2	USK 1.9	43.9	PXY	No Office	9.40	
	2.45		45	CU	78.1	CUSICK 10.2	42.0	X	8.00 AM to 5.00 PM	9.30	
	3.08	15			88.3	JARED 5.0	31.8	P	No Office	8.55	
	3.20		12		93.3	RUBY 3.7	26.8	P	No Office	8.45	
	3.30	12			97.0	BLUESLIDE 3.9	23.1	P	No Office	8.35	
	3.40	20			100.9	LOST CREEK 5.7	19.2	P	No Office	8.25	
	3.50	12			106.6	TIGER 4.0	13.5	P	No Office	8.10	
	4.10	28	21		110.6	IONE 9.5	9.5	PW	No Office	8.00	
A 4.40PM		20	180	MF	120.1	METALINE FALLS	0.0	KRXY	6.30AM to 3.30PM	L 7.30AM	

MAXIMUM PERMISSIBLE SPEED		
	Psgr. trains	Freight trains
Between Dishman and McGuires.....	30 mph.	25 mph.
Between McGuires and Ione.....	45 mph.	30 mph.
Between Ione and Metaline Falls.....	30 mph.	25 mph.
On curve 1 1/4 Mi. West of Newport.....	25 mph.	20 mph.
Trains handling logs.....		25 mph.

EASTWARD TRAINS ARE SUPERIOR TO WESTWARD TRAINS OF THE SAME CLASS

All trains will register at McGuires. Great Northern trains will, in addition, register at Spokane Bridge.

INDUSTRIAL TRACKS NOT SHOWN AS STATIONS

Name	Cap. In Cars	Miles	Direction	Station
Opportunity.....	28	0.8	West.....	Dishman
Vera.....	14	4.5	West.....	Dishman
Arturdee.....	8	2.6	West.....	Greenacres
Sachwell.....	8	3.7	West.....	Grand Jct.
Seasons.....	7	4.1	East.....	Jenida
Callspel.....	8	0.6	West.....	Cusick
Sand Creek.....	6	5.3	West.....	Ione

SECOND CLASS		Capacity in cars				Distance from McGuire's	TIME TABLE NO. 6 February 29, 1948	Distance from Coeur d'Alene	See Rule 6-A	Office open week days	THIRD CLASS	
95	G.N. Freight Daily Except Sat. and Sun.	Sidings	Other tracks	Telegraph calls	96						G.N. Freight Daily Except Sat. and Sun.	
L	L 9.40AM	44	22		0.0	McGUIRES -1.8	10.4	JPXR	No Office	A	4.01PM	
	9.45	16			1.8	POST FALLS (O. M. Co. Crossing)	8.6		No Office		3.40	
	9.55		50		6.2	HUETTERS (N. P. Crossing)	4.2	M	No Office		3.20	
	10.05				7.1	ATLAS -0.9	3.3		No Office		3.10	
A	A 10.30AM	18	18		8.7	GIBBS -1.7	1.7	VXZ	No Office	L	3.00PM	
A			20	CD	10.4	COEUR D'ALENE (G. N. Crossing)	0.0	BRVXY	8.00 AM to 5.00 PM		L	

Maximum Permissible Speed—25 miles per hour.

EASTWARD TRAINS ARE SUPERIOR TO WESTWARD TRAINS OF THE SAME CLASS

Trains need not obtain Clearance Form A at McGuire's.

At Huetters the Ohio Match Co. R. R. crossing is protected by gates normally set for movement on C. M. St. P. & P. R. R. tracks.

SECOND CLASS		Capacity in cars				Distance from Warden	TIME TABLE NO. 6 February 29, 1948	Distance from Moses Lake	See Rule 6-A	Office open week days	THIRD CLASS	
315	303	Sidings	Other tracks	Telegraph calls	304						316	
Mixed Fridays only	Mixed Daily Exe Sunday					WARDEN -8.2	23.2	JPRWY	Continuous	As	8.30PM	
L 7.00AM	L 2.30PM			WX	0.0	TIFLIS -9.0	15.0	JPY	No Office	As	7.50	
A 7.25AM	As 2.55		15		8.2	McDONALD -2.0	6.0			f	7.15	
	3.25	20	2		17.2	GOODRICH -4.0	4.0		No Office	f	7.10	
	f 3.30	25	13		19.2	MOSES LAKE	0.0	RPXY	8.00 AM to 5.00 PM	L	7.00PM	
	As 4.00PM	56	208	MO	23.2							

Maximum Permissible Speed—25 miles per hour.

EASTWARD TRAINS ARE SUPERIOR TO WESTWARD TRAINS OF THE SAME CLASS

Sieler—Capacity, 4 cars.....3 miles east of McDonald
Trains need not obtain Clearance Form A at Moses Lake

SECOND CLASS		Capacity in cars				Distance from Tiflis	TIME TABLE NO. 6 February 29, 1948	Distance from Marcellus	See Rule 6-A	Office open week days	THIRD CLASS	
315	Mixed Fridays only	Sidings	Other tracks	Telegraph calls	316						Mixed Fridays only	
L	L 7.25AM	23			0.0	TIFLIS -8.0	38.7	JPY	No Office	A	12.50PM	
	f 7.55	23			8.0	RUFF -5.8	30.7	PW	No Office	f	12.20PM	
	f 8.15	23			13.8	MOODY -5.0	24.9	P	No Office	f	11.55	
	f 8.35	23			18.8	BATUM -3.9	19.9	P	No Office	f	11.35	
	f 8.50	23			22.7	LAUER -0.8	16.0	P	No Office	f	11.20	
	f 9.15	23			29.5	SCHOONOVER -4.4	9.2	P	No Office	f	10.55	
	f 9.35	23			33.9	PACKARD -4.8	4.8	P	No Office	f	10.35	
	As 9.55AM	37			38.7	MARCELLUS	0.0	PWY	No Office	L	10.15AM	

Maximum Permissible Speed—25 miles per hour.

EASTWARD TRAINS ARE SUPERIOR TO WESTWARD TRAINS OF THE SAME CLASS

Trains need not obtain Clearance Form A at Tiflis or Marcellus.

INDUSTRIAL TRACKS NOT SHOWN AS STATIONS

Laing—Capacity, 6 cars.....4.6 miles west of Tiflis
Parnell—Capacity, 14 cars.....2.5 miles east of Ruff

Jantz—Capacity, 11 cars.....4.2 miles west of Lauer
Schafer—Capacity, 10 cars.....2 miles west of Packard

SPECIAL INSTRUCTIONS

ALL SUBDIVISIONS

G1 Engineers operating engines equipped with the oscillating emergency red headlight will be governed by the following:

When the air brakes are applied from any cause other than in normal operation by the engineer, or when it is found necessary to stop train due to some defect, or under circumstances which might cause a derailment and the fouling of adjacent main track, engineer must immediately display the oscillating red headlight.

Engineers on approaching trains will take notice and immediately bring train to a stop, and will not proceed until track is found to be safe and clear for their movement.

These instructions are applicable at all times, both day and night. The emergency headlight should not be used for any other purpose.

The operation and use of this device does not in any way relieve trainmen and enginemen from full compliance with Rules 99 and 102.

Emergency Red Rear End Lights. Trainmen on trains equipped with oscillating emergency red rear end lights must familiarize themselves with the location of the switches which control the lights and will be governed by the following:

The emergency red rear end light will be used on trains so equipped in the following manner:

To provide protection to trains on adjacent tracks as required by Rule 102.

To provide supplemental protection under Rule 99 in all circumstances where its use is necessary to stop following trains on one or more tracks.

A following train observing this emergency red light displayed must immediately reduce to restricted speed and be governed by instructions of flagman.

The use of this emergency red light does not in any way relieve the flagman from full compliance with Rules 99 and 102.

Portable emergency red lights must be removed before coupling onto the car.

G2 The Mars white light on engines so equipped shall be used at all times between the hours of sunset and sunrise, and during daylight hours on days that are dark, or during sleet, snow, fog or rain, such as would impair the vision of motorists and hinder them from observing approaching trains, except the light must be turned out when moving through certain portions of large terminals and yards where yard engines are employed, approaching junctions, or meeting points, or while standing at those points, and when approaching trains in the opposite direction on double or three or more tracks.

In case of failure of the regular headlight, the Mars white light should be used in stationary position as the headlight.

G3 Where Approach signals are used in connection with facing point switches or manual block signals, the switch or block signal will be considered as the Home signal.

G4 Employees are prohibited from:

Removing any of the appliances of engines or cars that will endanger the safety of themselves or others.

Standing on top of high cars while passing under bridges or through tunnels.

Getting on the end of an engine or of a car as it approaches them.

Going between or running ahead of moving cars to couple, uncouple, open, close, or arrange knuckles of couplers.

Working on the side of cars or trains where there are build-ings, sheds, cattle chutes, or other projections.

Kicking or holding draw bar in position to make a coupling with an approaching car or engine.

Following other dangerous practices.

G5 When, for any reason, adjustment is necessary to a draw bar, knuckle pin, or locking block prior to making coupling or when coupling does not make, the engine or cars must be separated not less than 20 feet and action taken to prevent the cars from moving before going between the cars to make the adjustments.

G6 Whenever a car without a drawbar or draft timber is to be moved by a train or engine and it is necessary to chain the car to other cars or engines, employees are prohibited from going between such car and other cars or engines until the persons performing the work have a thorough understanding with the engineer and other members of the train crew. During the process of chaining up the car, the car itself must be properly secured while being chained to other cars, and if the car is to be chained to the engine, then the car must be secured and the brakes on the engine set to avoid a movement of any kind. The engineer must not release the brakes until he has received verbal information that all employees are out from between the cars or engines, and under no circumstances must employees again go between such car or cars and engines until the engineer and other members of the train crew have been notified and the car properly secured and the engine brake set.

G7 Employees must not handle or board cars or engines that bear BAD ORDER cards without first ascertaining the nature of the defect so that they may guard against injury.

G8 When descending the gangway steps, employees must face the engine.

G9 Employees must not step on track rails nor other similar objects when it can be avoided.

G10 When run-ways, gang-planks or skids are used in handling freight to or from cars, they must be secured to prevent slipping.

G11 Lighting enginemen's torches by holding them in the fire box is hazardous and must not be permitted.

G12 Employees are prohibited from riding:

On engine footboards or pilot steps between engine and car when cars are being pushed.

On leading footboard or pilot steps while coupling engine to cars.

On deadwoods, drawbars, brake beams, journal boxes and brake wheels.

On ends of cars containing lading which may shift.

On engine pilot or footboards, sides or ends of cars, while going in or out of depressed tracks.

On forward footboard or pilot steps of engine in direction the engine is moving except in cases where operating conditions make it necessary for safety and then only one employe must ride on the footboard.

In the gangway of engine.

G13 When necessary to go outside when locomotive is either standing or moving, extreme caution must be exercised to avoid slipping or falling from cab ledge (catwalk) or running

board. Cab ledge (catwalk) is not to be used on standing locomotives when access to the running board can be had by other means.

G14 The use of gasoline stoves in Railroad Company's equipment or buildings is prohibited; the use of oil stoves other than modern kerosene stoves (preferably those bearing the Underwriter's label) is also prohibited.

This does not apply to U. S. Army Field Ranges when installed under the supervision of a U. S. Army commissioned officer and operated by his men.

G15 The provisions of Rule 815 also apply to transfer movements within yards.

G16 All 44-ton Diesel engines dead in freight trains must be handled at rear of train just ahead of the caboose and when a pusher engine is placed on the rear of the train, the 44-ton Diesel engine must be placed behind the pusher. When there is a 44-ton dead Diesel engine in the rear of the train, the train must not be pushed nor pulled from the rear, and the dead Diesel engine must not be handled in switching movements in conjunction with other cars.

The following equipment must not be towed or operated under its own power through water in excess of the maximum height of water above rail shown below. When towed or operated under own power through water of lesser depth than that shown below, a speed of three miles per hour must not be exceeded.

Diesel power units 600 and 1000 H.P. Switchers---4½ inches.

All other Diesel engines and Gas-Electric motor cars -----3 inches.

When operating through water under own power, controller should be in Series position.

G17 The following cars, loaded or empty, will be handled next ahead of the caboose giving preference in the order shown, except that at least one car must be handled between a flat car loaded with rails and the caboose:

Bad order cars.

Wood underframe flat cars.

Switch rear "S.R." cars.

G18 Unoccupied outfit cars of steel underframe or steel center sill construction when inspected and passed by a Car Department inspector, may be hauled in any part of the train.

G19 For the comfort of the passengers, the air-conditioning on our air-conditioned passenger trains should be kept operating as long as possible. When approaching stations where cars are to be picked up or set out between the engine and the rear car, the steam line must be blown out at the proper place and the steam shut off before the train stops. At the final terminal of the equipment, when no cars are to be set out between the engine and the rear car, the fireman will simply shut off the steam as soon as the train stops in the station.

G20 In case of heavy rain or violent windstorm, the operator must notify the section foreman.

G21 A yellow flag by day stencilled ELECTRIC CHARGE LINE and in addition, a yellow light by night, placed at one or both ends of a passenger car standing on a yard track, indicates that the battery of the car is connected to a charge line. When thus protected, it must not be coupled to or moved before the charge line has been removed. Other equipment must not be placed on the same track so as to intercept the view of the yellow signals without first notifying the workmen; in the absence of the workmen, the signals may be moved to the end of the equipment so placed to afford the necessary protection.

DEFINITIONS

G22 Centralized Traffic Control.—A block or a series of consecutive blocks, the signals of which, together with certain switches, are controlled from a central location.

Remote Control Interlocking.—A system of operating outlying signal appliances from a designated point.

C.T.C.—Abbreviation for Centralized Traffic Control.

CENTRALIZED TRAFFIC CONTROL

- G23 (a) On portions of the railroad so specified in the timetable, trains will be governed by block signals whose indications will supersede the superiority of trains for both opposing and following movement on the same track.
- (b) Except as affected by Special Instructions G23 (a), all block signal rules and operating rules remain in force.
- (c) The movement of trains and engines will be supervised by the Train Dispatcher, who may also control the C.T.C. When the C.T.C. is controlled by other than the Dispatcher, the Dispatcher will issue the necessary instructions to the operator at the control station, location of control station will be designated by special instructions.
- (d) Trains or engines must not enter C.T.C. territory unless the governing signal displays a Proceed indication or unless authority is obtained from the authorized employe at the control station.
- (e) In case of failure of a Stop signal, authority to proceed will be issued orally by the authorized employe at the control station.
- (f) Trains or engines must not move beyond the limits of C.T.C. territory without the proper authority including the information required by Rules S-83 and D-83.
- (g) When the governing signal displays a Stop indication and the operator knows that the interlocked switches are in proper position and there are no opposing or conflicting train or engine movements involved, he will authorize the train or engine to proceed in the following form:

"You may proceed at restricted speed to the next signal."

If the operator does not positively know that there are no opposing or conflicting train or engine movements involved or that the interlocked switches are in proper position, he will issue authority to proceed in the following form:

"You may proceed under protection of a flagman to the first signal that displays a proceed indication."

These instructions must be repeated by the conductor or engineer to insure correct understanding.

See Rule 663(A).

- (h) When the governing signal displays a Stop indication for an approaching train or engine and the means of communication have failed, the train or engine may proceed at restricted speed, when preceded by a flagman, to the next signal that displays a Proceed indication, or to the next point of communication. Flagman must be sent far enough in advance to insure full protection.
- (i) Where main track switches are not interlocked or equipped with electric locks, when a train or engine enters a siding or other track or makes a crossover movement, the operator in charge must be notified when the movement is complete and the main track switches have been closed and locked. The switches must not be opened nor will the train or engine enter upon or foul the main track without first receiving authority from the operator.
- (j) A train or engine must not move in the opposite direction to that authorized by the governing signal without proper authority from the operator, unless preceded

by a flagman sent far enough in advance to insure protection.

- (k) Instructions for the operation of the electric locks on hand operated switches are posted in telephone booths or on the inside of the door of the locks.
- (l) Dual Control switches are located at Interlocking in C.T.C. territory. See Rules 663(A), 663(B) and 663(C).

GENERAL SPEED RESTRICTIONS

G24 When freight cars (except cars that are equipped for passenger train service) are hauled in a passenger train, the maximum speed of that train will be that prescribed for freight trains in that territory unless a different speed is authorized by bulletin or train order.

G25 Dead engines must not be hauled in trains without instructions from the Chief Dispatcher and must be accompanied by a competent rider, except a rider is not required for gas-electric or diesel engines.

A rider is not required for dead engines handled by yard crews in terminals, except where condition of dead engine or other circumstances may require for safe movement.

Engines with side rods removed from one side only, must not be hauled in trains.

Dead engines equipped with wood underframe tenders, when hauled in trains, should be placed in the rear of the train just ahead of any Switch Rear cars.

G26 Gas-Electric motor cars should not be hauled dead in trains unless disabled. When necessary to haul such cars dead in freight trains, they should be hauled on the rear of short freight trains.

G27 Dead engines must not be hauled backward in trains if it can be prevented and then only at slow speed.

Conductors will notify engineers when one or more dead engines are to be hauled in trains and the conditions under which they are being handled, so that the speed may be regulated accordingly.

G28 When dead engines with side rods disconnected are hauled in trains there must be at least 8 cars between engines so hauled.

G29 Dead engines of Class K type or larger when hauled in trains should be placed approximately 10 cars from the road engine.

G30 Unless otherwise restricted, the following equipment must not be moved in excess of the maximum speeds shown below and further reduction must be made where conditions require:

Type of equipment	M.P.H.
Trains handling loaded air dump cars (must stop when meeting trains on double track)	25
Work trains with workmen or occupied outfit cars	25
Lidgerwood unloaders	15
Scale test cars, on branch lines 20, on main line	25
Class I engines	25
Passenger trains handled or helped by freight engines with single trucks	60
F-5 and F-6 engines (on first, second, third and fourth sub-divisions)	70
K-1 engines on passenger trains (but must not be used except in extreme emergency)	45
L-2 and L-3 engines	50
S-1 engines (on first, second, third and fourth sub-divisions)	70
Dead engines with side rods disconnected	15
Dead engines with side rods in position	25
Engines with side rods off and main rods connected when working steam, running light or in train	15
Engines (other than Mallet type) with side rods in position and one main rod removed, light or hauling cars	25

Mallet type engines working steam with one main rod removed
 20 |

Diesel switches, either dead in train or operating under their own power (except 600 H.P. Alco switches 1600 to 1603 inclusive)
 45 |

600 H.P. Alco switches, series 1600 to 1603 inclusive
 40 |

All 44-ton Diesels:

When dead in train
 25 |

When under own power
 30 |

Dead engines with all rods connected, pistons removed and valve motion disconnected
 45 |

G31 Unless otherwise specified, the speed of all trains or engines approaching interlocked railroad crossings must be reduced, and passenger trains must not exceed 45 miles per hour and other trains or engines 25 miles per hour when passing over such crossing. The stated speed must be further reduced where conditions require. This does not apply to railroad crossings protected by automatic signals or gates; trains and engines will approach such crossings at restricted speed and if proper proceed indication is received, may pass over the crossing at the speed prescribed by Special instructions or bulletin.

The speed of all trains must not exceed 20 miles per hour while passing over railroad crossings protected by signals or gates unless otherwise specified.

G32 The speed of trains handled by Gas-Electric or other similar type power, when consisting of power unit only, must not exceed 10 miles per hour when approaching and passing over railroad crossings protected by automatic signals.

G33 That enginemen may have knowledge of the maximum permissible speed around curves and at points where normal authorized speed must be restricted, a yellow sign with the black letters R.S. and black figures and placed at an upward angle of 45° on the right hand side of the track, indicates that the permissible speed beginning 3000 ft. distant corresponds in miles per hour, to the figures shown. A yellow sign with the black letters R.S. and placed in a vertical position on the right hand side of the track, indicates that normal speed may be resumed.

These signs do not apply to trains which by time-table or other instructions, are restricted to a slower speed.

Where these signs have two sets of figures the outside figures apply to the movement of freight trains and those nearest the track apply to passenger trains.

G34 Spring switches: Movement in facing point direction over a spring switch equipped with facing point lock may be made at normal speed. Movement in facing point direction over a spring switch not equipped with facing point lock must not exceed 25 miles per hour. If switch is lined for turnout, the allowable turnout speed must be observed.

Movement in trailing point direction over a spring switch on track for which the switch is lined may be made at normal speed.

Movement in trailing point direction which springs the switch points must not exceed 40 miles per hour.

If movement is through turnout the allowable turnout speed must be observed.

See Rules 520 to 525 inclusive.

G34(A) Spring switch must not be thrown by hand when wheels are standing on any part of the switch points, nor before the points have completed their full movement after being trailed through.

G35 In addition to Consolidated Code Rule 801 about handling of occupied outfit cars, the following will also apply on this Railroad:

When occupied outfit cars are set on a siding, the switches at

each end should be spiked to prevent any possibility of a train striking the cars.

The same principle will also apply when such cars are placed on other side tracks; but when, for operating reasons, it is not practicable to have the switches spiked, the train dispatcher must be notified.

When occupied outfit cars are standing on other than siding and the switches on each end are not spiked, a yellow signal must be displayed on each end of the outfit cars. Under such conditions, the cars must not be moved except when necessary and then only after the man in charge has given his permission. When other cars are placed on the same track, the yellow signal must be moved to the end of the string of cars on that track where it can be plainly seen.

G36 When a train order office is closed during the period authorized by time-table or bulletin, the light in the train order signal will be extinguished.

G37 Excessive use of sand at any point is prohibited and its use must be restricted to actual necessity.

ALL SUBDIVISIONS

X-1 When practicable, locomotive cranes, Jordan spreaders, shovels, pile drivers, and ditching machines, will be placed in trains with the heavy end in the direction the train moves. Trains handling this work equipment and steam derricks must not exceed speed limitations shown below. The indicated maximum speeds must be further reduced on tangents and on curves where track conditions do not justify the specified maximum speeds. When this work equipment is hauled in trains with the heavy end trailing, the speed must be further reduced to insure safe movement. Engine and train crews will make frequent observations of how these machines are riding.

	On Tangent Tracks	On Curves
1st, 2nd, and 3rd Subdivisions.....	35 MPH	25 MPH
4th, 6th, 7th and 8th Subdivisions.....	20 MPH	15 MPH
5th Subdivision	25 MPH	20 MPH

X-2 The speed of passenger trains when handled or helped by Class N-3 engines must not exceed a maximum of 50 MPH; S-1 S-2, and S-3 engines 65 MPH and F-6 engines 75 MPH.

X-3 The speed of all trains or engines passing through turnouts must not exceed 13 miles per hour, except those turnouts laid with long frogs and designated by Special instructions or bulletin where the speed may be increased to 25 miles per hour, unless otherwise authorized.

X3 (A) All spring switches except as indicated below are equipped with facing point locks, permitting maximum permissible speed in the territory involved while moving against the points. The speed must not exceed 25 MPH while moving against the points at the following spring switch. (See Special Instruction G34.)
Marengo.....West Siding Switch

X-5 The RS-12 sign located just east of Plummer Junction, governing westward trains, applies only to trains entering 2nd Subdivision.

X-6 The junction switch at Plummer Junction is equipped with an electric lock. Instructions for operating switch are posted in back of lower door of the electric lock.

X-7 The speed of engines when running backward, either light or handling trains must not exceed 25 MPH on tangent track and 20 MPH on curves.

X-8 Trains handling logs must stop before passing through Bridge 508 at Rover and make inspection of the loads of logs, setting out any which may be spread so they will not clear the bridge.

X-9 A rock slide detector fence approximately 657 feet in length with signals, has been placed in service just east of Tunnel 44 near Rock Lake siding.

The signals are of semaphore type displaying indications in accordance with rules 501A, 501B and 501C Consolidated Code. Two westward signals are located 1077 ft. and 3293 ft. east of Tunnel 44. Two eastward signals are located 360 ft. and 4081 ft. west of Tunnel 44.

These signals are not controlled by track circuit and serve only to check and indicate condition of the slide detector fence.

Trains must be brought to a stop before passing signals displaying a stop indication and proceed at restricted speed through the area protected by slide fence, making sure that track and bridge structures are in a safe condition.

X-10 At St. Maries, Plummer Junction, Manito, and Marengo trains, other than those displaying signals for a following section, may register by register ticket.

X-11 At the following stations, the siding is also used as a house track; the train Dispatcher need not be notified when cars are left on any of these sidings:

- 1st SubdivisionSeabury
- 3rd SubdivisionEwan
- 4th, 5th, 6th, 7th and 8th Subdivision .. All Stations

X-12 S-1 and F-6 engines must not be operated on industry tracks or spurs nor on Lind hole track, St. Maries rip, mill or Milwaukee Lumber spur tracks and wye at Warden.

X-13 The Washington State Law governing movements of trains over railroad crossings at grade is as follows: "Trains shall stop at railroad crossings; all railroads and street railroads operating in this State shall cause their trains and cars to come to a full stop at a distance not greater than 500 ft. before crossing the tracks of another railroad crossing at grade, excepting at crossings where there are established signal towers and signalmen, interlocking plants or gates."

X-14 Ten-minute fuses should be used on First, Second, and Third Subdivisions, and five-minute fuses on other Subdivisions.

X-15 In addition to those designated in the time table, standard clocks are located in Train Dispatcher's office and Round-house office at Spokane.

X-16 The wires on the trolley and transmission line poles and supports carry high voltage. Contact with them either by person or equipment is liable to cause fatal injury or damage to property. **THEY MAY BE HANDLED ONLY BY THOSE WHO HAVE RECEIVED SPECIFIC AUTHORITY TO DO SO.**

If wires are found hanging down or any part of the trolley or transmission system deranged in such a way that a person might come in contact with the wires, the train Dispatcher must be notified from the first point of communication.

If conditions are such that train or equipment is unable to pass without touching the wires, the train Dispatcher must be notified and he will give necessary instructions.

In case of fire, extinguishers filled with carbon tetra-chloride only should be used, if it is possible for the extinguishing liquid to come in contact with the wires.

In case of electric shock, resulting in apparent unconsciousness, application of the Prone Pressure Method of Resuscitation must proceed immediately; the knowledge of this method is required of all persons having duties within the electrified zone.

Freight trainmen will not be required to ride on top of train in electrified territory, unless some real emergency condition exists, which, in the judgment of the conductor of the train, would require special attention from some member of the crew located on top of the car. These instructions are not to be considered as relieving trainmen from the necessity of getting on top of cars while switching operations are carried on when conditions require. However, in no case must trainmen get on top of cars where, on account of lack of clearance, there is danger of contacting any part of energized trolley system.

YARD LIMITS AT

Avery—Extend from 662 ft. east of east switch to 3659 ft. west of west switch.

St. Maries—Extend from 4339 ft. east of Milwaukee Lbr. Co. spur switch to 2427 ft. west of west switch on 1st subdivision, and to 2714 ft. west of west wye switch on 4th, subdivision.

Plummer Jct.—Extends from 4591 ft. east of Jct. switch to 1655 ft. west of west switch on 1st subdivision, and to 2084 ft. west of west wye switch on 2nd subdivision.

Malden—Extend from 3099 ft. east of east switch to 5028 ft. west of west switch.

Manito—Extend from 2445 ft. east of east switch to Union Pacific Junction switch.

Marengo—Extend from 3032 ft. east of east switch to 4976 ft. west of west switch.

Othello—Extend from 3503 ft. east of east switch to 5280 ft. west of west switch.

Moses Lake—Extend from 2000 ft. east of east wye switch to Air-base.

Tiflis—Extend from 500 ft. west of west wye switch on 7th subdivision to 500 ft. east of east wye switch and from east wye switch to 500 ft. west of west siding switch on 8th subdivision.

Clarkia—Extend from 1060 ft. east of east switch to 2000 ft. west of west switch.

Purdue & Bovill—Extend from 800 ft. east of Purdue to 2279 ft. west of west switch Bovill.

Elk River—Extend from 3409 ft. east of east switch to end of track.

Dishman—Extend from 5448 ft. west of west switch to Union Pacific R. R. connection.

McGuires & Grand Jct.—Extend from 2004 ft. east of east switch McGuires to 2010 ft. west of west switch Grand Jct. on 5th. subdivision and to 4342 ft. west of junction switch on 6th. subdivision.

Newport—Extend from 1993 ft. east of east switch to 2010 ft. west of west switch.

Usk & Cusick—Extend from 2010 ft. east of east switch Usk to 1754 ft. west of planer track switch Cusick.

Metaline Falls—Extend from 1946 ft. east of east wye switch to end of track.

Gibbs & Coeur d'Alene—Extend from 2640 ft. east of Gibbs to end of tracks at Coeur d'Alene, including joint track to Rutledge mill.

FREIGHT TONNAGE RATINGS

EASTWARD	OTHELLO TO AVERY	ELK RIVER TO BOVILL	BOVILL TO SHERWIN	CHESTER TO MANITO	MANITO TO PLUMR. JOT.	NEWPORT TO TWEEDIE	COLEMAN TO JENIDA	
N-3	5543	1112	1400	1700	3574	3771	2815	
C-3	3018	615	788	933	1950	2057	1539	
F-5	2708	523	681	813	1735	1832	1362	
F-6	3000			1110	1935			
S-1	4000			1360	2500			
5400 H.P. DIESEL	7400			3000	5500			
WESTWARD	RAMSDELL TO SORBENTO	MARENGO TO HILLOREST	PLUMR. JOT. TO WORLEY	WORLEY TO SPOKANE	SPOKANE TO OHENEY	KEELER TO ELK RIVER	RATHDRUM TO JENIDA	ALDER ORK. TO ROVER
N-3	2815	4500	2815	3771	2806	1112	2815	1400
C-3	1539	2057	1539	2057	2079	615	1539	788
F-5	1462	1832	1462	1832	1853	523	1462	681
F-6	1675	2050	1700	2050	2100			
S-1	1920	3500	1920	2700	2750			
5400 H.P. DIESEL	4600	8400	4600	5600	6000			

Dispatcher may increase or decrease above tonnage ratings as may be necessary.

WEIGHT OF LOCOMOTIVE INCLUDING TENDER

L-2216 tons	N-3370 tons
F-5205 tons	K-1182 tons
C-5189 tons	S-1400 tons
I-5104 tons	F-6327 tons
	DE-5400 H.P.	462 tons
	DE-8000 H.P.	490 tons

SURGEONS MILWAUKEE HOSPITAL ASSOCIATION

Dr. J. F. DePree.....Chief Surgeon.....Seattle
 Dr. H. D. Moseley.....District Surgeon.....St. Maries
 Dr. Carroll Smith.....Oculist.....Spokane
 Dr. R. L. Pohl.....Asst. Oculist.....Spokane

HOSPITALS

St. Maries.....St. Maries Hospital
 Spokane.....(Deaconess Hospital
 {St. Luke's Hospital

Stretchers are located as follows: Avery, St. Joe, St. Maries, Plummer Jct., Rosalia, Malden, Bovill, Elk River, Spokane, Spirit Lake, Lind, Othello.

LOCATION	NAME	TITLE	OFFICE TELEPHONE	RESIDENCE TELEPHONE
St. Maries	Dr. H. D. Moseley	Local Surgeon	119	267
St. Maries	Dr. B. A. Rapp	" "	119	205W1
Tekoa	Dr. C. B. Clizer	" "	15	15X
Rosalia	Dr. L. A. Quaipe	" "	2504	2502
Spokane	Dr. J. M. Finney	" "	Main 6973	Riverside 0797
Spokane	Dr. C. L. Kyle	" "	Main 7744	Broadview 3040
Spokane	Dr. J. M. Nelson	" "	Main 5351	Lakeview 3561
Newport	Dr. R. W. Winston	" "		
Ione	Dr. G. Moulton Richards	" "	5	11
Coeur d'Alene	Dr. J. T. Wood	" "	29X	29
Moses Lake	Dr. D. H. Larson	" "	29W	

SUNDAY & HOLIDAY HOURS AT STATIONS

AveryContinuous
 St. MariesContinuous
 Plummer Jct.Continuous
 MaldenContinuous
 Manito.....12:01 AM to 11:00 AM
 4:00 PM to 11:59 PM
 MarengoContinuous
 OthelloContinuous
 Warden.....12:01 AM to 8:00 AM
 4:00 PM to 11:59 PM
 Lind.....11:00 PM to 7:00 AM

Other Stations Closed.

WATCH INSPECTORS

National Railway Time Service Co.....Chief Inspectors
 55 East Washington Street, Chicago, Ill.
 St. Maries.....H. W. Schumacker
 RosaliaH. Fulner
 Spokane.....408 Riverside Ave., Nelson Jewelry Co.
 MaldenPacific Watch Co.
 Othello.....Pacific Watch Co.
 Seattle.....114 Pike St., Weisfield & Goldberg, Inc.
 Tacoma.....1105 Broadway, A. A. Mierow
 Newport.....A. F. Benson

C. A. OLSON,

R. E. JOINER

A. D. BRUNEAU,

S. B. MCGINN,

Train Dispatchers.

F. B. BEAL,

Chief Dispatcher.

E. D. JEFFERSON,

C. J. SHOOK,

Traveling Engineers and
 Assistant Trainmasters.

D. W. AMICK,

Trainmaster