TAB	LE OF T	RAIN SPEE	EDS
Seconds	Miles	Seconds	Miles
per Mile	per Hour	per Mile	per Hour
45	80	63	57.1
46	78.3	64	56.3
47	76.6	65	55.4
48	75	66	54.5
49	73.5	67	53.7
50	72	68	52.9
51	70.6	69	52.2
52	69.2	70	51.4
53	67.9	75	48
54	66.7	80	45
55	65.5	85	42.4
56	64.3	90	40
57	63.2	100	36
58	62.1	120	30
59	61	144	25
60	60	180	20
61	59	240	15
62	58.1	360	10

55 East	Washington Street, Chicago, Ill.
Othello	Pacific Watch Co.
E sburg	304½ No. Pearl St., Chas. E. Dickson
C. Elum	Dean R. Ireland
Seattle	414 Pike St., Weisfield & Goldberg, Inc.
Seattle	425 Pike St., Corner 5th Ave., H. Raphael
Tacoma	1105 Broadway, A. A. Mierow
Tacoma	
Everett	2934 Colby Ave., O. P. Nelson
Enumclaw	A. C. Melsness
	Wright Jewelers
Hoquiam	Fred Wetzel
Raymond	Roy Doolittle
South Bend	Halver Holte
Bellingham	Milton E. Terry
Port Angeles	Lewie B. Filion
Port Townsend	840 Water St., Walter S. Wisniewski
Longview	1310 Commerce Ave., Friedlander & Sons, Inc.



CHICAGO, MILWAUKEE, ST. PAUL AND PACIFIC RAILROAD CO.

COAST DIVISION

TABLE NO. 35

Taking effect at 12:01 A.M.
Pacific Standard Time

SUNDAY, APRIL 15, 1956

For the government and information of employees only

A. W. HERVIN
Assistant Superintendent

D. P. VALENTINE
Superintendent of Transportation

C. A. NUMMERDOR
General Superintendent of Transportation

J. T. HANSEN
Superintendent

J. H. STEWART General Manager

2		WE	STV	VAR	D		FIRST SUBDI	VISIO	NC	EAST	WARD		
SECOND CLASS	FIRST	CLASS	Capac	city in			Time Table			9 IT	FIRST	CLASS	SECOND CLASS
263		15			Telegraph calls	from .	No. 35	Distance from Cle Elum	See Rule 6-A	Office Hours Also see page 12	16		264
Time Freight		Passenger	Sid-	Other	egrap	Distance Othello	APRIL 15, 1956	tance		•	Passenger		Time Freight
Daily	Α	Daily	ings	tracks	Tel	Oth	STATIONS	C Dis			Daily		Daily
L 12.15PM	v - In the	L 3.55AM		Yard	so	0.0	OTHELLO 5.5	98.9	BHKOPR TWX	Continuous	As 8.05PM	100	A 5.00PM
12.25		4.00	68			5.5	ANSON	93.4	P	No Office	7.54		4.15
12.31	27 - 22 - 24 - 27	4.05	113	11		9.2	TAUNTON	89.7	P	No Office	7.50		4.05
12.41		4.14	60	18		15.0	CORFU 9.7	83.9	P	No Office	7.41	100 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	3.45
12.55	5 68 1	4.25	111	10	=	24.7	SMYRNA 	74.2	P	No Office	7.30	5,	3.20
1.05		4.32		50		31.2	JERICHO	67.7	P	No Office	7.24	3	3.00
1.20	"	4.43	113	Yard	вv	37.8	BEVERLY	61.1	ВКРХУ	12.01AM to 4.00PM Except Sat. & Sun.	7.13		2.40
			63 - 54 F.B.C		in the state of th	38.8	BEVERLY JCT.	60.1	JPX	No Office	1	-	
264 1 - 50	E =	4.58	113	74		44.0	DORIS5.6	54.9	P	No Office	7.01	ï	263 1 · 5 C
2.10		5.09	60	5		49.6	RYE3.3	49.3	P	No Office	6.50		1.3
2.25		5.17	72			52.9	CHEVIOT	46.0	P	No Office	6.43	101 12 12	1.15
2.45		5.25	103	20		56.6	BOYLSTON	42.3	P	No Office	6.35		1.00
3.15				17		64.9	EAST KITTITAS	34.0	P	No Offi∞	va		12.25
3.25	1 5 67	5.46	113	85	KY	67.2	KITTITAS	31.7	KPWXY	8.00 AM to 5.00 PM Except Sun. & Mon.	6.19	Ÿ	12.20M
		0.		14		70.1	REGAL .	28.8		No Office			
3.35	T 1	s 5.56	91	48	NB	73.6	ELLENSBURG	25.3	P	8.00 AM to 5.00 PM Except Sat. & Sun,	∗ 6.12		11.59
3.45		6.06	60	27	0	80.5	THORP	18.4	P	No Office	6.01		11.50
4.00		6.18	109	8		88.9	HORLICK	10.0	P	No Office	5.50		11.30
A 4.25PM		A 6.35₩		Yard	СМ	98.9	CLE ELUM	0.0	BKPRWX	Continuous	L 5.38%		L 11.05AM

Passenger trains must not exceed 79 MPH. Other trains 55 MPH. See Special Instructions G-33.

EASTWARD TRAINS ARE SUPERIOR TO WESTWARD TRAINS OF THE SAME CLASS

Automatic Block System is in use between Othello and Cle Elum.

At Beverly Jct. the normal position of junction switch is for the First Subdivision.

Mountain grade extends from Beverly Jct. to East switch at Kittitas.

Trains must not meet or pass at Jericho.

	2	WESTV	VAR	D	1	SI	ECOND SUBDIVI	SIO	N	EAST	WARD	* -tu	3
SECOND CLASS	FIRST	CLASS		eity in			Time Table	en E			FIRST	CLASS	SECOND CLASS
263		15		ars .	ph calls	Distance from Cle Elum	No. 35	Distance from Scattlo	See Rule 6-A	Office Hours Also see page 12	16	_ 6.2-6	264
Time Freight		Passenger	Sid-	Other	Telegraph	stanc e Elu	APRIL 15, 1956	stane	Ē #	n	Passenger		Time Freight
Daily		Daily	ings	tracks	Te	ฉีอั	STATIONS	.5 %	an .	- F -	Daily		Daily
L 4.40PM		L 6.35M	1	Yard	CM	0.0	CLE ELUM	89.9	BKPRWX	Continuous	As 5.38PM		A 10.35W
16 5.23	1 2 >	6.49	106	34		11.6	EASTON 8.5	78.3	PVY	No Office	263 5 . 23	41=2=	10.00
5.43		7.01	70	15		20.1	WHITTIER 8.9	69.8	P W 4 Mi. West	No Office	5.11		9.40
6.03		7.14	98	106	HY	29.0	HYAK	60.9	PX	No Office	5.00		9.20
6.13		7.21	85	15		31.6	ROCKDALE 5.1	58.3	PWX	No Office	4.54		9.05
6.28		7.32	69			36.7	BANDERA 5,3	53.2	P	No Office	4.44		8.50
6.44		7.44	56	12		42.0	GARCIA	47.9	P	No Office	4.33		8.35
6.59		7.55	101	21		46.5	RAGNAR	43.4	P	No Office	4.24		8.20
7.13	=100	264 8.06	135	395	мч	50.8	CEDAR FALLS	39.1	BJKOPW XYZ	6.00 AM to 2.00 PM 8.00 PM to 4.00 AM Except Sat. & Sun.	4.16	V/S1 =	15 8.06
7.22		8.13				54.8	BAGLEY JCT.	35.1	JP	No Office	4.11		6.54
7.24		8.14	59			55.6	BARNESTON	34.3	P	No Office	4.10		6.51
7.32		8.21	115	20		59.5	TRUDE	30.4	P	No Office	4.04		6.35
7.41		8.28	60	18		64.4	NOBLE	25.5	P	No Office	3.58		6.15
A 7.48PM		A 8.35	79	14	MV	67.8	MAPLE VALLEY	22.1	JPRVX	Continuous	L 3.53M		L 6.004
8.08	500g e 11	8.53		154	RN	78.1	(N. P. Crossing) RENTON	11.8	Р	100 H 9	3.38		5.25
8.13		8.58		Yard	ві	80.5	BLACK RIVER (U. P. Crossing)	9.4	IJPRVX	V = 2	3.31		5.15
8.25			111	336		84.8	VAN ASSELT 1,7-	5.1	P	Via. P. C. R. R.			4.45
a a? E	= = 4 ₂	9.13				86.5	ARGO (U. P. Crossing) (N. P. Crossing)	3.4	IP	SET TO SE	3.23	⁷ am a ass	11 = 2
1						88.2	SPOKANE STREET TOWER	0.7		Via. P. C. R. R.			
A 9.30 PM						88.9	STACY STREET YARD	0.0	BKOPTVXZ			12 350 0 700	L 4.00 AM
100,000		A 9.30 AM		Yard	ow	89.9	SEATTLE	0.0	P	Via. U. P. R. R.	L 3.15 PM		

Passenger trains must not exceed a maximum speed of 70 MPH. Other trains 50 MPH. See Special Instructions G-33.

EASTWARD TRAINS ARE SUPERIOR TO WESTWARD TRAINS OF THE SAME CLASS

INDUSTRIAL TRACKS NOT SHOWN AS STATIONS

13	Name	Miles	Direction	Station
Landsburg		2.3	LEast	Noble

This time-table confers no authority between Maple Valley and Seattle. Between Maple Valley and Spokane St. tower, Pacific Coast time-table and rules govern. Between Argo and Union Passenger Station Seattle, Union Pacific R. R. time-table and rules govern.

Automatic Block System is in use between Cle Elum and Maple Valley.

Mountain grade extends from Cedar Falls depot to one mile west of Hyak.

Headlight and marker lamps must be lighted while passing through Snoqualmie Tunnel No. 50 between Hyak and Rockdale.

4														
	SECONE	CLASS	1 1	(1)	FIRST	CLASS						T. T. I.I.		
263	83	93	81	. V.	51	15	53	Capacity	in cars		a	Time Table No. 35		
Time Freight	U. P. R. R. Time Freight 690	Way Freight	U. P. R. R. Time Freight 692		U. P. R. R. Passenger 458	Passenger	U. P. R. R. Passenger 402			Telegraph calls	Distance from Scattle	APRIL 15, 1956		
Daily	Daily	Daily Except Sunday	Daily		Daily	Daily	Daily	Sidings	Other tracks	Teleg	Dist	STATIONS		
						L 9.45AM				ow	0.0	SEATTLE		
3 0	S	L 2.00PM							Yard		0.0	STACY ST. YARD		
		2.05									0.7	SPOKANE ST. TOWER		
=	- 0	2.10		В		9,53					3.4	ARGO (U. P. Crossing) (N. P. Crossing)		
		2.15						111	336		5.1	VAN ASSELT		
L 8.35PM	L 6.15PM	16 L 2.45PM	L 11.15PM		L 5.15PM	L 10.01AM	L 12.01AM		Yard	ві	9.4	BLACK RIVER (N. P. Crossing)		
8.45	6.35	3.05	11.27		f 5.23	10.09	f 12.10	95	112	ĸ	16.3	KENT5.0		
8.52	6.45	3.25	11.36	-100	f 5.29	f 10.15	f 12.18	90	134	BR	21.3	AUBURN 4.6		
8.57	6.55	3.40	11.44		5.35	- 18	12.26	64		200	25.9	BENROY		
9.02	7.05	82 3.45 4.45	11.50	۸	f 5.40	94 1 O. 24	1 12.30	91	50	υx	28.4	SUMNER		
9.05	7.15	4.50	11.55	3	5.44	10.27	12.34	59	22	II a	30.1	PUYALLUP		
9.15	A 7.30PM	5.00	A 12.10AM	Fi	A 5.50PM	10.33	A 12.43M	79		JN	35.6	TACOMA JCT. East End Double Track		
			X Section		70 0 C	10,39					37.1	(G.N., U.P. & N.P. Crossing) DEPOT SWITCH		
						A 10.45M					37.6	TACOMA		
A 9.30PM	fire terms	A 5.15™			F 114				Yard	FD	37.6	West End Double Track TIDE FLATS YARD		

Passenger trains must not exceed a maximum speed of 79 MPH. Other trains 55 MPH. See Special Instructions G-33.

EASTWARD TRAINS ARE SUPERIOR TO WESTWARD TRAINS OF THE SAME CLASS

INDUSTRIAL T	RACKS NOT	SHOWN AS	STATIONS
Name	Miles	Direction	Station
Thomas		West.	Kent Puvallup

This time-table confers no authority between Black River and Seattle. Between Black River and Spokane St. tower Pacific Coast R. R. time-table and rules govern. Between Argo and Union Passenger Station Seattle, Union Pacific R. R. time-table and rules govern.

Automatic Block System is in use between Black River and Tacoma Jct.

No. 15 will stop on signal at Auburn to detrain revenue passengers from the Twin Cities or points beyond.

No. 51 will stop on signal Kent, Auburn and Sumner to receive revenue passengers for Vancouver, Wash., and beyond.

No. 53 will stop on signal at Kent for revenue passengers for Tacoma or points beyond.

Double track is in use between Tacoma Ict. and Tide Fig. Yard. Trains and engines using these tracks must use the right hand track as prescribed by Rule D-151. Crossover movements and movements against the current traffic between Tacoma Ict. and Depot Switch must be properly protected and all trains and engines must move at restricted speed. Maximum speed must not exceed 15 MPH.

Single track is in use between Depot Switch and Tacoma. Normal position for the switch at Depot Switch is for movement to Tide Flats yard.

At Tacoma Jct. the normal position of junction switch is for the Seventh Subdivision.

The following tracks are wired: 6, 7, 8, 12 and east end of track 13, Seattle Union Station, and first three cross-over tracks east of station; Northern Pacific Railway Co. interchange track, Argo, and tracks 1 and 8 Van Asselt.

At Auburn, an auxiliary siding with a capacity of 58 cars is located west of the depot. Rule 5 applies at the siding located east of the depot.

See additional Special Instructions for Third Subdivision on Page 5.

图 (6,)			THIRD SU	JBDIVI:	SION	A LF	AT ANY	EASTWA	RI)		No.		5
Time Table		11	8 2 8	- <u>- 25</u> - 35 - 35	FIRST	CL/	ASS				SECOND	CLASS		a 2 a
No. 35	g		7 = 2 7 = 8	54	52		16			84	264	94		82
APRIL 15, 1956 STATIONS	Distance from Tacoma	See Rule 6-A	Office Hours Also see page 12	U. P. R. R. Passenger 401	U. P. R. R. Passenger 457	P	assenger	g a		J. P. R. R. ime Freight 691	Time Freight	Way Freight	U. Tir	P. R. R. me Freight 681
SIATIONS	ų t	esm ^X e	E i a	Daily	Daily		Daily			Daily	Daily	Daily Except Sunday		Daily
SEATTLE	37.6	P	Via U. P. R. R.	-		A	3.00PM							
STACY ST. YARD	36.6	BKOPT VXZ	0 ³	30 B						5.20		A 12.50PM	1	1 25 3 4
SPOKANE ST. TOWER	35.9	531	Via P. C. R. R.									12.45		3 300 00
ARGO (U. P. Crossing) (N. P. Crossing)	34.2	IP	Via P. C. R. R.	** b b	= =		2.48	1 80 T D 8		i		12.35		- 12 -
VAN ASSELT	32.5	P	in the second						T			12.30		
BLACK RIVER (N. P. Crossing)	28.2	IJPRVXY	Continuous	A 5.50AN	A 12.42M	A	93 2.40PM	58 -41	A	4.10A	A 4.30M	A 12.20PM	A	4.40
KENT 5.0	21.3	PX	8.00 AM to 5.00 PM Except Sat. & Sun.	1 5.39	12.34		2.31			3.56	4.19	12.05№		4.27
AUBURN	16.3	PX	7.45 AM to 5.00 PM Except Sat. & Sun.	f 5.29	12.28	f	2.25			3.45	4.09	11.30		4.17
BENROY	11.7	P	No Office	5.21	12.23				Г	3.35	3.59	11.05		4.07
SUMNER	9.2	PVX	7.00 AM to 11.00 PM Except Sat. & Sun.	1 5.16	12.20		2.17	×		3.28	3.54	15 11.00 10.00		93 4.01
PUYALLUP	7.5	P	No Office	5.11	12.17		2.14		1	3.23	3.50	9.55		3.57
TACOMA JCT. East End Double Track	2.0	JKPRVX	Continuous	L 5.02	L 12.11PM		2.08		L	3.104	3.40	9.40	L	3.45
(G.N., U. P. & N. P. Crossing) DEPOT SWITCH	0.5	MPX	No Office	ar -	121		2.02	7 1 >			111 82 9	2		1. 1
TACOMA	0.0	BPX	No Office		4	L	2.00PM							

Passenger trains must not exceed a maximum speed of 79 MPH. Other trains 55 MPH. See Special Instructions G-33.

EASTWARD TRAINS ARE SUPERIOR TO WESTWARD TRAINS OF THE SAME CLASS

UNION PACIFIC RR—BLACK RIVER WHISTLE SIGNALS:

BKOPRT

8.00 AM to 5.00 PM

VWXYZ Except Sat. & Sun.

West End Double Track

TIDE FLATS YARD

NORTHERN PACIFIC RR - BLACK RIVER

Trains approaching interlocking, desiring to use main track to

Tacoma or Seattle will give one long sound of the whistle. Trains desiring to use wye, will give four long sounds of the whistle.

L 3.30M L 9.30M

No. 16 will stop on signal at Auburn for revenue passengers to the Twin Cities or points beyond.

Rule 83 (B) does not apply at Tacoma and Tide Flats Yard. Eastward trains will get Clearance Form A at Tacoma Jct.

See additional Special Instructions for Third Subdivision on Page 4.

6		WES	STWA	ARD	1 - X	FOURTH SUBDIVISI	FOURTH SUBDIVISION			EASTWARD				
H H H	** B	Capacity in cars			E.	Time Table No. 35	from	\$ \$						
		Sidings	Other tracks	Telegraph calls	Distance from Beyerly Jct.	APRIL 15, 1956 STATIONS	Distance fr Hanford	See Rule 6-A	Office Hours Also see page 12					
	L		(6)		0.0	BEVERLY JUNCTION	20.79	JPX	No Office	A	7.			
1.0 1.0 T		21			4.0	LEVERING	16.79		No Office					
		60			14.4	PRIEST RAPIDS	6.39	PX	No Office					
	A		11 (20.79	HANFORD	0.0	х	No Office	L	9.			
1 37 BST108 - 1	II W I DAGS		NRDER Ø		¥	HANFORD YARD	е	PVXY						

Trains must not exceed a maximum speed of 30 MPH, except from one mile west of Levering to 4 miles west of Priest Rapids 20 MPH.

Rule 83 (B) does not apply at Hanford or Beverly Jct.

EASTWARD TRAINS ARE SUPERIOR TO WESTWARD TRAINS OF THE SAME CLASS

1. "H = "		WES	TWA	RD		FIFTH SUBDIVISION EASTWARD							
	19 34 E B	Capacit	y in cars	# 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	Ē	Time Table No. 35	Ø	18 gg 18 gg 18 9 80 18		7 0			
		Sidings	Other tracks	Telegraph calls	Distance from Cedar Falls	APRIL 15, 1956 STATIONS	Distance from Everett	See Rule 6-A	Office Hours Also see page 12				
	L	7. 15	Yard	МҮ	0.0	CEDAR FALLS	54.6	BJKOPRWXYZ	6.00 AM to 2.00 PM 8.00 PM to 4.00 AM Except Sat. & Sun.	A			
(I#M S B	e es iyy		×		5.9	TANNER (N. P. Crossing)	48.7	P	No Office		b > 555		
		37	19		8.0	NORTH BEND	46.6	PX	No Office	1			
			28	Q	11.2	SNOQUALMIE FALLS	43.4	PX	8.00 AM to 5.00 PM Except Sat. & Sun.	E SECTION	2 20		
		19			12.3	TOKUL	42.3		No Office				
		8			16.9	FALL CITY	37.7	P	No Office				
	[6]	35	20		22.3	CARNATION 8.7	32.3	P	No Office				
	N I	29	20	St 32 9653	31.0	DUVALL 5.6-	23.6	Р	No Office				
			10		36.6	HIGH ROCK	18.0		No Office		1 Min 20 12		
	A		,		40.2	MONROE JCT.	14.4	JPVX	No Office	L			
e de la companya de La companya de la companya de l				RO	40.5	MONROE 6.9	14.1		Sec. 101				
10					47.4	SNOHOMISH	7.2		Via G. N. Ry.				
					53.2	LOWELL 0.5-	1.4	JVX					
			150		53.7	BELT YARD	1.9	JVXZ	Via. N. P. Ry.	5 3			
	· -				53.2	LOWELL 1.4	1.4	JVX	2010 - 100 DE 100 D 100 DE 100 DE				
	A		Yard	RT	54.6	EVERETT	0.0	BKOPRX	8.00 AM to 5.00 PM Except Sat. & Sun.	L			

Trains must not exceed a maximum speed of 30 MPH. between Cedar Falls and Snoqualmie Falls and between 2 mi. east of Carnation and Monroe Jct., 15 MPH. between Snoqualmie Falls and 2 mi. east of Carnation.

Rule 83 (B) does not apply at Monroe Jct. Eastward trains will obtain clearance Form A at Monroe.

EASTWARD TRAINS ARE SUPERIOR TO WESTWARD TRAINS OF THE SAME CLASS

This time-table confers no authority between Monroe Jct. and Belt Yard. Between Monroe Jct. and Lowell, Great Northern Ry. Co. time-table and rules govern. Between Lowell and Belt Yard, Northern Pacific Ry. Co. time-table and rules govern.

INDUSTRIAL TR	ACKS NOT	SHOWN AS	STATIONS
Name	Miles	Direction	Station
Stuart	4.1	LWest	Carnation

in the second	Y	VEST	VARI	D	16	SIXTH SUBDIVISION	E	1	7		
		Capacity	y in cars			Time Table No. 35				1,487	9
		Sidings	Other tracks	Telegraph calls	Distance from Bagley Jct.	APRIL 15, 1956 STATIONS	Distance from Enumelaw	See Rule 6-A	Office Hours Also see page 12		
1 Vi 1722	r	· ·	d		0.0	BAGLEY JCT.	16.1	JPRX	No Office	A	
KYD RYw		9.7	40		2.3	SELLECK (Pacific States Lumber Co. Crossing)	13.8	PX	No Office		1100
					4.6	DURHAM	11.5		No Office		
					5.3	KANASKAT JCT.	10.8	JPV	No Office		
		11			7.4	2.1 PALMER	8.7		No Office		
			10		8.6	BAYNE JCT.	7.5	JPX	No Office	W COMMISSION	
			20	s.l.	8.8		7.3	x	No Office		
			97		9.9	CUMBERLAND	6.2		No Office		
		15		3	10.7	NACO	5.4		No Office		
			62		12.7	VEAZIE	3.4	P	No Office	e 22	
	A *		90	CW	16.1	3.4	0.0	BOPRXY	8.00 AM to 5.00 PM Except Sat. & Sun.	L	

Trains must not exceed a maximum speed of 15 MPH. between Bagley Jct. and Bayne Jct. and 25 MPH. between Bayne Jct. and Enumclaw.

At Bayne Jct. and Kanaskat Jct. normal position of junction switch is for joint track between Bayne Jct. and Kanaskat Jct.

Rule 83(B) does not apply at Bagley Jct., Kanaskat Jct. or Bayne Jct.

A derail is located 330 ft. west of junction switch at Bagley Jct.

EASTWARD TRAINS ARE SUPERIOR TO WESTWARD TRAINS OF THE SAME CLASS

- 1	WEST	WAF	RD	и Уб		\$150 c)	EIGHTH SUBDIVISION				EASTWARD			
	1		Capacity	y in cars	WE .5 10	£.¥	Time Table No. 35		r Sag		x = -			
			Sidings	Other tracks	Telegraph calls	Distance from Park Jct.	APRIL 15, 1956 STATIONS	Distance from Ashford	See Rule 6-A	Office Hours Also see page 12				
	L	*	35		b EV	0,0	PARK JCT.	5.5	JPXY	No Office	A			
				67		3.5	NATIONAL	2.0		No Office				
	A	n _e en å e ⁿ er		80	2 2 2 2	5.5	ASHFORD	0.0	x	No Office	L			

Trains must not exceed a maximum speed of 20 MPH.

Rule 83(B) does not apply at Park Jct. or Ashford.

At Park Ict. trains and engines should proceed expecting to find cars on siding and on main track west from west switch of siding on Eighth Subdivision.

EASTWARD TRAINS ARE SUPERIOR TO WESTWARD TRAINS OF THE SAME CLASS

8	WES	STWARD	1		*		SEVENTH SU	JBD1	VISION	ē*	5 25 B F	EASTW	/ARD
5	ECOND CLAS	55		į.	ı		Time Table					THIRD CLASS	l
563	791	863	Capacit	y in cars	elle:	8	No. 35	g g	the and the see to	Office Hours	864	792	564
Time Freight	Way Freight	Time Freight	0:3:	Other	qde.	ne fr	APRIL 15, 1956	l Se fr	See Rule 6-A	Also see page 12	Time Freight	Way Freight	Time Freight
Daily Except Saturday	Daily Except Sunday	Daily Except Saturday	Sidings	tracks	Telegraph calls	Distance from Tacoma Jet.	STATIONS	Distance from Morton			Daily Except Sunday	Daily Except Monday	Daily Except Sunday
564 L 10.35PM	L 7.30AM	L 5.00AM	79		JN	0.0	TACOMA JCT.	66.5	JKPRVX	Continuous	A 10.00AM	A 1.00PM	563 A 10.35
11.30	7.50	5.45	63	182		5.3	HILLSDALE	61.2	PX	No Office	9.40	12.40	10.15
11.50	8.15	6.00	84			9.0	ALLISON	57.5	P	No Office	9.30	12.20	10.05
A 11.59PM	8.27	A 6.15AM	32	33		13.2	FREDERICKSON	53.3	JPRXY	No Office	L 9.20M	12.05PM	L 9.55
	8.55		72	3,00		19.8	THRIFT	46.7	P	No Office		11.35	
	9.08		30			23.0	TANWAX	43.5	P	No Office		11.25	
	9.20					25.0	KAPOWSIN	41.5	P	No Office		10.40	The Title of the State of the S
= 1	792 1 0 0 0 1 0 4 5	Ξ	92			33.6	EATONVILLE JUNCTION	32.9	JPXY	No Office	п	791 1 O . O O 8 . 4 5	-
	10.30		82	30		34.6	EATONVILLE	33.9	PX	No Office		9.45	
8	11.15		92	20		41.5	NEW RELIANCE	25.0	PX	No Office		8.15	— (§).
00	11.30	4	16	30	BE	46.5	ELBE	20.0	P	8.00 AM to 5.00 PM Except Sat. & Sun.		7.45	
	11.40		35			48.9	PARK JCT.	17.6	JPXY	No Office		7.20	
п	12.45PM		27	200	D	53.0	(Log Co. Crossing) MINERAL	13.5	MPX	8.00 AM to 5.00 PM Except Sat. & Sun.		7.00	
	12.59		54	42		57.2	DIVIDE	9.3	PX	No Office		6.45	emman somes some
A CANADA	1.20	6	15		3.50	64.4	COAL CANYON	2.1	P	No Office		6.10	
	A 1.30PM		60	155	MN	66.5	MORTON	0.0	BKRPXY	6.00 AM to 10.00 PM Except Sat. & Sun.	8	L 6.00A	

Trains must not exceed a maximum speed of 30 MPH.

EASTWARD TRAINS ARE SUPERIOR TO WESTWARD TRAINS OF THE SAME CLASS

Automatic Block System is in use between Hillsdale and Tacoma Jct.

Rule 83(B) does not apply at Frederickson.

At Park Jct. trains and engines should proceed expecting to find cars on siding and on main track west from west switch of siding on Eighth Subdivision.

INDUSTRIAL TRACKS NOT SHOWN AS STATIONS

Name	Miles	Direction	Station
Midland	1.5	LEast	Allison
Columbia Powder Co	0.7	West	Frederickson
Clay City Spur	8.2	East	Eatonville Jct.
Nineteen Creek	1.9	East	Coal Canyon

At Eatonville Jct. and Park Jct. the normal position of junction switch is for the Seventh Subdivision.

At Frederickson the normal position of junction switch is for the Ninth Subdivision.

	***	STW				NINTH SUBDIVISION	and the second	EA	STWARD		9
SECONI	CLASS	Capacity	r in sees			Time Table No. 35	2 2	* * * * * * * * * * * * * * * * * * *	=	THIRD	CLASS
563	863	Capacit	y in cars	e e	rom on	APRIL 15, 1956	from	See Rule 6-A	Office Hours	864	564
Time Freight	Time Freight	Sidings	Other tracks	raph	nce f ricks	STATIONS	nce fr	0-д	Also see page 12	Time Freight	Time Freigh
Daily Except Saturday	Daily Except Saturday	Diame.	v.acab	Telegraph calls	Distance from Frederickson	JANUARO .	Distance fre		n 2 j 2 2 0 20	Daily Except Sunday	Daily Except Sunda
11.59™	L 6.15AM	34	33	SJ	0.0	FREDERICKSON	95.2	JPRXY	No Office	л 9.20 ^м	A 9.55
			19		3.4	LOVELAND	91.8		No Office		
12.204	6.30	70	30-7-5-30		8.0	GREENDALE 7.8	87.2	P	No Office	9.04	9.38
12.45	6.45	20	50		15.8	McKENNA 7.6	79.4	P	No Office	8.48	9.22
1.01	7.00	33	12		23.4	RAINIER	71.8	P	No Office	8.32	9.06
201				2.20	26.3	(Weyerbaeuser Timber Co. Crossing)	68.9	М			1
1.15	7.10		85		28.9	SKOOKUMCHUCK	66.3	11	No Office	8.21	8.55
1.20	7.14			JC	30.0	WESTERN JCT.	65.2	JVP	6.30 AM to 3.30 PM Except Sat. & Sun.	8.18	8.50
1.30	7.18	30			31.2	OFFUT LAKE	64.0	P	No Office	8.15	8.45
MAOO.	7.30	30	39	14	37.2	MAYTOWN	58.0	JPRX	No Office	8.00	L 8.30
9 90	864 7.45	51	3 H = 3		44.6	ESSEX 5.0	50.6	P	No Office	863 7.45	
	= a	Editor		-	49.6	(N. P. Crossing) (U. P. Crossing) BLAKESLEE JCT.	45.6	MX		= 5	
	8.00	40	36	CN	50.9	CENTRALIA	44.3	PXZ	8.00 AM to 5.00 PM Except Sat. & Sun.	7.30	
					54.2	(3 N. P. Crossings)	41.0	М			
H _{27/202}	8.15	54	100	СН	54.6	CHEHALIS	40.6	KMPRVX	6.00 AM to 10.00 PM Except Sat. & Sun.	7.15	
	A 8.30AM	II a		JO.	55.6	(N. P. Crossing) CHEHALIS JCT. 39.6	39.6	IJMPVX	7.00 AM to 4.00 PM Except Sat. & Sun.	L 7.004	i =
11 93	A 11.45AM				95.2	LONGVIEW	0.0	s 2, 2	Via N. P. Ry.	L 4.30AM	

Trains must not exceed a maximum speed of 35 MPH. between Frederickson and Western Jct., 40 MPH. between Western Jct. and M.P. 16, 2 mi. west of Centralia, 15 MPH. M.P. 16 and Chehalis Jct.

EASTWARD TRAINS ARE SUPERIOR TO WESTWARD TRAINS OF THE SAME CLASS

This time-table confers no authority between Chehalis Jct. and Longview, Northern Pacific Railway Co.'s time-table and rules govern.

Rule 83(B) does not apply to eastward trains at Chehalis Jct.
At Frederickson the normal position of junction switch is for the
Ninth Subdivision.

Rule 83(B) does not apply at Frederickson and Maytown.

At Maytown the normal position of junction switch is for the Ninth Subdivision.

At Skookumchuck, trains will be permitted to move on Weyerhaeuser Timber Company's tracks between the hours of 9 P. M. and 6 A. M., for switching purposes only. Such movements must be protected as prescribed by Rule 99.

	INDUSTRIAL TR	ACKS NOT	SHOWN AS	STAT	ONS
	Name	Miles	Direction		Station
UPCO		2.8	West	Offut	Lake

10	W	ESTW	'ARD			TENTH SUBDIVISION	T V	EAS	TWARD	- 971 - 1	STORY KE
SECON	CLASS				ī	Time Table No. 35	8 90 ×			THIRD	CLASS
563	E1 85	Capacity	y in cars		from	APRIL 15, 1956	from	See Rule	Office Hours	1.5	564
Time Freight		-	Other	aph	ee fre	STATIONS	an an	6-A	Also see page 12 -		Time Freight
Daily Except Sunday		- Sidings	tracks	Telegraph calls	Distance fa Maytown	SIAIIONS	Distance Hoquiam			-	Daily Except Sunday
L 2.00M	= =	30	39		0.0	MAYTOWN	56.6	JPRX	No Office	eu s	A 8.30PM
2.30		F 1	7		9.4	ROCHESTER (N. P. Crossing)	47.2	3	No Office		8.05
A 2.40AM	57				11.3	HELSING JCT.	45.3	JVR	No Office	10.70 110 10 10 10 10 10 10 10 10 10 10 10 1	F 8.00M
5.15					53.0	ABERDEEN	3.6	P	Via U. P. Ry.		5.20
A 5.45AM			7	-	56.6	HOQUIAM	0.0	P	Via N. P. Ry.		L 5.00PM

Trains must not exceed a maximum speed of 30 MPH.

EASTWARD TRAINS ARE SUPERIOR TO WESTWARD TRAINS OF THE SAME CLASS

This time-table confers no authority between Helsing Jct. and Hoquiam. Between Helsing Jct. and Aberdeen. Union Pacific Railroad Co. time-table and rules govern. Between Aberdeen and Hoquiam. Northern Pacific Railway Co. time-table and rules govern.

Rule 83(B) does not apply at Maytown and Helsing Jct.

At Maytown the normal position of junction switch is for the Ninth Subdivision.

At Helsing Ict, the normal position of junction switch is for the Union Pacific Railroad Co. track.

THIRD	CLASS	*-	× 8 1 5		9 1589	Time Table No. 35				THIRD	CLASS
963		Capacity	y in cars		됨	APRIL 15, 1956	g g		Office Hours Also see page 12	10000	964
Way Freight		~	Other	ųds.	lis Je		nce fro	See Rule 6-A	Mark 18 marks	2	Way Freight
Daily Except Sunday		Siding	tracks	Telegraph calls	Distance from Chebalis Jet.	STATIONS	Distance from Raymond				Daily Except Sunday
	18				0.0	CHEHALIS JCT.	46.2	IJMPVX	Via N. P. Ry.		747
L 1.40PM					16.9	DRYAD JCT.	29.3	JRVX	No Office		A 9.45A
1.45		7			17.9	DOTY 5.2	28.3	P	No Office		9.
2.00			60	2	23.1	HILDA 8.5	23.1	X	No Office		9.20
2.30		10			31.6	MACPHAIL	14.6	х	No Office		8.55
2.40		27			34.9	suțico	11.3	х	No Office		8.45
2.45					36.5	FIRDALE	9.7	PX	No Office		8.30
A 3.15PM		20	140	RD	46.2	RAYMOND (N. P. Crossing)	0.0	BKOPRVXY	8.00 AM to 5.00 PM Except Sunday	jā.	L 8.01A

Trains must not exceed a maximum speed of 20 MPH. between Dryad Jct. and MacPhail. 15 MPH. between MacPhail and Firdale, 20 MPH. between Firdale and Raymond.

EASTWARD TRAINS ARE SUPERIOR TO WESTWARD TRAINS OF THE SAME CLASS

This time-table confers no authority between Chehalis Jct. and Dryad Jct., Northern Pacific Railway Co.'s time-table and rules govern.

Rule 83(B) does not apply at Dryad Jct.

es	W	ESTW	/ARD	Ĺ	6.8	TWELFTH SUBDIVISION		, n ²	EASTWARD		11
27 37% 38		Capacity	v in cars			Time Table No. 35	200		a 2 2 3		
Ē		- Jup			B T	APRIL 15, 1956	ā	See Rule 6-A	000	4.0	7 5
	E 0	- Sidings	Other tracks	Tolegraph calls	Distance from Bellingham	STATIONS	Distance from Glacier		Office Hours Also see page 12	2 36 1 2	
	L		Yard	ВМ	0.0	BELLINGHAM (3 G. N. Crossings)	46.8	BKMOPRTVXZ	8.00 AM to 10.00 PM Except Sat. & Sun.	A	an in Y
	ES.	23			4.0	CORNWALL 7.4	42.8		No Office		
		38			11.4	WAHL 1.5	35.4	P	No Office		
			7		12.9	GOSHEN	33.9		No Office		
	The same of the	23			17.0	STRANDELL 0.8	29.8	PAR PROPRIES I NAME OF THE PARTY.	No Office		
The same of the sa			30		17.8	EVERSON	29.0	PX	No Office		
		25			19.3	HAMPTON	27.5	JPRXY	No Office		
	77	17			22.2	CLEARBROOK	24.6		No Office		
B U 2	WI St.		Yard	SU	25.1	2.9 SUMAS	21.7	PVXY	7.00 AM to 4.00 PM Except Sat. & Sun.		7 2 374
	- 80				26.1	(N. P. Crossing)	20.7		No Office		
		21			31.9	HILLTOP	14.9		No Office		1000.000
	A 40 40 4 4	15			32.7	COLUMBIA	14.1	11 12 12	No Office		
					33.4	LIMESTONE JCT.	13.4	Y	No Office		
, , , t		12			36.3	KENDALL	10.5		No Office		
		15			39.5	MAPLE FALLS	7.3		No Office		
2 25	A	22	55	1 8	46.8	7.3- GLACIER	0.0	Y	No Office	L	

Trains must not exceed a maximum speed of 25 MPH.

EASTWARD TRAINS ARE SUPERIOR TO WESTWARD TRAINS OF THE SAME CLASS

INDUSTRIAL TRA	CKS NOT	SHOWN AS	STATIONS
Name	Miles	Direction	Station
Lind Spur	2.7	West	Bellingham
Cement Spur	3.3	West	Bellingham
	3.2	West	Cornwall
Jacobs	0.33	East	Hilltop
Boulder Creek Spur	2.0	West	Maple Falls
Mt. Baker Mill Co		East	Glacier

A derail is located on main track west of west wye switch at Glacier.

All trains must stop before crossing Guide Meridian St. at Cornwall except westward trains may proceed at restricted speed if engineer deems it safe to do so.

Rule 83(B) does not apply at Glacier.

WI	ESTWARD			6 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	THIRTEENTH SUBDIV	THIRTEENTH SUBDIVISION EASTWARD						
	Capacit	y in cars			Time Table No. 35		= 1			Т		
	Sidings	Other tracks	Telegraph calls	Distance from Hampton	APRIL 15, 1956 STATIONS	Distance from Lynden	See Rule 6-A	Office Hours Also see page 12				
L		20		0.0	HAMPTON	5.4	JPRY	No Office	Δ			
A		Yard	LY	5.4	LYNDEN	0.0	PR	S.00 AM to 5.00 PM Except Sat. & Sun.		7 8		

Trains must not exceed a maximum speed of 20 MPH. Over Slade Crossing I.3 mi. east of Lynden 3 MPH.

EASTWARD TRAINS ARE SUPERIOR TO WESTWARD TRAINS OF THE SAME CLASS

Rule 83(B) does not apply at Hampton and does not apply at Lynden when operator not on duty.

12	Wi	ESTW	/ARD	g (21)	FOURTEENTH SUBDIVISION EASTWARD								
SECON	D CLASS		040			Time Table No. 35			9	SECOND	CLASS		
2 1/Viii	95	Capacity	y in cars		om send	APRIL 15, 1956	g _x	See Rule 6-A	Office Hours	96			
	Way Freight	0.1.	Other	aph	lown:	STATIONS	ngele	1 1	Also see page 12	Way Freight			
n	Daily Except Monday	Sidings	tracks	Telegraph calls	Distance from Port Townsend	SIAIIONS	Distance from Port Angeles	10 10 10 10 10 10 10 10 10 10 10 10 10 1	8 8 8 8 HISS	Daily Except Monday			
	L 9.05AM			31	0.0	PORT TOWNSEND	50.8	yvx	8.00 AM to 5.00 PM Except Sat. & Sun.	As 8.05AM			
	9.59	23			12.3	DISCOVERY JUNCTION	38.5	v	No Office	7.15	ACC TOO CONTROLOGY		
			10		13.5	1,2- MAYNARD 11,2-	37.3	x	No Office				
		19			24.7	BLYN 6 8	26.1		No Office		e [®]		
	s 11.20	34	8		31.5	SEQUIM 3.6	19.3		8.00 AM to 5.00 PM Except Sat. & Sun.	■ 6.00			
		7		10 - 10 T D D D	35.1	CARLSBORG	15.7	х	No Office				
		7			38.9	AGNEW	11.9		No Office				
			12		42.4	3.5 CRANE	8.4		No Office	1 / 2			
		23			48.0	ENNIS CREEK	2.8	х	No Office				
	№12.30PM		Yard		50.8	PORT ANGELES	0.0	BKOPRXYZ	S.00 AM to 5.00 PM Except Sunday	L 5.00M	G:		

Trains must not exceed a maximum speed of 15 MPH. between Port Townsend and Discovery Jct., 25 MPH. between Discovery Jct. and Port Angeles.

EASTWARD TRAINS ARE SUPERIOR TO WESTWARD TRAINS OF THE SAME CLASS

INDUSTRIAL	TRACKS NOT	SHOWN AS	STATIONS
Name	Miles	Direction	Station
ekkvar		LEast	l Blyn

Rule 83(B) does not apply at Port Townsend.

C. P. MILES, W. H. SMITH, R. H. KOUBE.

R. G. JENSEN, J. O. IRVIN, H. L. HITCHCOCK.

W. F. REED, Train Dispatchers.

F. B. CEDERHOLM,

N. C. GROGAN, Chief Dispatcher R. C. SCHWICHTENBERG, Trainmaster.

E. G. TALLMADGE, C. W. McMILLAN,

> Traveling Engineers and Assistant Trainmasters.

OFFICE HOURS NOT OTHERWISE SHOWN

STATION	SATURDAY	SUNDAY	HOLIDAY
Cedar Falls	6:00 AM to 2:00 PM	6:30 AM to 8:30 AM	6:00 AM to 2:00 PM
Morton	7:00 AM to 9:00 AM	7:00 AM to 9:00 AM	7:00 AM to 9:00 AM
Chehalis	9:00 AM to 11:00 AM	9:00 AM to 11:00 AM	9:00 AM to 11:00 AM
Chehalis Jct.	8:00 AM to 10:00 AM	11:00 AM to 1:00 PM	8:00 AM to 10:00 AM
Raymond			8:00 AM to 5:00 PM
Bellingham	8:00 AM to 5:00 PM		8:00 AM to 5:00 PM
Port Angeles			8:00 AM to 5:00 PM

OTHER STATIONS CLOSED

YARD LIMITS AT

- Othello—Extend from 3496 ft. east of east switch to 5280 ft. west of west switch.
- Beverly and Beverly Jct.—Extend from 3700 ft. east of east switch Beverly to 245 ft. west of junction switch Beverly Jct. on First Subdivision, and 5000 ft. west of junction switch Beverly Jct. on Fourth Subdivision.
- Kittitas—Extend from 3005 ft. east of east switch to 2989 ft. west of west switch.
- Cle Elum—Extend from 2613 ft. east of east switch to 4314 ft. west of west switch.
- Hyak & Rockdale—Extend from 3069 ft. east of east switch Hyak to 103 ft. west of west portal of Snoqualmie Tunnel.
- Cedar Falls—Extend from 2670 ft. east of east switch to 3895 ft. west of west switch on 2nd subdivision, and 2900 ft. west of west switch of Log Loading track on 5th subdivision.
- Le Valley—Extend from 3000 ft. east of east switch to Pacific Coast R. R. yard limits.
- Black River—Extend from 3063 ft. west of Northern Pacific Railway crossing to Pacific Coast R. R. and Union Pacific R. R. yard limits.
- Kent—Extend from 3000 ft. east of east switch to 1847 ft. west of west switch.
- Auburn—Extend from 3007 ft. east of east switch to 2600 ft. west of west switch connection to Government Yard.
- Sumner—Extend from 3088 ft. east of east switch to 2994 ft. west of west switch.
- Tacoma, Tacoma Jct. & Hillsdale—Extend from 3500 ft. east of east siding switch at Tacoma Jct. to end of track at Tacoma and Tide Flats Yard on 3rd Subdivision and to 4721 ft. west of west switch Hillsdale on 7th Subdivision.
- st Rapids—Extend from 2000 ft. east of east switch to 2000 ft. west of west switch.
- Hanford—Extend from Hanford Station Sign (MP 20.79) to 3000 ft. west of west switch Hanford Yard.
- North Bend-Extend from east switch to 3500 ft. west of west switch.
- Snoqualmie Falls—Extend 3100 ft. east of east switch to 2692 ft. west of west switch.
- Monroe Jct.—Extend from 5300 ft. east of junction switch to Monroe Jct.
- Everett & Belt Yard—Extend from Lowell Jct. to end of track Everett, and Belt Yard N. P. Ry. connection to end of track.
- Bagley Jct.—Extend from Bagley Jct. switch to 800 ft. west of switch on 6th Subdivision.
- Selleck—Extend from 2263 ft. east of east switch to 3120 ft. west of west switch.
- Bayne—Extend from 2774 ft. east of Occidental spur switch to 2627 ft. west of Bayne Mine switch.

- Enumclaw—Extend from 1288 ft. east of east wye switch to 2025 ft. west of west switch of Northern Pacific siding and to 666 ft. east of N. P. setout track on White River Lbr. Co. R. R.
- Frederickson—Extend from 493 ft. east of east switch to 3250 ft. west of west switch on 7th Subdivision, and 2672 ft. west of west switch on 9th Subdivision.
- Eatonville Jct. and Eatonville—Extend from 2500 ft. east of east switch to 2500 ft. west of west switch Eatonville Jct., and to end of track west of Eatonville.
- New Reliance—Extend from 1000 ft. east of east switch to 2500 ft. west of west switch.
- Park Jct.—Extend from 3060 ft. east of east switch to 2860 ft. west of west switch on 7th Subdivision, and 6468 ft. west of west switch on 8th Subdivision.
- Mineral—Extend from 1438 ft. east of east switch to 1473 ft. west of west switch.
- Divide—Extend from 2500 ft. east of east switch to 3500 ft. west of west switch.
- Morton—Extend from 2578 ft. east of east switch to Kosmos Logging Co. interchange.
- Ashford-Extend from 242 ft. east of east switch to end of track.
- Maytown—Extend from 2874 ft. east of east switch to 1347 ft. west of west switch on 9th Subdivision, and to 3279 ft. west of west switch on 10th Subdivision.
- Centralia & Blakeslee Jct.—Extend from 512 ft. east of N. P. Ry. crossing at Blakeslee Jct. to 3555 ft. west of west switch Centralia.
- Chehalis—Extend from 2975 ft. east of east switch to N. P. Ry. and C. C. & C. Ry. connection.
- Dryad Jct.—Extend from junction switch to 1500 ft. west of junction switch.
- Hilda—Extend from 1500 feet east of east switch to 1500 feet west of west switch.
- MacPhail—Extend from 2476 ft. east of east switch to 2000 ft. west of west switch.
- Firdale—Extend from 1500 feet west of water tank to 1000 ft. east of east switch at Sutico.
- Raymond—Extend from 4230 ft. east of east switch to end of track.
- Port Angeles & Ennis Creek—Extend from 2500 ft. east of east switch at Ennis Creek to 1500 ft. west of Bayside yard switch.
- Carlsborg—Extend from 2500 ft. east of east switch to 2500 ft. west of west switch.
- Maynard—Extend from 7920 ft. east of switch to 1500 ft. west of switch.
- Port Townsend—Extend from 2500 ft. west of west main line switch, east to end of yard tracks.
- Bellingham—Extend from 2000 ft. west of Comont Plant switch to end of tracks, including Lake Line, Bellingham.
- Everson & Hampton—Extend from 2000 ft. east of east switch Everson to 2008 ft. west of west wye switch Hampton.
- Sumas—Extend from 1954 ft. east of east wye switch to 2000 ft. west of west wye switch.

SPECIAL INSTRUCTIONS

ALL SUBDIVISIONS

G1 Engineers operating engines equipped with the oscillating emergency red headlight will be governed by the following:

When the air brakes are applied from any cause other than in normal operation by the engineer, or when it is found necessary to stop train due to some defect, or under circumstances which might cause a derailment and the fouling of adjacent main track, engineer must immediately display the oscillating red headlight.

Engineers on approaching trains will take notice and immediately bring train to a stop, and will not proceed until track is found to be safe and clear for their movement.

These instructions are applicable at all times, both day and night. The emergency headlight should not be used for any other purpose.

The operation and use of this device does not in any way relieve trainmen and enginemen from full compliance with Rules 99 and 102.

Emergency Red Rear End Lights. Trainmen on trains equipped with oscillating emergency red rear end lights must familiarize themselves with the location of the switches which control the lights and will be governed by the follow-

ing:
The emergency red rear end light will be used on trains

so equipped in the following manner:

To provide protection to trains on adjacent tracks as re-

quired by Rule 102.

To provide supplemental protection under Rule 99 in all circumstances where its use is necessary to stop following trains on one or more tracks.

A following train observing this emergency red light displayed must immediately reduce to restricted speed and be governed by instructions of flagman.

The use of this emergency red light does not in any way relieve the flagman from full compliance with Rules 99 and

Portable emergency red lights must be removed before coupling onto the car.

G2 The Mars white light on engines so equipped shall be used at all times between the hours of sunset and sunrise, and during daylight hours on days that are dark, or during sleet, snow, fog or rain, such as would impair the vision of motorists and hinder them from observing approaching trains, except the light must be turned out when moving through certain portions of large terminals and yards where yard engines are employed, approaching junctions, or meeting points, or while standing at those points, and when approaching trains in the opposite direction on double or three or more tracks.

In case of failure of the regular headlight, the Mars white light should be used in stationary position as the headlight.

- G3 Where Approach signals are used in connection with facing point switches or manual block signals, the switch or block signal will be considered as the Home signal.
- G4 Employees are prohibited from:

Removing any of the appliances of engines or cars that will

endanger the safety of themselves or others.

Standing on top of high cars while passing under bridges or through tunnels.

Getting on the end of an engine or of a car as it approaches

Going between or running ahead of moving cars to couple, uncouple, open, close, or arrange knuckles of couplers.

Working on the side of cars or trains where there are buildings, sheds, cattle chutes, or other projections. Kicking or holding draw bar in position to make a coupling

with an approaching car or engine. Following other dangerous practices.

G5 When, for any reason, adjustment is necessary to a drawbar, knuckle pin, or locking block prior to making coupling or when coupling does not make, the engine or cars must be separated not less than 20 feet and action taken to prevent the cars from moving before going between the cars to make the adjustments.

G6 Whenever a car without a drawbar or draft timber is to be moved by a train or engine and it is necessary to chain the car to other cars or engines, employes are prohibited from going between such car and other cars or engines until the persons performing the work have a thorough understanding with the engineer and other members of the train crew. During the process of chaining up the car, the car itself must be properly secured while being chained to other cars, and if the car is to be chained to the engine, then the car must be secured and the brakes on the engine set to avoid a movement of any kind. The engineer must not release the brakes until he has received verbal information that all employes are out from between the cars or engines, and under no circumstances must employes again go between such car or cars and engines until the engineer and other members of the train crw have been notified and the car properly secured and the engine brake set.

G7 Employees must not handle or board cars or engines that bear BAD ORDER cards without first ascertaining the nature of the defect so that they may guard against injury.

G8 When using handholds and ladders or stirrup steps to descend from engines, cars or other equipment, employes must the equipment and be sure of a secure handhold and foot.

G9 Employes must not step on track rails nor other similar

objects when it can be avoided.

G10 When run-ways, gang-planks or skids are used in handling freight to or from cars, they must be secured to prevent slipping.

G11 Lighting enginemen's torches by holding them in the fire

box is hazardous and must not be permitted.

G12 Employes are prohibited from riding:

On engine footboards or pilot steps between engine and car when cars are being pushed.

On leading footboard or pilot steps while coupling engine to

On deadwoods, drawbars, brake beams, journal boxes and brake wheels.

On ends of cars containing lading which may shift.

On engine pilot or footboards, sides or ends of cars, while going in or out of depressed tracks.

On forward footboard or pilot steps of engine in direction the engine is moving except in cases where operating conditions make it necessary for safety and then only one employee must ride on the footboard.

In the gangway of engines. G13 When necessary to go outside when locomotive is eit standing or moving, extreme caution must be exercised avoid slipping or falling from cab ledge (catwalk) or running board. Cab ledge (catwalk) is not to be used on standing locomotives when access to the running board can be had by other means.

G14 The use of gasoline stoves and burners in Company's build-

ings and equipment is prohibited.

The use of oil and bottled gas (propane) stoves and burners for either cooking, heating or refrigeration is permitted only when authorized by the Company and when installation is made in accordance with Company standards.

The above does not apply to U.S. Army Field Ranges when

installed under the supervision of a U.S. Army Commissioned

Officer and operated by his men.

G15 The provisions of Rule 815 also apply to transfer move-

ments within yards.

G16 All 44-ton Diesel engines dead in freight trains must be handled at rear of train just ahead of the caboose and when a pusher engine is placed on the rear of the train, the 44-ton Diesel engine must be placed behind the pusher. When there is a 44-ton dead Diesel engine in the rear of the train, the train must not be pushed nor pulled from the rear, and the dead Diesel engine must not be handled in switching movements in conjunction with other cars.

All diesel engines must not be towed or operated under own power through water over three inches above the rails. When towed or operated under own power through water above rails, a speed of 3 miles per hour must not be exceeded. G17 The following cars, loaded or empty, will be handled next ahead of the caboose giving preference in the order shown, except that at least one car must be handled between a flat car loaded with rails and the caboose:

Bad order cars. Wood underframe flat cars. Switch rear "S.R." cars.

- G18 Unoccupied outfit cars of steel underframe or steel center sill construction when inspected and passed by a Car Department inspector, may be hauled in any part of the train.
- G19 For the comfort of the passengers, the air-conditioning on our air-conditioned passenger trains should be kept operating as long as possible. When approaching stations where cars are to be picked up or set out between the engine and the rear car, the steam line must be blown out at the proper place and the steam shut off before the train stops. At the final terminal of the equipment, when no cars are to be set out between the engine and the rear car, the fireman will simply shut off the engine as soon as the train stops in the station.
- G20 In case of heavy rain or violent windstorm, the operator must notify the section foreman.
- G21 A yellow flag by day stencilled ELECTRIC CHARGE LINE and in addition, a yellow light by night, placed at one or both ends of a passenger car standing on a yard track, indiates that the battery of the car is connected to a charge line. When thus protected, it must not be coupled to or moved before the charge line has been removed. Other quipment must not be placed on the same track so as to intercept the view of the yellow signals without first notifying the workmen; in the absence of the workmen, the signals may be moved to the end of the equipment so placed to afford the necessary protection.

DEFINITIONS

G22 Centralized Traffic Control.—A block or a series of consecutive blocks, the signals of which, together with certain switches, are controlled from a central location.

Remote Control Interlocking.—A system of operating outlying signal appliances from a designated point.

ong signal appliances from a designated point.

C.T.C.—Abbreviation for Centralized Traffic Control.

CENTRALIZED TRAFFIC CONTROL

- G23(a) On portions of the railroad so specified in the timetable, trains will be governed by block signals whose indications will supersede the superiority of trains for both opposing and following movement on the same track.
 - (b) Except as affected by Special Instructions G23 (a), all block signal and operating rules remain in force.
 - (c) The movement of trains and engine will be supervised by the Train Dispatcher, who may also control the CTC. When the CTC is controlled by other than the Dispatcher, the Dispatcher will issue the necessary instructions to the operator at the control station, location of control station will be designated by special instructions.
 - (d) Train or engines must not enter CTC territory unless the governing signal displays a Proceed indication or unless authority is obtained from the authorized employe at the control station.
 - (e) In case of failure of a Stop signal, authority to proceed will be isued orally by the authorized employe at the control station.
 - (f) Trains or engines must not move beyond the limits of CTC territory without the proper authority including the information required by Rules S-83 and D-83.
 - (g) When the governing signal displays a Stop indication and the operator knows that the interlocked switches are in proper position and there are no opposing or conflicting train or engine movements involved, he will authorize the train or engine to proceed in the following form:

"You may proceed at restricted speed to the next signal."

If the operator does not positively know that there are no opposing or conflicting train or engine movements involved or that the interlocked switches are in

proper position, he will issue authority to proceed in the following form:

"You may proceed under protection of a flagman to the first signal that displays a Proceed indication." These instructions must be repeated by the conductor or engineer to insure correct understanding. See Rule 663(A).

- (h) When the governing signal displays a Stop indication for an approaching train or engine and the means of communication have failed, the train or engine may proceed at restricted speed, when preceded by a flagman, to the next signal that displays a Proceed indication, or to the next point of communication, Flagman must be sent far enough in advance to insure full protection.
- (i) Where main track switches are not interlocked or equipped with electric locks, when a train or engine enters a siding or other track or makes a crossover movement, the operator in charge must be notified when the movement is complete and the main track switches have been closed and locked. The switches must not be opened nor will the train or engine enter upon or foul the main track without first receiving authority from the operator.
- (j) A train or engine must not move in the opposite direction to that authorized by the governing signal without proper authority from the operator, unless preceded by a flagman sent far enough in advance to insure protection.
- (k) Instructions for the operation of the electric locks on hand operated switches are posted in telephone booths or on the inside of the door of the locks.
- (1) Dual Control switches are located at Interlocking in C.T.C. territory. See Rules 663 (A), 663 (B) and 663 (C).

GENERAL SPEED RESTRICTIONS

- G24 When freight cars (except cars that are equipped for passenger train service) are hauled in a passenger train, the maximum speed of that train will be that prescribed for freight trains in that territory unless a different speed is authorized by bulletin or train order.
- G25 Diesel or electric engines with unobstructed view in either direction may be operated at permissible speeds in either direction.

Diesel or electric engines with restricted view in one direction must, when operated in that direction, reduce speed to the extent necessary for safe operation.

Dead engines must not be hauled in trains without instructions from the Chief Dispatcher. When, in the opinion of the Superintendent or the Master Mechanic a rider is necessary to insure safe movement of the engine, it will be accompanied by a competent rider.

Diesel engines moving dead in train will come under the provisions of Rule 806 and when the doors of the locomotive are locked and the hand brake is not accessible, a freight car with operative hand brakes must be coupled to the diesel with uncoupling mechanism made inoperative.

The provisions of Rule 806 will apply to oil carrying locomotive tenders X-908160, X-908167 to X-908171 inclusive. These tenders are equipped with roller bearings and when set out must be properly secured to prevent their moving.

A rider is not required for dead engines handled by yard crews in terminals, except where condition of dead engine or other circumstances may require for safe movement.

Engines with side rods removed from one side only, must not be hauled in trains.

Dead engines equipped with wood underframe tenders, when hauled in trains, should be placed in the rear of the train just ahead of any Switch Rear cars.

- G26 Gas-Electric motor cars should not be hauled dead in trains unless disabled. When necessary to haul such cars dead in freight trains, they should be hauled on the rear of short freight trains.
- G27 Dead engines must not be hauled backward in trains if it can be prevented and then only at slow speed.

Conductors will notify engineers when one or more dead

engines are to be hauled in trains and the conditions under which they are being handled, so that the speed may be regulated accordingly.

G28 When dead engines with side rods disconnected are hauled in trains there must be at least 8 cars between engines so hauled.

G29 Dead engines of Class K type or larger when hauled in trains should be placed approximately 10 cars from the road engine.

G30 Unless otherwise restricted, the following equipment must not be moved in excess of the maximum speeds shown below and further reduction must be made where conditions require:

M.P.H. Type of equipment Scale test cars, on branch line 20, on main line____ Trains handling loaded air dump cars (must stop when 25 meeting trains on double track)_ 25 Work trains with workmen or occupied outfit cars_ Lidgerwood unloaders_ Class I engines_ Passenger trains handled or helped by freight engines with single trucks_ K-1 engines on passenger trains (but must not be used except in extreme emergency)_____ L-2 and L-3 engines_ Dead engines with side rods disconnected__ 15 Dead engines with side rods in position___ Dead engines with all rods connected, pistons removed and valve motion disconnected_ 45 Engines with side rods off and main rods connected when working steam, running light or in train_. 15 Engines (other than Mallet type) with side rods in position and one main rod removed, light or hauling cars Mallet type engines working steam with one main rod 20 Diesel switchers, either dead in train or operating under their own power (except 600 H.P. Alco switchers 1600 to 1603, inclusive). 600 H.P. Alco switchers, series 1600 to 1603, inclusive__ All 44-Ton Diesels: When dead in train_. When under own power__

G31 Unless otherwise specified, the speed of all trains or engines approaching interlocked railroad crossings must be reduced, and passenger trains must not exceed 45 miles per hour and other trains or engines 25 miles per hour when passing over such crossing. The stated speed must be further reduced where conditions require. This does not apply to railroad crossings protected by automatic signals or gates; trains and engines will approach such crossings at restricted speed and if proper Proceed indication is received, may pass over the crossing at the speed prescribed by Special instructions or bulletin.

The speed of all trains must not exceed 20 miles per hour while passing over railroad crossings protected by signals or gates unless otherwise specified.

G32 The speed of trains handled by Gas-Electric or other similar type power, when consisting of power unit only, must not exceed 10 miles per hour when approaching and passing over railroad crossings protected by automatic signals.

G33 That enginemen may have knowledge of the maximum permissible speed around curves and at points where normal authorized speed must be restricted, a yellow sign with or without the black letters R.S. and black figures and placed at an upward angle of 45 degrees on the right hand side of the track, indicates that the permissible speed beginning 3,000 feet distant corresponds in miles per hour to the figure shown. A yellow sign with the black letters R.S. and placed in a vertical position on the right hand side of the track, indicates that normal speed may be resumed.

These signs do not apply to trains which by timetable or other instructions, are restricted to a slower speed.

Where these signs have two sets of figures, the outside figures apply to the movement of freight trains and those nearest the track apply to passenger trains.

G34 Spring switches:

Movement in facing point direction over a spring switch

equipped with facing point lock may be made at normal speed. Movement in facing point direction over a spring switch not equipped with facing point lock must not exceed 25 miles per hour. If switch is lined for turnout, the allowable turnout speed must be observed.

Movement in trailing point direction over a spring switch on track for which the switch is lined may be made at normal speed.

Movement in trailing point direction which springs the switch points must not exceed 40 miles per hour.

If movement is through turnout the allowable turnout speed must be observed.

See Rules 520 to 525 inclusive.

G34 (A) Spring switch must not be thrown by hand when wheels are standing on any part of the switch points, nor before the points have completed their full movement after being trailed through.

G35 In addition to Consolidated Code Rule 801 about handling of occupied outfit cars, the following will also apply on this Railroad:

When occupied outfit cars are set on a siding, the switches at each end should be spiked to prevent any possibility of a train striking the cars.

The same principle will also apply when such cars are placed on other side tracks; but when, for operating reasons, it is not practicable to have the switches spiked, the train dispatcher must be notified.

When occupied outfit cars are standing on other than ing and the switches on each end are not spiked, a yellow signal must be displayed on each end of the outfit cars. Under such conditions, the cars must not be moved except when necessary and then only after the man in charge has given his permission. When other cars are placed on the same track, the yellow signal must be moved to the end of the string of cars on that track where it can be plainly seen.

G36 When a train order office is closed during the period authorized by time-table or bulletin, the light in the train order signal will be extinguished.

G37 Excessive use of sand at any point is prohibited, and its use must be restricted to actual necessity.

G38 When passenger trains are unusually delayed, passengers should be informed as to cause and extent of delay.

Conductors will make suitable announcements to passengers on trains or arrange for brakeman and sleeping or parlor car employes to do so.

Agents or station masters will see that such announcements are made to passengers in stations when waiting for delayed trains.

Public address system should be utilized both at stations and on trains when available.

G39 In complying with Rule 3 of the Consolidated Code of Cating Rules and General Instructions, the prescribed form for yard masters and foremen of yard engines to register the time when watches are compared will be placed provided on back of time slips, Form 3256.

G40 When two or more diesel engine units are coupled together the numerals and suffix letter of the leading unit will be illuminated at all times when in service. The numerals and suffix letter of trailing units must not be illuminated.

The number and suffix letter of the leading unit only to be used in train orders.

G41 Where Automatic Block and Interlocking rules and signal indications require movement at RESTRICTED SPEED, such movement must be made prepared to stop short of train, obstruction or switch not properly lined, and be on the lookout for broken rail or anything that may require the speed of a train to be reduced, but a speed of 15 miles per hour must not be exceeded.

G42 When flat spots develop en route on cars or locomotive wheels, speed of train must be reduced to not exceed forty (40) MPH to the first available point of communication, where Conductor or Engineer will notify Chief Dispatcher and be governed by his instructions. If in the judgment of the Conductor or Engineer a lesser speed is deemed advisable, speed of the train will be reduced in line with their judgment.

From tests made it develops that it is desirable, in order to reduce the impact, to operate cars or locomotives with flat

spots at a speed either under seventeen (17) MPH or in excess of twenty-three (23) MPH as the most severe impact occurs at speeds seventeen (17) to twenty-three (23) MPH.

X1 Trains handling steam derricks must not exceed the following speed limitations. The indicated maximum speeds must be further reduced on tangents and on curves where track is not in proper condition for the specified maximum speeds.

n ves P.H. P.H.
P.H.
P.H.
PH
* ***
P.H.

X2 Trains handling rotary snow plows, locomotive cranes, Jordan spreaders, shovels, pile drivers and ditching machines must not exceed speed limitations shown below. The indicated paximum speeds must be further reduced on tangents and urves where track conditions do not justify the specified maximum speeds. Engine and train crews will make frequent observations of how these machines are riding and when in damaged or questionable condition, or when this equipment is hauled in trains with heavy end trailing, the speed must be further reduced to insure safe movement.

	On Tangent Track	On
		Curves
First Subdivision	35 M.P.H.	25 M.P.H.
Second Subdivision	35 M.P.H.	20 M.P.H.
Third Subdivision	35 M.P.H.	25 M.P.H.
Fourth Subdivision	20 M.P.H.	15 M.P.H.
Fifth Subdivision	20 M.P.H.	15 M.P.H.
Sixth Subdivision	20 M.P.H.	15 M.P.H.
Seventh Subdivision	20 M.P.H.	15 M.P.H.
Eighth Subdivision	15 M.P.H.	10 M.P.H.
Ninth Subdivision	25 M.P.H.	20 M.P.H.
Tenth Subdivision	20 M.P.H.	15 M.P.H.
Eleventh Subdivision	20 M.P.H.	15 M.P.H.
Twelfth Subdivision	15 M.P.H.	10 M.P.H.
Thirteenth Subdivision	15 M.P.H.	10 M.P.H.
Fourteenth Subdivision	15 M.P.H.	10 M.P.H.

The speed of all trains or engines passing through turnouts nust not exceed 13 miles per hour, except those turn-outs aid with long frogs and designated by Special Instructions or bulletin where the speed may be increased to 25 miles per hour, unless otherwise authorized.

Turnouts laid with long frogs are located at:

Station Location Maple Valley Turnout from CMStP&P to PCRR track Turnout from CMStP&P to UPRR track Tacoma Junction

X3 (A) All spring switches except those indicated below are equipped with facing point locks, permitting maximum permissible speed in the territory involved while moving against the points. The speed must not exceed 25 MPH while moving against the points at the following spring switches. (See Special Instruction G34). _____West siding switch Ragnar__ Tacoma Junction_____East end of double track Frederickson____Junction switch Maytown_ _Junction switch Signals at spring switches at Tacoma Jct., Frederickson

and Maytown indicate only the position of the spring switch. X4 Electric freight engines class EF-1, EF-2, or EF-3 must not

X5 Ten-minute fusees should be used on First, Second, and Third Subdivisions. Five-minute fusees should be used on all other Subdivisions except where operating under the rules of another railroad, requiring the use of ten-minute fusees.

exceed a speed of 45 MPH.

- X6 When any type of engine is used in helper service on passenger trains, the helper engine should be placed on the head
- X7 Log handling trains will come to a stop while passenger trains are being met or are passing.
- X8 The wires on the trolley and transmission line poles and supports carry high voltage. Contact with them either by person or equipment is liable to cause fatal injury or damage to property. THEY MAY BE HANDLED ONLY BY THOSE WHO HAVE RECEIVED SPECIFIC AUTHORITY TO DO

If wires are found hanging down or any part of the trol-ley or transmission system deranged in such a way that a person might come in contact with the wires, the train dispatcher must be notified from the first point of communication.

If conditions are such that train or equipment is unable to pass without touching the wires, the train dispatcher must be notified and he will give necessary instructions.

In case of fire, extinguishers filled with carbon tetra-chloride only should be used if it is possible for the extinguishing liquid to come in contact with the wires.

In case of electric shock, resulting in apparent unconsciousness, application of the Prone Pressure Method of Resuscitation must proceed immediately; the knowledge of this method is required of all persons having duties within the electrified zone.

Freight trainmen will not be required to ride on top of train in electrified territory unless some real emergency condition exists, which, in the judgment of the conductor of the train, would require special attention from some member of the crew located on top of the car. These instructions are not to be considered as relieving trainmen from the necessity of getting on top of cars while switching operations are carried on when conditions require. However, in no case must trainmen get on top of cars where, on account of lack of clearance, there is danger of contacting any part of energized trolley system.

Due to settling of trolley poles on fills, raising of track when ballast is applied, and other similar causes over a period of years, the height of trolley wire above top of rail is variable; and in some locations, it is less than standard height of 24'2".

X9 At the following stations, the siding is also used as a house track; the train dispatcher need not be notified when cars are left on any of these sidings: Fourth Subdivision _____All Stations Fifth Subdivision _____All Stations Sixth Subdivision ... __All Stations Seventh Subdivision: Hillsdale, Frederickson, Elbe, Mineral,

Ninth Subdivision______McKenna, Offut Lake, Maytown Tenth Subdivision______All Stations Eleventh Subdivision All Stations
Twelfth Subdivision All Stations
Thirteenth Subdivision All Stations Fourteenth Subdivision_____All Stations

X10 Operation of trains on mountain grades. - In addition to instructions contained in Air Brake and Signal Instruction Book, Form 2697 Revised, and approved April 1936, in which reference is made to paragraph numbers, the following will

- (a) When there is no helper on the rear, the rear car must be one that is equipped with a good hand brake. Conductors are responsible for having trainmen properly stationed.
- (b) When a helper is used on the rear of a freight train, it must be in advance of outfit cars, or cars of insufficient strength to safely resist the push of such
- (c) Before commencing descent of grade from Hillsdale to C Street, Tacoma, a brake pipe test as per Rule 85-A must be made and all retainers must be turned up on eastward trains between Hillsdale and Tacoma as per Rule 90-A. (See Special Instruction X11.)
- (d) Before commencing descent of grade from New Reliance to Eatonville Junction, brake pipe test as per

Rule 85-A must be made at New Reliance, and retainers must be turned up between New Reliance and Eatonville Junction as per Rule 90-A. Does not apply to trains handled by diesel electric engines equipped with regenerative braking.

- (e) Before commencing descent of grade from MacPhail to Sutico, a sufficient number of retainers as determined by the conductor and engineer handling the train will be turned up to insure proper control of train speed. When engineer handling train is not familiar with this portion of the railroad, retainers must be turned up on all cars in the train.
- (f) Trainmen must watch closely for excessive heating of wheels and if any are found, the train must be brought to a stop and remain standing a sufficient length of time to allow the wheels to cool.
- (g) Paragraphs 97 and 128 (Inoperative Air Brakes) do not apply on mountain grade.
- (h) In electrified territory, the use of retaining valves and the testing of brakes before starting descent is not required providing there has been no change in position of hose cocks or double heading cocks since last test, EXCEPT when necessary to hold train with air brakes, in which case Rules 90-A, 139 and 140 will govern.
- (i) If regeneration fails descending a mountain grade, the train must be brought to a stop immediately as per Paragraph 140, all available retainers turned up and the brake pipe pressure fully restored before proceeding.
- (j) Engineers on freight trains must adjust the brake pipe feed valve pressure to 90 lbs. and have brake pipe charged to this pressure before commencing descent of mountain grade as per Rule 139. When there is no stop to be made at summit of mountain grade, engineers will adjust the brake pipe pressure to 90 lbs. four miles before reaching summit and trainmen on rear must note that pressure is being raised as indicated by caboose gauge as per Rule 104.
- (k) Whenever the engine handling a freight train is to be detached on a mountain grade, in addition to the use of hand brakes, the engineer on the helper engine will cut in the brake valve on his engine and keep the brake pipe fully charged. If two helpers are used, the one nearest the head end will cut in the brake valve on his engine. When the road engine is again attached to the train, the helper engineer will cut out the brake valve on his engine. Brake pipe test, as per Paragraphs 38 and 85-A, must be made before proceeding.
- All trains descending the grade Boylston to Beverly and Rockdale to Cedar Falls with air brakes will stop at Rye and Garcia for inspection and to permit wheels to cool.
- (m) On descending grade when power goes off the line, train must be immediately brought to a stop. If power does not come on the line again within one minute, engineer will notify trainmen who will immediately set enough hand brakes to alone hold the train. When power again comes on the line, engineer will recharge the brake pipe. Hand brakes must not be released until it is known that the air brake system has been fully recharged and the brakes operative.
- (n) All trains descending grade designated as mountain grade in the electrified territory with steam power or a power unit that will not regenerate, must turn up all available retainer valve handles just before passing over the summit of such grades and turn them down when foot of the grade has been reached. Rules 90-A and 139 governing.
- (o) With no helper at the rear of the train and a backing movement is made during the ascent of the grade, the brake pipe test, as per Paragraphs 38 and 85-A, must be made before the backing movement begins; the brake pipe pressure must be fully restored, a sufficient number of hand brakes applied on the rear of the train to properly control the slack, and a man stationed within reach of the Conductor's valve in order

to stop the train promptly in case of emergency. If there is a helper in the train when the backing movement is to be made, the following will govern:

When the engineer on the road engine applies the brakes for brake-pipe test, he will cut out the brake valve on his engine and when the test has been completed, the engineer on the helper engine nearest the rear end will cut in the brake valve on his engine, fully recharge the brake pipe and control the air brakes during the backing movement; electric locomotives should be operated in series regeneration during the backing movement.

When the backing movement has been completed, the engineer on the helper engine will make a full service application of the train brakes and cut out the brake valve on his engine; the engineer on the road engine will cut in the brake valve on his engine and release the brakes. Trainmen must know that the brakes on the rear end of the train are released before the train starts.

X11 When eastward freight trains with logs between Morton and Tacoma are handled by a diesel locomotive with dynamic brake working on all units, Paragraphs (c) and (d) of Special Instruction X10 are modified to read as follows:

"Before leaving Divide and when cars are picked up enroute, place all retainers on loaded cars in the fourth or slow release position except on the last eight cars in ton which retaining valves will be left in release position. Retainers will be left in these positions to Tacoma. When twelve cars or less not equipped with fourth position retainers are handled in these trains, eight will be placed just ahead of the caboose, the balance anywhere in the train."

"If the number of cars exceed twelve, eight will be placed just ahead of the caboose and balance next to the engine. The retainers on the cars next to the engine will be placed in the high-pressure position at Hillsdale and turned down to release position at C Street, Tacoma. The retainers on the eight cars next to the caboose will be left in release position."

X12 In placing passenger equipment with buffers in freight trains, such cars must not be placed between freight cars equipped with top pin lifter couplers unless the top pin lifter couplers have a direct connected uncoupling rod (not a chain) and provided the coupler heights are such that the buffer will not come in contact with the lock lifter or the uncoupling rod.

Express refrigerators or passenger cars equipped with U. C. brake equipment, when handled in freight trains, should be handled on the head end of the train.

Passenger cars equipped with L. N. brakes can be had in either head or rear end of freight trains.

- X13 When safe operation of trains will permit, brakes should not be applied on engine or cars during dry weather while passing over Bridge EE-384-B, four and one-half miles west of Ellensburg; Bridge EE-386-B, five and one-half miles west of Ellensburg, or other open deck trestles or bridges between Othello and Tacoma.
- X14 Train order signal at Tacoma Junction does not apply to yard movements. When there are train orders affecting yard movements, Dispatchers will instruct the operator to flag such engines with hand signals and bring engine to a stop before making delivery.
- X15 Until further notice, all eastward trains handling loaded log cars and all other trains which in the engineers' judgment require increased braking power will raise air brake train line pressure to 100 lbs. at Hillsdale.

Feed valve should be set at normal pressure after arrival of train at Tide Flats Yard.

X16 If a train hauled by a Diesel locomotive is stopped in a tunnel under cricumstances where it cannot proceed through or back out of the tunnel promptly, the engine crew will immediately shut down the Diesel engines and in addition, on passenger trains, the Clarkson or other type steam generators. The train crew of passenger trains will promptly shut down Waukesha ice engines and engine generator sets only

on those of the following cars which are so equipped, and which may be standing in the tunnel:

 Touralux Sleepers
 5752, 5753, 5754

 Diners
 113 and 114

 Tap Cars
 160 and 161

 P&B Cars
 206 and 207

 Coaches
 454 to 478 inclusive

 Coaches
 552, 553, 554

 Super Dome Cars
 50 to 59 inclusive

(Instructions for shutting off and turning on air conditioning will be found in electrical control locker in each car.)

Circulating fans must be shut down on all cars standing

in the tunnel.

Use of lights and other electrical equipment must be held to a minimum to prevent excessive discharge of batteries. Blower fans on all steam jet air conditioned cars standing OUTSIDE the tunnel ONLY, may be used to keep the cars properly ventilated.

X17 At Maple Valley, Black River and Tacoma Junction, trains other than those displaying signals for a following section, may register by register ticket.

X18 Seattle water shed extends from one mile east of Cedar Falls station to Landsburg, and from Cedar Falls station to one mile west of station on 5th Subdivision. All toilets must be kept locked in trains in this district and in city limits Renton and Seattle. Refuse must not be thrown from private, ining, or other cars within these limits. Conductors will be eld responsible for strict observance of this rule.

X19 In addition to those designated in timetable, standard clocks are located in Tide Flats Yard Office, Train Dispatcher's Office, Tacoma Roundhouse Office and Seattle Roundhouse Office.

X20 Manually controlled crossing signals are in use at D Street, Tacoma. Movement on team track over D Street must be protected by a member of the crew taking a position on the crossing to warn highway traffic of approaching trains.

X21 In Automatic Block Signal territory, Manual Block System Rules will apply when trains are run against the current of traffic.

X22 If trolley wires are observed to be slack the pantograph should be lowered and locomotive drifted by. If there is any question about low wires becoming entangled with locomotive or cars, train should be brought to a stop immediately and actual condition with regard to clearance of wires above locomotive and cars should be determined before proceeding.

X23 Eastward second and inferior class trains and engines and yard movements must not enter upon the eastward main track between Depot Switch and Tacoma Jct. until it has rst been determined that all eastward first class trains due to Tacoma Jct. have passed Tacoma Jct. Westward second and inferior class trains and engines and yard movements must not enter upon the westward main track between Ta-

coma Jct. and Depot Switch until it has first been determined that all westward first class trains due at Tacoma

have arrived Tacoma.

X24 Cle Elum substation is operated automatically. Emergency switch is located in Cle Elum Depot, just west of operator's desk, which may be opened in an emergency, but before doing so, all persons must be familiar with operation and train dispatcher notified so that proper protection will be provided in addition to flagging air gap.

X25 CREWS HANDLING ELECTRIC ROTARY SNOW PLOW X-900212 WILL BE GOVERNED AS FOLLOWS:

(A) When moving to and from terminals, not in snow operation, pantograph must be locked down and secured to prevent coming in contact with trolley. Grounding switch must be in proper position.

(B) Must have regular air gap order at all times.

(C) When handled by diesel power and crew has air gap order, pantograph must be locked down and secured before passing air gap and order issued: "May pass air gap after it is known pantograph is locked down and secured."

(D) Crews handling this machine are responsible for knowing pantograph is properly secured and grounding switch is in proper position.

FIRST SUBDIVISION

X26 Speed restrictions (In addition to General Speed Restrictions)

Maximu	m Spec	ed MPH.
	egr.	Other
	rains	Trains
Bridge EE-260, 2 mi. east Jericho	50	40
Bridge EE-384-B, 21/2 mi. east Thorp	50	40
Corporate Limits Town of Othello, Wash	40	40
Corporate Limits Town of Kittitas, Wash	65	50
Corporate Limits City of Ellensburg, Wash	50	35
Corporate Limits Town of Cle Elum, Wash		50

SECOND SUBDIVISION

X27 Speed Restrictions (In addition to General Speed Restrictions)

Maxim	num Spee	d MPH
	Pagr.	Other
	Trains	Trains
1st curve east and 1st curve west Bridge		
FF-4, 4½ mi. west Cle Elum		35
Corporate Limits Town of Cle Elum, Wash.	60	50

X28 Trains handling logs loaded on flat cars without side stakes should not exceed a speed of 15 M.P.H. when operating over bridge FF-120, one mile west of Cedar Falls.

THIRD SUBDIVISION

X29 Speed Restrictions (In addition to General Speed Restrictions)

Maxin	num Spee	MPH
W SEL F. S. S. S. S. SEL	Psgr.	Other
	Trains	Trains
Over N.P. Crossing Black River	35	35
East Leg of Wye Black River	13	13
Corporate Limits Town of Pacific, Wash		50

X30 At Tacoma, the normal position of the crossing gate over the N.P. crossing at Lincoln Avenue east of the roundhouse, is for movements on the CMStP&P tracks.

X31 Manually controlled switches for operating traffic signal lights at the foot of west end of Eleventh Street Bridge Tacoma must be operated when switching movements are made over Eleventh Street.

X32 Manually controlled switches are installed to permit the starting or stopping by hand of crossing signals at Pacific

Highway crossing at Sumner.

This switch consists of a knob, with a cover locked with a switch lock, on a box mounted on the instrument case for the crossing signals which is between the main track and siding and just east of the crossing. To operate, unlock cover, turn knob in one direction to stop signals, and opposite direction to start signals.

X33 At Tacoma, before a train or engine enters onto or makes a move over the crossing at Pacific Avenue, South 26th Street and Wakefield Drive, a trainman must first place the City Traffic lights at the crossing in a STOP position by operating switch located in box on either side of crossing.

After movement has been completed, the Traffic lights must be restored to normal position by operating switch located in box on opposite side of crossing.

X34 Union Pacific engines are prohibited from using the following tracks between Black River and Tacoma Jct.:

Sumner: Track over Stuck River Bridge serving Standard Brands, Fibreboard Products and Pacific Lumber Agency.

UP CLASS 3800, 3900 and 4500 H.P. Alco-GE gas turbine electric locomotives, in addition to the above restrictions, are prohibited from using Associated Frozen Foods track at Sumner. Maximum speed permissible for this class engine between Tacoma Jct. and Black River is 60 M.P.H., subject to speed restrictions due to curvature and other time-table or special rules restrictions.

X35 Eastward trains having authority to hold main track when meeting westward trains at Puyallup must not pass signal at west switch until westward train has arrived. A train on main track between switches will give a westward train a

stop indication at the west switch at Sumner.

X36 The signal located 850 feet west of Tacoma Jct. office on Third Subdivision governs eastward movements from eastward track and will display indications in accordance with Rules 601 A Fig. 11 and 601 F Fig. 7 (See Rule 514.)

Rules 601 A Fig. 11 and 601 F Fig. 7. (See Rule 514.)

The eastward signal located 225 feet west of Tacoma Jct. office on Seventh Subdivision governs eastward movements and will display indications in accordance with Rules 601 A Fig. 8, 601 B Fig. 7, 601 C Fig. 7, (See Rule 519), Rule 601 D Fig. 3.

Fig. 3.

The three-unit westward signal located 550 feet east of Tacoma Jct. office governs westward movements as follows:
The top unit governs westward C.M.St.P.&P. movements to

the Seventh Subdivision and will display indications in accordance with Rules 601 A Fig. 9 and 601 B Fig. 8.

The middle unit governs westward movements to the U.P. track and will display indications in accordance with Rules 601 A Fig. 9 and 601 E Fig. 8.

The lower unit governs westward C.M.St.P.&P. movements on Third Subdivision and will display indications in accord-

ance with Rules 601 A Fig. 9 and 601 F Fig. 5.

The signal located 35 feet east of Tacoma Jct. office on the U.P. track governs movements to C.M.St.P.&P. track and will display indications in accordance with Rules 601 A Fig. 6, 601 B Fig. 5 and 601 C Fig. 5.

X37 All eastward trains from Tacoma Line, will, upon arrival at Black River Yard, register with operator Black River Tower by telephone unless register check has previously been left at Tower.

FOURTH SUBDIVISION

X38 Speed Restrictions (In addition to General Speed Restrictions)

Maximum Speed MPH.
All Trains

Beverly to Hanford	halist as
1000 and 1200 HP Diesels	25
1750 HP 4-wheel truck Diesels	15

FIFTH SUBDIVISION

X39 Speed Restrictions (In addition to General Speed Restrictions)

Maximum Speed MPH.
All Trains

au a	TIGHT
Monroe to Cedar Falls	
1000 and 1200 HP Diesels	25
1750 HP 4-wheel truck Diesels	15
11/2 mi. west Cedar Falls to 1/2 mi. east Tanner	15
Within Yard Limits Snoqualmie Falls	6
Trains handling logs, 2 mi. east Carnation to	
	15
On Curve just west M.P. 38, about 2 mi.	1979 (1)
east Monroe Jct	25
Over Bridge FF-962 between M.P. 39 and 40,	
about 1/2 mi. east Monroe Jct	15
Corporate Limits Town of North Bend, Wash,	
Corporate Limits Town of Carnation, Wash	
Corporate Limits Town of Duvall, Wash	

X40 Engines when doubleheading must not exceed a speed of 15 miles per hour over bridge FF-856-B one-half mile east of Carnation, and over Bridge FF-962 one-fourth mile east of Monroe Jct.

SIXTH SUBDIVISION

X41 Speed Restrictions (In addition to General Speed Restrictions)

Maximum Speed MPH. All Trains

Bagley Jct. to Enumclaw	
1750 HP 4-wheel truck Diesels	15
Corporate Limits Town of Enumclaw, Wash	25
Between Kanaskat Jct. and Bagley Jct., trains	
handling steam wrecking derrick, pile driver	
or locomotive crane	10
	2 2

X42 Beween Bayne Jct. and Bagley Jct., via joint track, Northern Pacific wrecking derricks 41 to 48, inclusive, Pile Driver 25, and engines heavier than NP class S-4 not permitted.

Between Bayne Jct. and Enumclaw, Northern Pacific engines, classes A-2 to A-5, inclusive, and Z-5 to Z-8, inclusive, not permitted.

X43 Trains handling logs will not cross on overhead bridge between Bayne Jct. and Kanaskat Jct. while a train is passing under this bridge on Northern Pacific First Subdivision.

X44 At Selleck the Cascade Timber Company's tracks may be used to a point 250 feet beyond the east switch. All movements must be made at restricted speed, looking out for engines and cars of the Cascade Timber Company. Derail is located on west end of Northern Pacific siding and on Cascade Timber Company's track 1000 feet west of west yard switch.

SEVENTH SUBDIVISION

X45 Speed Restriction (In addition to General Speed Restrictions)

Maximum S	peed M	PH.
Al	l Trains	
Over C and D Streets, Tacoma	_ 10	
Between Tacoma Jct. and Hillsdale	_ 15	
Eastward trains New Reliance and Eatonville Jct.	_ 20	
Over Nisqually River Bridge	_ 15	
On curve 1 mi, east Mineral		
2 mi. west of Divide and Coal Canyon	_ 15	
Coal Canyon and Morton	_ 25 _	27.
Corporate Limits, Town of Eatonville, Wash	_ 20	
Corporate Limits Town of Morton, Wash	_ 15	
From St. Paul Reload track switch to west end		
interchange at Morton	_ 15	
40 At Mineral the manual modition of the annual		

X46 At Mineral, the normal position of the crossing gates over the West Fork Logging Company crossing is for movements on the CMStP&P tracks,

X47 Engines or loaded cars must not be moved or placed on West Fork empty track at Mineral.

X48 When shoving cars over highway crossings on Kosmos Logging Line between Morton and Interchange Track, trains must come to a full stop and flag the crossing. During the night the crossing floodlight must be lighted for all trains while passing over crossing.

X49 Eastward trains and engins on Seventh Subdivision moving between Hillsdale and Tacoma Jct. must stop before passing stop board located just west of C Street.

NINTH SUBDIVISION

X50 Speed Restrictions (In addition to General Speed Restrictions)

X51 Chehalis and Western Ry. Co. trains will not register at Maytown,

X52 At Skookumchuck, the normal position of the crossing gates over the Weyerhaeuser Timber Company crossing, located 1.6 miles east of the station, is for movements on the CMStP&P tracks.

X53 In moving over main track between Chehalis Junction and CCC interchange track at Chehalis, trains and engines should proceed expecting to find cars on this track.

X54 At Chehalis the normal position of the crossing gates over the N.P. crossings is for movements on the CMStP&P tracks.

X55 That part of Palmer Lumber Company Spur, located west of West Street crossing just east of Chehalis depot must not be used.

TENTH SUBDIVISION

X56 Speed Restriction (In addition to General Speed Restrictions)

Maximum Speed MPH.
All Trains

Maximum Speed MPH.

			1	n ::		21
ELEVENTH SUBDI	VISION	Tunnol	AS Comitable	N- 10	1/2	1550' east of tunnel
X57 Speed Restrictions (In addition to		Rowlete	43, SWITCH	No. 18		400' east of east H.B.
tions)	General Speed Resure-					
	Maximum Speed MPH.					miles east of east switch
Daniel de Daniel	All Trains					ontrolled from Substation
Dryad to Raymond 1750 HP 4-wheel truck Diesels_	16					325' east of tunnel
1150 III 4-wheel track Dieseis_						500' west of tunnel
TWELFTH SUBDIV						475' west of west H.B.
X58 Speed Restrictions (In addition to	General Speed Restric-					ontrolled from Substation
tions)	35					7 miles west of Cle Elum
	Maximum Speed MPH. All Trains	Keeche	lus snowshe	ed, Switch l	No. 37	325' east of shed
Bellingham to Glacier						1325' west of shed
1750 HP 4-wheel truck Diesels:	not permitted.	Garcia,	Switch No.	44		875' east of east HLB.
1000 and 1200 HP Diesels	15		Falls Insula			
On O.P.C. track between east wy	e switch and					tion and switch No. 50-Y
end of track Limestone Jct.						1575' east of west switch
X59 At Bellingham, the normal positi over the crossing of the G. N. tr	on of the crossing gates					650' west of west H.B.
movements on the G. N. track.	ack in the yard, is for					east of double track H.B.
X60 When trains operating on the 12	h and 13th Subdivisions					800' west of wye
are double-headed, there must be		Black B	liver, Switch	1 No. 101 c	ontrolling	
engines.						650' north of O-W tower
FOURTEENTH SUBD	TUISION		liver, Switch			A-04
Speed Restriction (In addition to						650' north of O-W tower
ons)	General Speed Restric-	Argo, S	witch No. 1	U5 controlli	ng	at P.CO-W crossover
	Maximum Speed MPH.		witch No. 10			at P.CO-W crossover
	All Trains	Argo, S	hound P.C.	track	ıg	at P.CO-W crossover
Port Angeles to Discovery Jct. 1750 HP 4-wheel truck Diesels_			witch No. 1			1.00-17 (10220701
Discovery Jct. to Port Townsend	15	inb	ound O-W	track		at P.CO-W crossover
Only 600 HP and 6-axle Diesels i	nav be operated.	Argo, S	witch No. 10	08 controllin	ıœ	
Over Morse Creek Bridge at M.P.	45 to ½ mi.	out	bound O-W	track		at P.CO-W crossover
west of M.P. 50	10	Trolley	Switches I	Nos. 107 a	ad 108 may	be operated by remote
On curves and slide areas	15	con	trol switch	located in	U.P. Tower,	Argo.
	TATE OTTE O		Pagr. Statio			
TROLLEY CUT OUT S	WITCHES					0.4 mile south of station
At stations where substations ar		Seattle	Pagr. Static	n, No. 110	controlling	at 0.4 mile south of station
are near substations, and the switch	thes are located in the					in emergency from near
substations. At other stations swit	ches are located near	ana witche	t and of plo	ttorm Seat	lle Pagr. Dep	in emergency from hear
each end of siding or yard except:						n be opened under load
Othello, west Switch					of persons	
Jericho, Switch No. 9						1375' west of west H.B.
Beverly, Switch No. 11						650' west of west H.B.
Cohasset Pit, Switch No. 12						1050' east of east H.B.
Condabat 111, Dwitch 110, 12	. miles west or bevery jen					
	TOWNS		n nagra di n d			
	TONNAG	E CHART		300 //		
	Fo					- , 5 _ = 39
TONN	AGE RATING—EAST			EF-2		
		EP-2	EF-1	EF-3	EF-5	
Tacoma to Bl		3450	CL	CL	CL	
	Cedar Falls	2000	4100	5500	8200	
	o Hyak Elum	1250 CL	1700	2550	3400 CL	
	Cittitas	4000	6000	7500	12000	
	ylston	1300	1670	2500	3340	and the second of the second
	everly	1300R	1670R	2500R	3340R	

eac Wile	TONNAGE RATING—EAST		. "	EF-2		
· =		EP-2	EF-1	EF-3	EF-5	
	Tacoma to Black River	3450	CL	CL	CL	
=	Black River to Cedar Falls	2000	4100	5500	8200	, 1 a 1 a 1 a 1 a 1 a 1 a 1 a 1 a 1 a 1
	Cedar Falls to Hyak	1250	1700	2550	3400	
	Hyak to Cle Elum	CL	CL	CL	CL	
- 0	Cle Elum to Kittitas	4000	6000	7500	12000	e was the letter of a final for
= ×	Kittitas to Boylston	1300	1670	2500	3340	THE RESERVE OF THE RESERVE OF THE STATE OF T
	Boylston to Beverly	1300R	1670R	2500R	3340R	The same was a same and
	Beverly to Othello	3200	5000	7000	10000	
				1		
B	TONNAGE RATING—WEST		존상대	yn es l	in the N	
# ¥		CL	CL	CL	CL	
* * * * * * * * * * * * * * * * * * * *	Othello to Beverly	CL	CL	CL 2100	CL	
#				CL 2100 4650R	CL 2800 6200R	
9 9 9 9	Othello to Beverly	980	1400	2100	2800	
	Othello to Beverly Beverly to Boylston Boylston to Kittitas	980 1400R	1400 3100R	2100 4650R	2800 6200R	
	Othello to Beverly Beverly to Boylston Boylston to Kittitas Kittitas to Cle Elum	980 1400R 3700	1400 3100R 5000	2100 4650R 7000	2800 6200R 10000	
	Othello to Beverly Beverly to Boylston Boylston to Kittitas Kittitas to Cle Elum Cle Elum to Hyak	980 1400R 3700 3200	1400 3100R 5000 4000	2100 4650R 7000 5500	2800 6200R 10000 8000	
	Othello to Beverly Beverly to Boylston Boylston to Kittitas Kittitas to Cle Elum Cle Elum to Hyak Hyak to Cedar Falls	980 1400R 3700 3200 1250R	1400 3100R 5000 4000 2800R	2100 4650R 7000 5500 4000R	2800 6200R 10000 8000 5600R	

Dispatcher may increase or decrease above tonnage ratings as may be necessary.

EMERGENCY TELEPHONES

Dormitory cars of trains 15 and 16 are equipped with telephones. EMERGENCY TELEPHONES ARE LOCATED AT AND BETWEEN STATIONS AS FOLLOWS:

FIRST SUBDIVISION:

Othello-West switch phone box. Anson-West switch phone box.

Tauton-Substation.

Corfu—East switch phone box and section house. Smyrna—East switch phone box, section house and depot. Jericho-Middle of siding phone box.

M.P. 2023—15 pole lengths west phone box.

Beverly—East switch phone box, section house and cafe.

Columbia River Bridge—West end phone box. M.P. 2029-6 pole lengths west phone box. Doris-Substation and west switch phone box.

Rye-West switch phone box. Cheviot-West switch phone box.

M.P. 2043—8 pole lengths east phone box. Boylston—Section house and west switch phone box.

M.P. 2049—12 pole lengths west phone box.

East Kittitas—Scale house.

Kittitas-Substation.

Ellensburg—Baggage Room.

Thorp—East switch and west switch phone boxes.

Taneum—Watchman's shanty, ½ mi. west of M.P. 2070. Tunnel 47—Just east of M.P. 2073 phone booth.

Horlick-East switch and west switch phone boxes and section

Riverside—Just east M.P. 2079 and M.P. 2080 phone boxes.

Cle Elum—Section house, substation, and west switch phone box.

SECOND SUBDIVISION:

Signal 5-7—10 pole lengths west of M.P. 2091 phone box.

Easton—East switch, baggage room and section house.

Bridge 18—M.P. 2100 phone booth.
M.P. 2104—6 pole lengths east phone box.
Whittier—East switch phone booth, west switch phone box and section house.

Meadow Creek—Signal 23-0 phone box. Roaring Creek—1/4 mi. west of M.P. 2110. Keechelus Snow Shed—West end phone booth.

Hyak—East switch phone box, section house, substation, baggage room and Signal Mtr.'s house.

Rockdale—East switch phone box and west switch phone booth.

Humpback Snow Shed-100 feet west phone box.

Windy Point-1/2 mi. west M.P. 2120 watchman's shack.

Bandera—East switch watchman's shanty, west switch phone box.

Harris Creek-M.P. 2125 phone booth.

Minot-Watchman's shanty.

Garcia-Section house, depot and west switch phone booth.

Hull Creek—Watchman's shanty, ½ mi. west of M.P. 2130.

Ragnar—East switch and west switch phone booths.

Cedar Falls-Substation, waiting room and west switch phone booth.

Bagley Ict.—Phone booth.

Barneston-West switch phone booth.

Trude—East switch and west switch phone booths.

Landsburg-1/2 mi. west M.P. 2148.

Noble-West switch phone booth.

Maple Valley—Section house, east switch phone box and 2 mi. west near M.P. 2156 phone box.

Cedar Mountain*—Overhead highway crossing phone box.

Indian*—East switch and west switch phone boxes. Elliot*—Phone box, 1 mi. east phone box, Bridge 14-2 1 mi. west.

13-4 Old Bridge 7 phone box.

Renton*-East switch and west switch phone boxes, outside depot

Black River*—East switch yard phone box. N.P. transfer phone box. Boeing Bridge*—Signal 7-2 phone box. Davis Crossing*—Phone box.

Van Asselt*—East end yard.

-These phones connected to the Pacific Coast Dispatcher at Maple Valley only.

THIRD SUBDIVISION:

Black River Intg. Plant-W.B. home signal.

Black River Jct .- Yard office.

Black River-N.P. crossover phone box.

Orillia—Highway crossing phone box.

Kent—East switch and west switch phone boxes and freight house. Auburn-East switch phone box freight house, and west Army point switch phone box.

Benroy-East switch phone box.

Sumner-Freight house.

Puyallup—Freight house and west switch.

FOURTH SUBDIVISION:

M.P. 9-2 pole lengths east phone box. Priest Rapids-Station house.

FIFTH SUBDIVISION:

Tanner-Phone booth.

North Bend—Section house. Snoqualmie Falls—East switch phone booth and baggage room.

Fall City-Phone box.

Carnation—East switch phone booth and section house.

Duvall-Phone box.

Monroe Jct.-G.N. phone booth.

Everett-Roundhouse.

SIXTH SUBDIVISION:

Selleck-Phone booth.

Kanaskat Jct.—Phone booth.

Bayne Jct .- Phone booth.

Veazie-N.P. booth, also N.P. phone.

Enumclaw-Baggage room.

SEVENTH SUBDIVISION:

Tacoma—On pole east end of Bridge C Street.

Hillsdale—Phone booths near 60th, 64th and 72nd Streets.

Bridge GG-46-Small building.

Allison—Booth near west switch. Frederickson—Depot.

Thrift—In building near west switch.

Tanwax—On pole at east switch.

Kapowsin-Section house.

Clay City-Box on pole near loading platform.

Eatonville Jct.—Depot. New Reliance—Phone booth near west switch at highway crossing.

Elbe-Freight house.

Park Jct.—Phone booth near east switch.
Old Burt—On pole in box.
Mineral—Depot waiting room and section house.

Divide—Phone booth near east switch.

19 Creek-Phone booth near east switch.

Coal Canyon—Phone box on pole near east switch.

NINTH SUBDIVISION:

Greendale—Phone box near west switch. McKenna—Section house.

Rainier-Freight house.

Offut Lake—Phone box on pole near west switch. Maytown—Freight house and section house.

Essex-Phone booth near west switch.

Centralia—Freight house.

Chehalis-Section house.

ELEVENTH SUBDIVISION:

Doty-City phone in section house. Firdale—City phone in section house.

TWELFTH SUBDIVISION:

Wahl-Middle of siding.

Everson—Freight house. Hampton—Freight house.

Sumas-Freight house.

SURGEONS MILWAUKEE HOSPITAL ASSOCIATION

HOSPITALS

Dr. J. F. DePree	Chief Surgeon	Seattle
Dr. W. F. Hoffman	Oculist	Seattle
Dr. E. DeMar Anderson	Oculist	Seattle
Dr. D. G. Willard	District Surgeon	Tacoma
Dr. A. W. Howe	Oculist	Tacoma
Dr. S. S. Thordarson	Oculist	Tacoma
Dr. Paul B. Smith	Oculist	Tacoma
Dr. H. L. Maier	Oculist	Tacoma
Dr. Robert F. Kaiser	Oculist	Bellingham
Dr. H. D. Waltz	Oculist	Everett
Dr. W. W. Hicks	Oculist	Ellensburg

Ellensburg	Ellensburg General	Hospital
Cle Elum	Roslyn Cle Elum	Hospital
Everett	Providence	Hospital
Seattle	Providence	Hospital
Port Angeles	Olympia Memorial	Hospital
Tacoma	St. Joseph's	Hospital
Tacoma	Doctors'	Hospital
Hoquiam		Hospital
Chehalis	St. Helen's	Hospital
Bellingham	St_ Luke's	Hospital

Stretchers are located as follows: Othello, Beverly, Ellensburg, Cle Elum, Hyak, Cedar Falls, Tacoma, Morton, Mineral, Black River.

LOCATION	NAME	TITLE	OFFICE TELEPHONE	RESIDENCE TELEPHONE
Othello	Dr. Kenneth G. Pershall	Local Surgean		
Ellensburg	*Dr. Carl W. Olander	" "	2-1461	2-4601
Elum	*Dr. Roy V. Jutzy		Roslyn 61	Cle Elum 79
orth Bend	Dr. J. O. Borgen		Secretary Control of C	
Snogualmie	Dr. P. E. Roth	" "		
Snogualmie	Dr. J. L. Whitaker		<u>.</u>	
Fall City	Dr. W. W. Cheney	" "	A2	Al
Carnation	Dr. Irene C. Werthmann	" "	2000 W NO 100	
Monroe	Dr. Minard Allison		Get thru Monroe Gen. Hospital	
Everett	*Dr. A. H. Gunderson	" "	m construence and control of the con	
Enumclaw	Dr. E. R. Tiffin		163	175
Renton	Dr. H. H. Adams			
Renton	Dr. Lloyd F. Lackie	Asst. "	3461	
Seattle	*Dr. I. F. DePree	Local "	Elliott 3037	Dexter 3921
Seattle	*Dr. C. W. Moen	,, ,,		E 11
Seattle	*Dr. I. M. Cohn	Asst. "	Elliott 2839	Dexter 0212
Seattle	*Dr. Wm. C. Speidel	Local "	Main 1291	RA. 0240
Kent	Dr. J. O. Taylor		590	114
Auburn	Dr. John Darst	" "	199-J	354-M
Auburn	Dr. E. K. Giere			
Sumner	Dr. H. H. Andrews	" "	E 0 20	a (1)
Puyallup	Dr. E. F. McCabe	" "	R = "	
Tacoma	*Dr. D. G. Willard	Local "	Broadway 1193	Main 0630
Tacoma	*Dr. S. E. Adams	Asst. "		
Tacoma	*Dr. G. G. McBride	" "	Broadway 5385	Main 0684
Tacoma	*Dr. A. J. Hermann			17-01
Tacoma	Dr. F. P. Hoskins	n > n		
tonville	Dr. D. M. Nevitt	Local "	113	114
Aberdeen	Dr. K. D. Graham	20,111		
Hoguiam	Dr. R. F. Ballard	" "	E E E E	in which the same is
Chehalis	Dr. L. G. Steck		320W	320R
South Bend	Dr. A. C. Dalinkus			
Longview	Dr. J. L. Norris	,, ,,	LV23	LV580
Port Townsend	*Dr. H. G. Plut			
Port Angeles	*Dr. R. S. Hamilton		156-W	156-W
Port Angeles	*Dr. F. B. Wyman	Asst. "		1
	*Dr. W. C. Moren	Local "	844	845
Bellingham Bellingham	Dr. E. S. Sgrvis	Locul "		
Everson	Dr. J. P. Vette	E 2		

^{*—}Examining Surgeons