

# CHICAGO, MILWAUKEE, ST. PAUL AND PACIFIC RAILROAD CO.

## COAST DIVISION

# TIME TABLE No. 1

Taking effect at 12:01 A.M.

Pacific Standard Time

## TUESDAY, DECEMBER 1, 1959

For the government and information  
of employees only

**A. W. HERVIN**  
Assistant Superintendent

**S. E. HERSOG**  
Assistant Superintendent

**R. C. SCHWICHTENBERG**  
Assistant Superintendent

**N. H. McKEGNEY**  
Superintendent

**Q. W. TORPIN**  
Superintendent of Transportation

**V. P. SOHN**  
General Superintendent of Transportation

**R. G. SCOTT**  
Assistant General Manager

**L. V. ANDERSON**  
General Manager

TABLE OF TRAIN SPEEDS

Seconds per Mile	Miles per Hour	Seconds per Mile	Miles per Hour
45	80	63	57.1
46	78.3	64	56.3
47	76.6	65	55.4
48	75	66	54.5
49	73.5	67	53.7
50	72	68	52.9
51	70.6	69	52.2
52	69.2	70	51.4
53	67.9	75	48
54	66.7	80	45
55	65.5	85	42.4
56	64.3	90	40
57	63.2	100	36
58	62.1	120	30
59	61	144	25
60	60	180	20
61	59	240	15
62	58.1	360	10

### WATCH INSPECTORS

St. Maries.....	H. W. Schumacher
Spokane.....	N. 221 Washington St., Harold J. March
Spokane.....	N. 3 Wall St., Klatt Jewelers
Malden.....	Pacific Watch Co.
Pine City.....	C. N. Harthill
Othello.....	James P. Nelson
Ellensburg.....	304½ No. Pearl St., Chas. E. Dickson
Cle Elum.....	Dean R. Ireland
Seattle.....	First Ave. So. & Lander, c/o Sears, Roebuck & Co., Lonnie Wilcox
Tacoma.....	1016 So. 11th St., A. C. Paulson
Everett.....	2934 Colby Ave., O. P. Nelson
Enumclaw.....	1639 Cole St., Miller's Jewelry
Morton.....	Wright Jewelers
Hoquiam.....	Fred Wetzel
Raymond.....	223 Duryea St., Antilla & Kolcz Jewelers
Bellingham.....	Milton E. Terry
Port Angeles.....	Lewie B. Filion
Port Townsend.....	840 Water St., Walter S. Wisniewski

SECOND CLASS	FIRST CLASS		Capacity in cars		Telegraph Calls	Distance from Avery	Time Table No. 1 DECEMBER 1, 1959	Distance from Malden	See Rule 6-A	Office Hours Also See Page 18 for Other Assigned Hours	FIRST CLASS		SECOND CLASS
	263	15	Sidings	Other Tracks							16	264	
Time Freight	Passenger	Daily			Daily	STATIONS	Daily	Daily	Daily				
L 12.45AM	L 8.45PM			Yard						NF	0.0	<b>AVERY</b> 5.3	108.8
12.55	8.55	59	20		5.3	<b>ETHELTON</b> 8.5	103.5	P	No Office	2.02		9.33	
1.10	264 9.13	120	15		13.8	<b>POCONO</b> 8.6	95.0	P	No Office	1.44		15 9.13	
16 1.30	9.27	127	25		22.4	<b>CALDER</b> 10.9	86.4	P	No Office	263 1.30		8.54	
1.51	9.46	124	19		33.3	<b>ST. JOE</b> 6.6	75.5	P	No Office	1.11		8.29	
2.10	9.56	60			39.9	<b>OMEGA</b> 5.5	68.9	P	No Office	1.01		8.18	
2.24	s 10.06	182	Yard	CB	45.4	<b>ST. MARIES</b> 5.0	63.4	BHJK OPRWXYZ	See Footnote	s 12.51		8.08	
2.33	10.14	55	58		51.3	<b>RAMSDELL</b> 5.9	57.5	P	No Office	12.42		7.59	
2.48	10.26	156	11		57.2	<b>PEDEE</b> 7.2	51.6	P	No Office	12.30		7.46	
3.30	A 10.43PM	121	108	WJ	64.4	<b>PLUMMER JCT.</b> 7.6	44.4	JKPR VXY	Continuous	L 12.16AM		7.30	
3.43		60			72.0	<b>MOWRY</b> 8.1	36.8	P	No Office			6.50	
3.55		113	28	TK	80.1	<b>TEKOA</b> 7.2	28.7	P	7.00 AM to 4.00 PM Except Sat. & Sun.			6.30	
4.05		23			87.3	<b>SEABURY</b> 5.0	21.5	P	No Office			6.16	
4.14		110			93.2	<b>PANDORA</b> 6.5	15.6	P	No Office			6.01	
4.24		51	21		99.7	<b>ROSALIA</b> 5.5	9.1	PV	No Office			5.48	
4.35			28		105.2	<b>SQUAW CANYON</b> 3.6	3.6	P	No Office			5.38	
A 4.45AM			Yard	M	108.8	<b>MALDEN</b>	0.0	BHKP RWXY	12.01 AM to 5.00 PM Except Monday			L 5.30PM	

Passenger trains must not exceed a maximum speed of 70 miles per hour, other trains 45 miles per hour between Avery and Plummer Jct. Passenger trains must not exceed a maximum speed of 55 miles per hour, other trains 40 miles per hour between Plummer Jct. and Malden.

#### EASTWARD TRAINS ARE SUPERIOR TO WESTWARD TRAINS OF THE SAME CLASS

St. Maries is a register station only for trains starting and terminating at that point.

The train order signal at St. Maries applies only to First Sub-division trains.

Automatic Block Signal System is in use between Avery and a point 2902 feet west of Sorrento tunnel No. 41.

The time of No. 15 and No. 16 at Plummer Jct. applies at the junction switch.

#### INDUSTRIAL TRACKS NOT SHOWN AS STATIONS

Name	Cap. In Cars	Miles	Direction	Station
Hoyts Spur	5	0.5	West	Ethelton
Erlmo	45	0.2	West	Pocono
Hepton Spur	5	1.5	West	St. Maries
Lone Pine	17	2.0	West	Tekoa

Office Hours at St. Maries are .....7:00 AM to 3:00 PM  
6:00 PM to 2:00 AM  
except Wed. and Thurs.

Wednesday and Thursday hours .....Continuous

## WESTWARD

## SECOND SUBDIVISION

## EASTWARD

3

SECOND CLASS		FIRST CLASS	Capacity in Cars		Telegraph Calls	Distance from Plummer Jct.	Time Table No. 1 DECEMBER 1, 1959	Distance from Marenco	See Rule 6-A	Office Hours Also See Page 18 for Other Assigned Hours	FIRST CLASS	SECOND CLASS	
387 UP	63	15	Sidings	Other Tracks							16	64	388 UP
Mixed Daily	Time Freight Daily	Passenger Daily									Passenger Daily	Time Freight Daily	Mixed Daily
L 8.45AM	L 6.00AM	L 10.43PM			WJ	0.0	<b>PLUMMER JCT.</b> 6.4	102.7	JKPR VXY	Continuous	A 12.16AM	A 1.15AM	A 2.10AM
	6.09			26	WY	6.4	<b>WORLEY</b> 1.4	96.3	P	7.00 AM to 4.00 PM Except Sat. & Sun.		1.01	
9.03	6.14	10.53	94			7.8	<b>MOZART</b> 5.3	94.9	P	No Office	12.05AM	12.56	1.55
				23		13.1	<b>SETTERS</b> 2.4	89.6	P	No Office			
9.15	7.05	11.02	42			15.5	<b>SAXBY</b> 4.3	87.2	P	No Office	11.56	12.40	1.42
A 9.25AM	A 7.15AM	A 11.07PM	66	8	MU	19.8	<b>MANITO</b> 15.2	82.9	JPRVXY	9.30 PM to 1.30 PM	L 11.51PM	L 12.25AM	L 1.30AM
					SP	35.0	<b>DISHMAN</b> 1.0	67.7	P				
	A 8.15AM			Yard		36.0	<b>SPOKANE YARD</b> 2.8	66.7	BOPR			L 9.30PM	
						38.8	<b>EAST SPOKANE</b> 0.8	63.9					
						39.6	<b>N. P. CROSSING</b> 1.9	63.1		Via U. P. R. R.			
		11.50PM 12.01AM			SN	41.5	<b>SPOKANE</b> 61.2	61.2	BKOP RVWZ		11.05PM 10.55		
		A 1.16AM			RA	102.7	<b>MARENGO</b>	0.0	JPRV WXY		L 9.30PM		

Passenger trains must not exceed a maximum speed of 70 miles per hour, other trains 50 miles per hour.

## EASTWARD TRAINS ARE SUPERIOR TO WESTWARD TRAINS OF THE SAME CLASS

This time-table confers no authority between Manito and Marenco. Union Pacific R. R. time-table and rules govern.

Automatic Block Signal System is in use between Manito and Plummer Jct.

The time of Trains No. 15 and No. 16 at Plummer Jct. applies at the junction switch.

Time of Trains No. 387 and No. 388 applies at U. P. connection on Second subdivision. U. P. connection switch is located in front of depot at Plummer Jct.

SECOND CLASS	FIRST CLASS	Capacity in cars				Telegraph calls	Distance from Malden	Time Table No. 1 DECEMBER 1, 1959 STATIONS	Distance from Othello	See Rule 6-A	Office Hours Also See Page 18 for Other Assigned Hours	FIRST CLASS	SECOND CLASS
		263	15	Siding	Other tracks							16	264
		Time Freight	Passenger									Passenger	Time Freight
Daily	Daily										Daily	Daily	
L 5.00AM			Yard	M	0.0	MALDEN	103.4	BHKPRWXY	12.01 AM to 5.00 PM Except Monday		A 5.15PM		
5.06			27		3.6	PINE CITY	99.8	P	No Office			4.28	
5.10		58			5.6	KENOVA	97.8	P	No Office			4.22	
5.22		63			11.3	ROCK LAKE	92.1	P	No Office			4.12	
5.32		112			17.0	LAVISTA	86.4	P	No Office			3.57	
5.36		26	9		19.2	EWAN	84.2	PW	No Office			3.53	
5.52		110	31		29.6	REVERE	73.8	P	No Office			3.30	
5.58		61			33.7	PAXTON	69.7	P	No Office			3.20	
6.30	L 1.16AM	87	41	RA	44.0	MARENGO	59.4	JPRVWXY	Continuous	A 9.30PM		3.00	
6.42	1.23	59			49.9	HILLCREST	53.5	P	No Office			9.20	
6.46	1.27	107	28		53.5	RALSTON	49.9	P	No Office			9.16	
			25		58.5	PIZARRO	44.9	P	No Office				
6.57	1.37	61			63.3	VASSAR	40.1	P	No Office			9.06	
7.03	1.42	158	33	NE	68.0	LIND	35.4	P	7.00 AM to 4.00 PM Exc. Sat. & Sun.			9.01	
7.12	1.50	63			76.0	SERVIA	27.4	P	No Office			8.53	
7.18	1.55	117	29		80.9	ROXBORO	22.5	P	No Office			8.48	
7.30	2.04	175	50	WX	90.6	WARDEN	12.8	JPY	8.00 AM to 5.00 PM Exc. Sat. & Sun.			8.39	
7.42	2.12	60			99.4	NOVARA	4.0	P	No Office			8.31	
A 8.00AM	As 2.26AM		Yard	SO	103.4	OTHELLO	0.0	BHKOPRTWX	Continuous	L 8.25PM	L 1.30PM		

Passenger trains must not exceed a maximum speed of 55 miles per hour, other trains 40 miles per hour between Malden and Marengo. Passenger trains must not exceed a maximum speed of 79 miles per hour, other trains 55 miles per hour between Marengo and Othello.

#### EASTWARD TRAINS ARE SUPERIOR TO WESTWARD TRAINS OF THE SAME CLASS

Automatic Block Signal System is in use between Marengo and Othello.

At Warden, at east end of siding, the normal position of the west wye switch is for movement from the siding to the west leg of the wye.

The time of eastward trains departing from Othello applies at the east crossover, located 1275 feet east of the depot. Under train order meets or waits, westward trains entering Othello will take siding at this crossover unless otherwise designated in the orders.

#### INDUSTRIAL TRACKS NOT SHOWN AS STATIONS

Name	Cap. In Cars	Miles	Direction	Station
Carlmar	5	3.0	East	Marengo
East Lind	16	0.1	East	Lind
Hole Track	162	1.7	West	Lind

SECOND CLASS	FIRST CLASS		Capacity in Cars		Telegraph calls	Distance from Othello	Time Table No. 1 DECEMBER 1, 1959	Distance from Cle Elum	See Rule 6-A	Office Hours Also See Page 18 for Other Assigned Hours	FIRST CLASS		SECOND CLASS
	263	15	Sidings	Other tracks							16	264	
Time Freight	Passenger										Passenger	Time Freight	
Daily	Daily										Daily	Daily	
L 9.30AM	L 2.36AM		Yard	80	0.0	<b>OTHELLO</b>	98.9	BHKOPR TWX	Continuous		As 8.20PM	A 12.01PM	
9.42	2.49	113	11		9.2	<b>TAUNTON</b>	89.7	P	No Office		8.05	11.05	
9.52	2.55	60	18		15.0	<b>CORFU</b>	83.9	P	No Office		7.56	10.45	
264 10.06	3.06	111	10		24.7	<b>SMYRNA</b>	74.2	P	No Office		7.45	263 10.06	
10.27	3.22	113	Yard	BV	37.8	<b>BEVERLY</b>	61.1	BKPKY	12.01 AM to 4.00 PM Except Sat. & Sun.		7.28	9.20	
					38.8	<b>BEVERLY JCT.</b>	60.1	JPX	No Office				
10.52	3.36	113			44.0	<b>DORIS</b>	54.9	P	No Office		7.16	8.56	
11.12	3.47	60	5		49.6	<b>RYE</b>	49.3	P	No Office		7.05	8.37	
11.42	4.01	103	20		56.6	<b>BOYLSTON</b>	42.3	P	No Office		6.50	8.15	
11.59			17		64.9	<b>EAST KITTITAS</b>	34.0	P	No Office			7.40	
12.04PM	4.21	113	85	KY	67.2	<b>KITTITAS</b>	31.7	KPWXY	8.00 AM to 5.00 PM Except Sat. & Sun.		6.34	7.30	
			14		70.1	<b>REGAL</b>	28.8		No Office				
12.14	4.31	91	48	NB	73.6	<b>ELLENSBURG</b>	25.3	P	8.00 AM to 5.00 PM Except Sat. & Sun.		6.27	7.15	
12.24	4.39	60	27		80.5	<b>THORP</b>	18.4	P	No Office		6.16	7.06	
12.39	4.52	108	8		88.9	<b>HORLICK</b>	10.0	P	No Office		6.05	6.50	
A 1.00PM	As 5.08AM		Yard	CM	98.9	<b>CLE ELUM</b>	0.0	BKPRWX	1.00 AM to 9.00 AM 10.00 AM to 7.00 PM		L 5.53PM	L 6.30AM	

Passenger trains must not exceed a maximum speed of 79 miles per hour. Other trains 55 miles per hour.

EASTWARD TRAINS ARE SUPERIOR TO WESTWARD TRAINS OF THE SAME CLASS

Automatic Block Signal System is in use between Othello and Cle Elum.

Rule 83(B) does not apply at Beverly Jct.

Mountain grade extends from Beverly Jct. to East switch at Kittitas.

At Beverly Jct. the normal position of junction switch is for the Fourth Subdivision.

SECOND CLASS	FIRST CLASS		Capacity in Cars		Telegraph calls	Distance from Cle Elum	Time Table No. 1 DECEMBER 1, 1959 STATIONS	Distance from Seattle	See Rule 6-A	Office Hours Also See Page 18 for Other Assigned Hours	FIRST CLASS		SECOND CLASS
	263	15	Sidings	Other tracks							16	264	
Time Freight	Passenger										Passenger	Time Freight	
Daily	Daily										Daily	Daily	
L 1.15 PM	L 5.08 AM		Yard	CM	0.0	CLE ELUM -11.6-	89.9	BKPRWX	1.00 AM to 9.00 AM 10.00 AM to 7.00 PM	As 5.53 PM		A 6.30 AM	
1.40	5.20	106	34		11.6	EASTON 8.5	78.3	PVY	No Office	5.38		6.12	
1.53	5.30	70	15		20.1	WHITTIER 8.9	69.8	P	No Office	5.26		6.01	
2.09	5.41	98	106		29.0	HYAK 2.6	60.9	PX	No Office	5.15		15 5.41	
2.17	5.46	37			31.6	ROCKDALE 5.1	58.3	PWX	No Office	5.09		5.11	
2.31	5.58	69			38.7	BANDERA 5.3	53.2	P	No Office	4.59		4.56	
2.56	6.07	56	12		42.0	GARCIA 4.5	47.9	P	No Office	4.48		4.41	
3.10	6.17	101	21		46.5	RAGNAR 4.3	43.4	P	No Office	4.39		4.26	
3.23	6.26	135	395	MY	50.8	CEDAR FALLS 4.0	39.1	BJKOPW XYZ	Continuous Except Sat., Sun. & Mon.	4.31		4.01	
3.30	6.32				54.8	BAGLEY JCT. 0.8	35.1	JP	No Office	4.26		2.20	
3.32	6.33	59			55.6	BARNESTON 3.9	34.3	P	No Office	4.25		2.18	
3.43	6.38	115			59.5	TRUDE 8.3	30.4	P	No Office	4.19		2.05	
<sup>16</sup> A 4.08 PM	A 6.49 AM	79	14	MV	67.8	MAPLE VALLEY 10.3	22.1	JPRVX	Continuous	L <sup>203</sup> 4.08 PM		L 1.40 AM	
4.24	7.06			RN	78.1	(N. P. Crossing) RENTON 2.4	11.8	IPV		3.53		1.20	
4.30	7.10		Yard	BI	80.5	BLACK RIVER (U. P. Crossing) 4.3	9.4	IJPRVXY		3.46		1.15	
4.49		111	336		84.8	VAN ASSELT 1.7-	5.1	P	Via. P. C. R. R.			12.45	
	7.26				86.5	ARGO (U. P. Crossing) (N. P. Crossing) 1.7-	3.4	IP		3.38			
					88.2	SPOKANE STREET TOWER 0.7	0.7		Via. P. C. R. R.				
A 6.00 PM					88.9	STACY STREET YARD	0.0	BOPTVXZ				L 12.01 AM	
	As 7.45 AM		Yard	OW	89.9	SEATTLE	0.0	P	Via. U. P. R. R.	L 3.30 PM			

Passenger trains must not exceed a maximum speed of 70 miles per hour. Other trains 50 miles per hour.

EASTWARD TRAINS ARE SUPERIOR TO WESTWARD TRAINS OF THE SAME CLASS

#### INDUSTRIAL TRACKS NOT SHOWN AS STATIONS

Name	Miles	Direction	Station
Landsburg	2.6	West	Trude

This time-table confers no authority between Maple Valley and Seattle. Between Maple Valley and Spokane St. tower, Pacific Coast time-table and rules govern. Between Argo and Union Passenger Station Seattle, Union Pacific R. R. time-table and rules govern.

Rule 83(B) does not apply at Bagley Jct.

Automatic Block Signal System is in use between Cle Elum and Maple Valley.

Mountain grade extends from Cedar Falls depot to one mile west of Hyak.

Marker lamps must be lighted while passing through Snoqualmie Tunnel No. 50 between Hyak and Rockdale.

**SIXTH SUBDIVISION WESTWARD**

Time Table No. 1 DECEMBER 1, 1959 STATIONS	Distance from Seattle	Telegraph calls	Capacity in cars		FIRST CLASS				SECOND CLASS				
					15	51			81	93	263	83	
					Passenger	U. P. R. R. Passenger 458			U. P. R. R. Time Freight 692	Way Freight	Time Freight	U. P. R. R. Time Freight 690	
					Daily	Daily			Daily	Daily Except Sunday	Daily	Daily	
SEATTLE	0.0	OW			L 8.00AM								
STACY ST. YARD	0.0			Yard					L 2.00PM				
SPOKANE ST. TOWER	0.7								2.05				
ARGO (U. P. Crossing) (N. P. Crossing)	1.7				8.08				2.10				
VAN ASSELT	4.3		111	336					2.15				
BLACK RIVER (N. P. Crossing)	6.9	BI		Yard	L 8.16AM	L 5.15PM			L 12.40AM	L 2.30PM	L 6.05PM	L 6.15PM	
KENT 5.0	16.3	K	95	112	8.24	f 5.23			<sup>264</sup> 12.52	<sup>16</sup> 2.46	6.15	6.35	
AUBURN 4.6	21.3	BR	90	134	f 8.30	f 5.29			1.01	3.01	6.22	6.45	
BENROY 2.5	25.9		64			5.35			1.09	3.16	6.27	6.55	
SUMNER 1.7	28.4	UX	91	50	8.39	f 5.40			1.15	<sup>82</sup> 3.21 4.30	6.32	7.05	
PUYALLUP 5.5	30.1		59	22	8.42	5.44			1.20	4.35	6.35	7.15	
TACOMA JCT. (East End Double Track)	35.6	JN	79		8.48	A 5.50PM			A 1.35AM	4.45	6.45	A 7.30PM	
(G.N., U.P. & N.P. Crossing) DEPOT SWITCH	37.1				8.54								
TACOMA 0.5	37.6	MA			As 9.00AM								
(West End Double Track) TIDE FLATS YARD	37.6			Yard					A 5.00PM	A 7.00PM			

Passenger trains must not exceed a maximum speed of 79 miles per hour. Other trains  
55 miles per hour.

**EASTWARD TRAINS ARE SUPERIOR TO WESTWARD TRAINS OF THE SAME CLASS**

**INDUSTRIAL TRACKS NOT SHOWN AS STATIONS**

Name	Miles	Direction	Station
Concora	0.8	West	Black River
Hughes	1.4	West	Puyallup

This time-table confers no authority between Black River and Seattle. Between Black River and Spokane St. tower Pacific Coast R. R. time-table and rules govern. Between Argo and Union Passenger Station Seattle, Union Pacific R. R. time-table and rules govern.

Automatic Block Signal System is in use between Black River and Tacoma Jct.

No. 15 will stop on signal at Auburn to let off revenue passengers from Spokane or points beyond.

No. 51 will stop on signal Kent, Auburn and Sumner to receive revenue passengers for Vancouver, Wash., and beyond.

Double track is in use between Tacoma Jct. and Tide Flats Yard. Trains and engines using these tracks must use the right hand track as prescribed by Rule D-151. Crossover movements and movements against the current traffic between Tacoma Jct. and Depot Switch must be properly protected and all trains and engines must move at restricted speed. Maximum speed must not exceed 15 MPH.

Single track is in use between Depot Switch and Tacoma. Normal position for the switch at Depot Switch is for movement to Tide Flats yard.

At Tacoma Jct. the normal position of junction switch is for the Seventeenth Subdivision.

The following tracks are wired: 6, 7, 8, 12 and east end of track 13, Seattle Union Station, and first three cross-over tracks east of station; Northern Pacific Railway Co. interchange track, Argo, and tracks 1 and 8 Van Asselt.

At Auburn, an auxiliary siding with a capacity of 58 cars is located west of the depot. Rule 5 applies at the siding located east of the depot.

Time Table No. 1 DECEMBER 1, 1959 STATIONS	Distance from Tacoma	See Rule 6-A	Office Hours Also See Page 18 for Other Assigned Hours	FIRST CLASS			SECOND CLASS			
				52	16		264	84	94	82
				U. P. R. R. Passenger 457	Passenger		Time Freight	U. P. R. R. Time Freight 691	Way Freight	U. P. R. R. Time Freight 681
				Daily	Daily	Daily Except Sunday	Daily			
SEATTLE	37.6	P	Via U. P. R. R.		As 3.15PM					
STACY ST. YARD	36.6	BOPT VXZ						A 12.50PM		
SPOKANE ST. TOWER	0.7- 1.7-		Via P. C. R. R.					12.45		
ARGO (U. P. Crossing) (N. P. Crossing)	34.2	IP	Via P. C. R. R.		3.03			12.35		
VAN ASSELT	32.5	P						12.30		
BLACK RIVER (N. P. Crossing)	28.2	LJPRVXY	Continuous	A 12.52PM	A 2.55PM	A 1.01AM	A 4.10AM	A 12.20PM	A 4.40PM	
KENT	21.3	PX	8.00 AM to 5.00 PM Except Sat. & Sun.	12.44	93 2.46	81 12.52	3.56	12.05PM	4.27	
AUBURN	16.3	PX	7.45 AM to 5.00 PM Except Sat. & Sun.	12.38	f 2.40	12.40	3.45	11.30	4.17	
BENROY	11.7	P	No Office	12.33		12.30	3.35	11.05	4.07	
SUMNER	9.2	PVX	7.00 AM to 3.00 PM 4.15 PM to 12.15 AM Except Sat. & Sun.	12.30	2.32	12.24	3.28	11.00	93 4.01	
PUYALLUP	7.5	P	No Office	12.27	2.29	12.21	3.23	10.10	3.57	
TACOMA JCT. (East End Double Track)	2.0	JKPRVX	Continuous	L 12.21PM	2.23	12.11	L 3.10AM	9.55	L 3.45PM	
DEPOT SWITCH	0.5	MPX	No Office		2.17					
TACOMA	0.0	BPX	No Office		L 2.15PM					
(West End Double Track) TIDE FLATS YARD	0.0	BKOPRT VWXYZ	No Office			L 12.01AM		L 9.45AM		

Passenger trains must not exceed a maximum speed of 79 miles per hour. Other trains 55 miles per hour.

**EASTWARD TRAINS ARE SUPERIOR TO WESTWARD TRAINS OF THE SAME CLASS**

**UNION PACIFIC RR — BLACK RIVER**

**WHISTLE SIGNALS:**

To Seattle via Pacific Coast R. R. .... 1 long 1 short 1 long  
To Seattle via Union Pacific R. R. .... 1 long

**NORTHERN PACIFIC RR — BLACK RIVER**

Trains approaching interlocking, desiring to use main track to Tacoma or Seattle will give one long sound of the whistle. Trains desiring to use wye, will give four long sounds of the whistle.

No. 16 will stop on signal at Auburn for revenue passengers to Spokane or points beyond.

Rule 83(B) does not apply at Tacoma and Tide Flats Yard. Eastward trains will obtain Clearance Form A at Tacoma Jct.



		Capacity in cars		Telegraph calls	Distance from St. Maries	Time Table No. 1 DECEMBER 1, 1959 STATIONS	Distance from Elk River	See Rule 6-A	Office Hours Also See Page 18 for Other Assigned Hours	
		Sidings	Other tracks							
L			Yard	CB	0.0	ST. MARIES	72.2	BHJKOPRWXYZ	See Footnote under First Subdivision Page 2	A
		11			9.4	LOTUS -0.4	62.8	P	No Office	
		30	18		11.1	ALDER CREEK -1.7	61.1	P	No Office	
		24			13.5	ROVER -2.4	58.7	P	No Office	
		43			19.6	MASHBURN -6.1	52.6	P	No Office	
		39			21.1	WAYLAND -1.5	51.1	P	No Office	
		25	43		25.1	TYSON CREEK -4.0	47.1	P	No Office	
		23	6		27.1	FERNWOOD -2.0	45.1	P	No Office	
		33			31.7	EMERALD CREEK -4.6	40.5	P	No Office	
		25	184		36.9	CLARKIA -5.2	35.3	PX	No Office	
			7		42.6	KEELER -5.7	29.6	P	No Office	
		30			44.8	SHERWIN -2.2	27.4	P	No Office	
A					50.4	PURDUE -5.6	21.8	JVX	No Office	L
						PURDUE -2.0			Via W. I. & M. R. R.	
						BOVILL				
L		38	57	BO	52.4	BOVILL -8.7	19.8	JPVWXY	8.00 AM to 5.00 PM Except Sat. & Sun.	A
		10			61.1	NEVA -4.0	11.1	P	No Office	
		17	45		65.1	KAMERON -5.2	7.1		No Office	
		13			70.3	JERSEY -1.9	1.0		No Office	
A		10	94		72.2	ELK RIVER	0.0	PWXY	No Office	L

Trains must not exceed a maximum speed of 25 miles per hour.

EASTWARD TRAINS ARE SUPERIOR TO WESTWARD TRAINS OF THE SAME CLASS

This time-table confers no authority between Purdue and Bovill. W. I. & M. Ry. time-table and rules govern except eastward trains will not be required to obtain Clearance Form A at Bovill when operator is not on duty.

Rule 83(B) does not apply at Purdue and Elk River, and does not apply at Bovill when operator is not on duty.

INDUSTRIAL TRACKS NOT SHOWN AS STATIONS

Name	Cap. In Cars	Miles	Direction	Station
Cardwell Spur	9	1.0	West	Rover
Renfrew	19	2.5	West	Wayland
Ryans Spur	7	0.4	East	Fernwood
Jim's Spur	3	1.0	West	Emerald Creek

SECOND CLASS		Capacity in cars		Telegraph calls	Distance from McGuires	Time Table No. 1 DECEMBER 1, 1959 STATIONS	Distance from Coeur d'Alene	See Rule 6-A	Office Hours Also See Page 18 for Other Assigned Hours	THIRD CLASS	
95		Sidings	Other tracks							96	
G. N. Freight Daily Except Sunday										G. N. Freight Daily Except Sunday	
L 9.40AM	43				0.0	McGUIRES	10.4	JPRX	No Office	A 4.01PM	
9.45		25			1.8	POST FALLS -4.4	8.6		No Office	3.40	
10.05		74			6.2	HUETTER -0.9	4.2	VX	No Office	3.20	
10.15					7.1	ATLAS -1.6	3.3	X	No Office	3.10	
A 10.30AM		17			8.7	GIBBS -1.7	1.7	VXZ	No Office	L 3.00PM	
		99		CD	10.4	COEUR D'ALENE	0.0	BPRVXY	7.00 AM to 4.00 PM Except Sat. & Sun.		

Trains must not exceed a maximum speed of 25 miles per hour.

EASTWARD TRAINS ARE SUPERIOR TO WESTWARD TRAINS OF THE SAME CLASS

Rule 83(B) does not apply at McGuires and Gibbs.

**10 WESTWARD NINTH SUBDIVISION EASTWARD**

SECOND CLASS		Capacity in cars		Telegraph calls	Distance from Dishman	Time Table No. 1 DECEMBER 1, 1959	Distance from Metaline Falls	See Rule 6-A	Office Hours Also See Page 18 for Other Assigned Hours	SECOND CLASS	THIRD CLASS
95	291	Siding	Other tracks							292	96
G. N. Freight	Way Freight			Daily Except Sunday	Daily Except Saturday	Way Freight	G. N. Freight				
Daily Except Sunday	Daily Except Saturday	Daily Except Sunday	Daily Except Saturday			Daily Except Sunday	Daily Except Sunday				
	L 8.30AM	56	5	SP	0.0	DISHMAN	120.1	JPRVXY	Continuous	A 3.01PM	
	8.50		17		5.7	GREENACRES	114.4		No Office	2.40	
L	9.30AM	41	71		11.7	SPOKANE BRIDGE	108.4	PRVX	No Office	2.25	A 4.10PM
A	9.40AM	43			15.0	McGUIRES	105.1	JPRVX	No Office	2.15	L 4.01PM
					16.5	(N. P. Crossing) (S. I. Crossing)	103.6	U	No Office		
	9.40		60		16.6	GRAND JCT.	103.5	PVX	No Office	1.45	
	9.55				23.3	RATHDRUM	96.8	PV	No Office	1.20	
	10.30	95	12		37.1	SPIRIT LAKE	83.0	P	No Office	12.30	
	10.55	32			44.7	BLANCHARD	75.4	P	No Office	12.01PM	
	<sup>292</sup> 11.30 12.05PM	52	84	NR	59.0	NEWPORT	61.1	PVXZ	7.00 AM to 4.00 PM Except Sat. & Sun.	<sup>291</sup> 11.30	
	12.15		100		63.5	SULLIVAN	56.6	P	No Office	10.15	
	12.30	15			71.0	DALKENA	49.1	P	No Office	9.55	
	12.45	34	19		76.2	USK	43.9	PXY	No Office	9.40	
	1.05		48		78.1	CUSICK	42.0	PX	No Office	9.30	
	1.30	14			88.3	JARED	31.8	P	No Office	8.55	
	1.52	7			97.0	BLUESLIDE	23.1	P	No Office	8.35	
	2.00	15			100.9	LOST CREEK	10.2	P	No Office	8.25	
	2.12	8			106.6	TIGER	13.5	P	No Office	8.10	
	2.30	48	11		110.6	IONE	9.5	P	No Office	8.00	
A	3.00PM	17	183	MF	120.1	METALINE FALLS	0.0	KPRXYZ	6.30 AM to 3.30 PM Except Sunday	L 7.30AM	

Trains must not exceed a maximum speed of 25 miles per hour between Dishman and McGuires; 30 miles per hour between McGuires and Ione; 25 miles per hour between Ione and Metaline Falls.

**EASTWARD TRAINS ARE SUPERIOR TO WESTWARD TRAINS OF THE SAME CLASS**

Great Northern trains only will register at Spokane Bridge.  
Rule 83(B) does not apply at McGuires and Spokane Bridge.

INDUSTRIAL TRACKS NOT SHOWN AS STATIONS				
Name	Cap. In Cars	Miles	Direction	Station
Opportunity	28	0.8	West	Dishman
Cougar	1	2.3	West	Dishman
Vera	14	4.5	West	Dishman
Seasons	7	6.5	East	Spirit Lake
Calispel	8	0.6	West	Cusick

	Capacity in cars	Telegraph calls	Distance from Warden	Time Table No. 1		Distance from Moses Lake	See Rule 6-A	Office Hours Also See Page 18 for Other Assigned Hours	
				DECEMBER 1, 1959					
	Sidings	Other tracks		STATIONS					
L			WX	0.0	WARDEN	23.2	JPRXY	8.00 AM to 5.00 PM Exc. Sat. & Sun.	A
		14		8.2	TIFLIS	15.0	JPXY	No Office	
		18		10.8	JARDINE	12.4		No Office	
	61	77		14.2	SIELER	9.0	P	No Office	
	17	23		17.2	MCDONALD	6.0	P	No Office	
	24			19.2	GOODRICH	4.0		No Office	
A	57	350	MO	23.2	MOSES LAKE	0.0	PXY	8.00 AM to 5.00 PM Exc. Sat. & Sun.	L

Trains must not exceed a maximum speed of 40 miles per hour between Warden and Tiflis; 35 miles per hour between Tiflis and Moses Lake.

EASTWARD TRAINS ARE SUPERIOR TO WESTWARD TRAINS OF THE SAME CLASS

Rule 83(B) does not apply at Moses Lake.

INDUSTRIAL TRACKS NOT SHOWN AS STATIONS

Name	Miles	Direction	Station
Scalley Spur	0.4	West	Sieler

	Capacity in cars	Telegraph calls	Distance from Tiflis	Time Table No. 1		Distance from Marcellus	See Rule 6-A	Office Hours Also See Page 18 for Other Assigned Hours	
				DECEMBER 1, 1959					
	Sidings	Other tracks		STATIONS					
L	20			0.0	TIFLIS	38.7	JPXY	No Office	A
	27			8.0	RUFF	30.7		No Office	
	28			13.8	MOODY	24.9		No Office	
	22			18.8	BATUM	19.9		No Office	
	22			22.7	LAUER	16.0		No Office	
	22			29.5	SCHOONOVER	9.2		No Office	
	21			33.9	PACKARD	4.8		No Office	
A	25			38.7	MARCELLUS	0.0	Y	No Office	L

Trains must not exceed a maximum speed of 25 miles per hour.

EASTWARD TRAINS ARE SUPERIOR TO WESTWARD TRAINS OF THE SAME CLASS

Rule 83(B) does not apply at Tiflis or Marcellus.

INDUSTRIAL TRACKS NOT SHOWN AS STATIONS

Name	Miles	Direction	Station
Laing	4.6	West	Tiflis
Jantz	4.2	West	Lauer
Reiman	2.0	West	Lauer

		Capacity in cars		Telegraph calls	Distance from Beverly Jct.	Time Table No. 1		Distance from Hanford	See Rule 6-A	Office Hours Also See Page 18 for Other Assigned Hours	
		Sidings	Other tracks			DECEMBER 1, 1959					
L					0.0	BEVERLY JCT.		20.8	JPX	No Office	A
		21			4.0	LEVERING	1.0			No Office	
		60			14.4	PRIEST RAPIDS	10.4		PX	No Office	
A					20.8	HANFORD	6.4		X	No Office	L
						HANFORD YARD	3.6		PVXY		

Trains must not exceed a maximum speed of 30 miles per hour, except from one mile west of Levering to 4 miles west of Priest Rapids 20 miles per hour.

**EASTWARD TRAINS ARE SUPERIOR TO WESTWARD TRAINS OF THE SAME CLASS**

Rule 83(B) does not apply at Hanford and Beverly Jct.

INDUSTRIAL TRACKS NOT SHOWN AS STATIONS

Name	Miles	Direction	Station
M. C. S.	0.8	West	Priest Rapids

		Capacity in cars		Telegraph calls	Distance from Cedar Falls	Time Table No. 1		Distance from Everett	See Rule 6-A	Office Hours Also See Page 18 for Other Assigned Hours	
		Sidings	Other tracks			DECEMBER 1, 1959					
L			Yard	MY	0.0	CEDAR FALLS		54.6	BJKOPRWXYZ	Continuous Except Sat., Sun. & Mon.	A
					5.9	TANNER	5.9		P	No Office	
		67	19		8.0	(N. P. Crossing)	2.1		PX	No Office	
						NORTH BEND	3.2		PX	8.00 AM to 5.00 PM Except Sat. & Sun.	
		80		Q	11.2	SNOQUALMIE FALLS	1.1		PX	No Office	
					12.3	TOKUL	4.6		P	No Office	
					16.9	FALL CITY	5.4		P	No Office	
		92	20		22.3	CARNATION	8.7		P	No Office	
					31.0	DUVALL	5.6		P	No Office	
		29	20		36.6	HIGH ROCK	3.6			No Office	
A					40.2	MONROE JCT.	0.3		JPVX	No Office	L
				RO	40.5	MONROE	6.9				
					47.4	SNOHOMISH	5.8			Via G. N. Ry.	
					53.2	LOWELL	0.5		JVX		
					53.7	BELT YARD	0.5		JVXZ	Via. N. P. Ry.	
		300			53.2	LOWELL	1.4		JVX		
A			Yard	RT	54.6	EVERETT	1.4		BKOPRX	8.00 AM to 5.00 PM Except Sat. & Sun.	L

Trains must not exceed a maximum speed of 30 miles per hour between Cedar Falls and Snoqualmie Falls and between 2 miles east of Carnation and Monroe Jct., 15 miles per hour between Snoqualmie Falls and 2 miles east of Carnation.

**EASTWARD TRAINS ARE SUPERIOR TO WESTWARD TRAINS OF THE SAME CLASS**

Rule 83 (B) does not apply at Monroe Jct. Eastward trains will obtain clearance Form A at Monroe.

This time-table confers no authority between Monroe Jct. and Belt Yard. Between Monroe Jct. and Lowell, Great Northern Ry. Co. time-table and rules govern. Between Lowell and Belt Yard

via the Northern Pacific Ry. Co., the Northern Pacific Ry. Co. time-table and rules govern.

		Capacity in cars		Telegraph calls	Distance from Bagley Jct.	Time Table No. 1 DECEMBER 1, 1959 STATIONS	Distance from Enumclaw	See Rule 6-A	Office Hours Also See Page 18 for Other Assigned Hours		
		Sidings	Other tracks								
L					0.0	BAGLEY JCT. 2.3	16.1	JPRX	No Office	A	
			40		2.3	SELLECK 3.0	13.8	PX	No Office		
					5.3	KANASKAT JCT. 2.1	10.8	JPV	No Office		
		11			7.4	PALMER 1.2	8.7		No Office		
			10		8.6	BAYNE JCT. 0.2	7.5	JPX	No Office		
			20		8.8	BAYNE 1.1	7.3	X	No Office		
					9.9	CUMBERLAND 0.8	6.2		No Office		
		15			10.7	NACO 2.0	5.4		No Office		
			62		12.7	VEAZIE 3.4	3.4	P	No Office		
A			90	CW	16.1	ENUMCLAW	0.0	BOPRVXY	8.00 AM to 5.00 PM Except Sat. & Sun. See Page 18 for Other Assigned Hours	L	

Trains must not exceed a maximum speed of 15 miles per hour between Bagley Jct. and Bayne Jct. and 25 miles per hour between Bayne Jct. and Enumclaw.

**EASTWARD TRAINS ARE SUPERIOR TO WESTWARD TRAINS OF THE SAME CLASS**

At Bayne Jct. and Kanaskat Jct. normal position of junction switch is for joint track between Bayne Jct. and Kanaskat Jct.

Rule 83(B) does not apply at Bagley Jct., Kanaskat Jct. or Bayne Jct.

A derail is located 330 ft. west of junction switch at Bagley Jct.

		Capacity in cars		Telegraph calls	Distance from Park Jct.	Time Table No. 1 DECEMBER 1, 1959 STATIONS	Distance from Ashford	See Rule 6-A	Office Hours Also See Page 18 for Other Assigned Hours		
		Sidings	Other tracks								
L		35			0.0	PARK JCT. 3.5	5.5	JPXY	No Office	A	
			67		3.5	NATIONAL 2.0	2.0		No Office		
A			80		5.5	ASHFORD	0.0	X	No Office	L	

Trains must not exceed a maximum speed of 20 miles per hour.

**EASTWARD TRAINS ARE SUPERIOR TO WESTWARD TRAINS OF THE SAME CLASS**

Rule 83(B) does not apply at Park Jct. or Ashford.

At Park Jct. trains and engines should expect to find cars on siding and on main track west from west switch of siding on Fifteenth Subdivision.

SECOND CLASS			Capacity in cars				Telegraph calls	Distance from Frederickson	Time Table No. 1 DEC. 1, 1959 STATIONS	Distance from Morton	See Rule 6-A	Office Hours Also See Page 18 for Other Assigned Hours	SECOND CLASS		
791	Way Freight	Daily Except Sat. & Sun.	Sidings	Other tracks									792	Way Freight	Daily Except Sun, & Mon.
L 6.57AM			32	34		0.0	FREDERICKSON	53.3	JPRXY	No Office		A 12.35PM			
7.25			72			6.6	THRIFT	46.7	P	No Office		12.05PM			
7.38			30			9.8	TANWAX	43.5	P	No Office		11.55			
8.30			82			20.4	EATONVILLE JUNCTION	32.9	JPXY	No Office		10.55			
			82	30		21.4	EATONVILLE	33.9	PX	No Office					
9.00			92	20		28.3	NEW RELIANCE	25.0	PX	No Office		10.25			
9.15			16	30	BE	33.3	ELBE	20.0	P	8.00 AM to 5.00 PM Except Sat. & Sun.		9.55			
792 9.25 9.40						35.7	PARK JCT.	17.6	JPXY	No Office		791 9.30 9.20			
10.45			27	220	D	39.8	MINERAL	13.5	PX	8.00 AM to 5.00 PM Except Sat. & Sun.		9.00			
10.59			54	42		44.0	DIVIDE	9.3	PX	No Office		8.45			
11.20			15			51.2	COAL CANYON	2.1	P	No Office		6.10			
A 11.30AM			60	155	MN	53.3	MORTON	0.0	BKRPVXY	8.00 AM to 5.00 PM Except Sat. & Sun.		L 6.01AM			

Trains must not exceed a maximum speed of 30 miles per hour.

EASTWARD TRAINS ARE SUPERIOR TO WESTWARD TRAINS OF THE SAME CLASS

Rule 83(B) does not apply at Frederickson and Park Jct.

At Park Jct. trains and engines should expect to find cars on siding and on main track west from west switch of siding on Fifteenth Subdivision.

Frederickson is a register station for No. 791 only.

INDUSTRIAL TRACKS NOT SHOWN AS STATIONS

Name	Miles	Direction	Station
Columbia Powder Co.	0.7	West	Frederickson
Clay City Spur	8.2	East	Eatonville Jct.
Nineteen Creek	1.9	East	Coal Canyon

At Eatonville Jct. and Park Jct. the normal position of junction switch is for the Sixteenth Subdivision.

At Frederickson the normal position of junction switch is for the Seventeenth Subdivision.

SECOND CLASS		Capacity in cars		Telegraph calls	Distance from Tacoma Jct.	Time Table No. 1 DECEMBER 1, 1959 STATIONS	Distance from Longview	See Rule 6-A	Office Hours Also See Page 18 for Other Assigned Hours	SECOND CLASS	THIRD CLASS
791	863	Sidings	Other tracks							792	864
Way Freight	Time Freight			Daily Except Sat. & Sun.	Daily Except Saturday	Way Freight	Time Freight				
Daily Except Sat. & Sun.	Daily Except Saturday	Daily Except Sun. & Mon.	Daily Except Monday								
L 6.00AM	L 8.00PM	79		JN	0.0	TACOMA JCT.	108.4	JKPRVX	Continuous	A 1.30PM	A 5.20AM
6.20	8.45		234		5.3	HILLSDALE	103.1	PX	No Office	1.10	5.00
6.45	9.00	119			9.0	ALLISON	99.4	P	No Office	12.50	4.50
A 6.57AM	9.15		34		13.2	FREDERICKSON	95.2	JPRXY	No Office	L 12.30PM	4.40
			19		16.6	LOVELAND	91.8		No Office		
	9.30	70			21.2	GREENDALE	87.2	P	No Office		4.20
	9.45	20	50		29.0	MCKENNA	79.4	P	No Office		4.03
	10.00	33	12		36.6	RAINIER	71.8	P	No Office		3.47
	10.10		85		42.1	SKOOKUMCHUCK	66.3	JV	No Office		3.36
	10.14			JC	43.2	WESTERN JCT.	65.2	JVP	6.30 AM to 3.30 PM Except Sat. & Sun.		3.33
	10.18	30			44.4	OFFUTT LAKE	64.0	P	No Office		3.30
	10.45	30	39		50.4	MAYTOWN	58.0	JPRX	No Office		3.15
	11.00	51			57.8	ESSEX	50.6	P	No Office		2.45
					62.8	(N. P. Crossing) (U. P. Crossing) BLAKESLEE JCT.	45.6	MX	No Office		
	11.15	40	36	CN	64.1	CENTRALIA	44.3	PXZ	8.00 AM to 5.00 PM Except Sat. & Sun.		2.30
	12.15AM	54	80	CH	67.8	(3 N. P. Crossings) CHEHALIS	40.6	KMPRVX	7.00 AM to 4.00 PM Except Sat. & Sun.		2.15
	A 12.30AM			JO	68.8	(N. P. Crossing) CHEHALIS JCT.	39.6	LJMPVX	10.00 PM to 7.00 AM Except Sat. & Sun.		L 1.15AM
	A 5.00AM				108.4	LONGVIEW	0.0		Via N. P. Ry.		L 12.01AM

Trains must not exceed a maximum speed of 30 miles per hour between Tacoma Jct. and Frederickson, 35 miles per hour between Frederickson and Western Jct., 40 miles per hour between Western Jct., and Mile Post 16, and 15 miles per hour between Mile Post 16 and Chehalis Jct.

#### EASTWARD TRAINS ARE SUPERIOR TO WESTWARD TRAINS OF THE SAME CLASS

This time-table confers no authority between Chehalis Jct. and Longview, Northern Pacific Railway Co. time-table and rules govern.

Automatic Block Signal System is in use between Tacoma Jct. and Hillsdale.

Rule 83(B) does not apply to eastward trains at Chehalis Jct. Unless otherwise provided, eastward trains must obtain clearance Form A at Chehalis.

Frederickson is a register station for No. 791 only.

At Frederickson the normal position of junction switch is for the Seventeenth Subdivision.

Rule 83(B) does not apply at Frederickson and Maytown.

At Maytown the normal position of junction switch is for the Seventeenth Subdivision.

At Skookumchuck, trains will be permitted to move on Weyerhaeuser Timber Company's tracks between the hours of 9 P. M. and 6 A. M., for switching purposes only. Such movements must be protected as prescribed by Rule 99.

#### INDUSTRIAL TRACKS NOT SHOWN AS STATIONS

Name	Miles	Direction	Station
MIDLAND	1.6	East	Allison
UPCO	2.8	West	Offutt Lake

		Capacity in cars		Telegraph calls	Distance from Maytown	Time Table No. 1		Distance from Hoquiam	See Rule 6-A	Office Hours Also See Page 18 for Other Assigned Hours		
		Sidings	Other tracks			DECEMBER 1, 1959	STATIONS					
	L	30	39		0.0		MAYTOWN	56.6	JPRX	No Office		A
			7		9.4		ROCHESTER (N. P. Crossing)	47.2	PU	No Office		
	A				11.3		HELISING JCT.	45.3	JVR	No Office		L
					53.0		ABERDEEN	3.6	P	Via U. P. Ry.		
					56.6		HOQUIAM	0.0	P	Via N. P. Ry.		

Trains must not exceed a maximum speed of 30 miles per hour.

**EASTWARD TRAINS ARE SUPERIOR TO WESTWARD TRAINS OF THE SAME CLASS**

This time-table confers no authority between Helsing Jct. and Hoquiam. Between Helsing Jct. and Aberdeen, Union Pacific Railroad Co. time-table and rules govern. Between Aberdeen and Hoquiam, Northern Pacific Railway Co. time-table and rules govern.

At Maytown the normal position of junction switch is for the Seventeenth Subdivision.

At Helsing Jct. the normal position of junction switch is for the Union Pacific Railroad Co. track.

Rule 83(B) does not apply at Maytown and Helsing Jct.

THIRD CLASS		Capacity in cars		Telegraph calls	Distance from Chehalis Jct.	Time Table No. 1		Distance from Raymond	See Rule 6-A	Office Hours Also See Page 18 for Other Assigned Hours	THIRD CLASS	
963		Sidings	Other tracks			DECEMBER 1, 1959	STATIONS					
	Way Freight Daily Except Sunday				0.0		CHEHALIS JCT.	46.2	LJMPVX	Via N. P. Ry.		
L	9.40AM				16.9		DRYAD JCT.	29.3	JRVX	No Office	A	7.10AM
	9.45		7		17.9		DOTY	28.3		No Office		7.05
	10.01		60		23.1		HILDA	23.1	X	No Office		6.45
	10.30		10		31.6		MACPHAIL	14.6	X	No Office		6.15
	10.43	27			34.9		SUTICO	11.3	X	No Office		5.40
	10.49				36.5		FIRDALE	9.7	X	No Office		5.30
A	11.20AM		Yard	RD	46.2		RAYMOND	0.0	BKORVXY	8.00 AM to 5.00 PM Except Sunday	L	5.00AM

Trains must not exceed a maximum speed of 20 miles per hour between Dryad Jct. and MacPhail, 15 miles per hour between MacPhail and Firdale, 20 miles per hour between Firdale and Raymond.

**EASTWARD TRAINS ARE SUPERIOR TO WESTWARD TRAINS OF THE SAME CLASS**

This time-table confers no authority between Chehalis Jct. and Dryad Jct., Northern Pacific Railway Co. time-table and rules govern.

Rule 83(B) does not apply at Dryad Jct.



		Capacity in cars		Telegraph calls	Distance from Bellingham	Time Table No. 1		Distance from Glacier	See Rule 6-A	Office Hours Also See Page 18 for Other Assigned Hours		
		Sidings	Other tracks			DECEMBER 1, 1959					STATIONS	
L			Yard	BM	0.0	BELLINGHAM (4 G. N. Crossings)	4.0	46.8	BKMORTVXZ	8.00 AM to 5.00 PM Except Sunday	A	
		23			4.0	CORNWALL		42.8		No Office		
		38			11.4	WAHL		35.4		No Office		
		23			17.0	STRANDELL		29.8		No Office		
			30		17.8	EVERSON		29.0	X	No Office		
		25			19.3	HAMPTON		27.5	JXY	No Office		
		17			22.2	CLEARBROOK		24.6		No Office		
			Yard	SU	25.1	SUMAS		21.7	VXY	8.00 AM to 5.00 PM Except Sat. & Sun.		
					26.1	(N.P. Crossing)		20.7	U	No Office		
		21			31.9	HILLTOP		14.9		No Office		
			15		32.7	COLUMBIA		14.1		No Office		
					33.4	LIMESTONE JCT.		13.4	Y	No Office		
			12		36.3	KENDALL		10.5		No Office		
			15		39.5	MAPLE FALLS		7.3		No Office		
A		22	55		46.8	GLACIER		0.0	Y	No Office	L	

Trains must not exceed a maximum speed of 25 miles per hour.

EASTWARD TRAINS ARE SUPERIOR TO WESTWARD TRAINS OF THE SAME CLASS

INDUSTRIAL TRACKS NOT SHOWN AS STATIONS

Name	Miles	Direction	Station
Lind Spur	2.7	West	Bellingham
Cement Spur	3.8	West	Bellingham
Bonneville Spur	3.2	West	Cornwall
Boulder Creek Spur	2.0	West	Maple Falls
Mt. Baker Mill Co.	1.8	East	Glacier

A derail is located on main track west of west wye switch at Glacier.

Rule 83(B) does not apply at Glacier and Hampton.

		Capacity in cars		Telegraph calls	Distance from Hampton	Time Table No. 1		Distance from Lynden	See Rule 6-A	Office Hours Also See Page 18 for Other Assigned Hours		
		Sidings	Other tracks			DECEMBER 1, 1959					STATIONS	
L			20		0.0	HAMPTON	5.4	5.4	JY	No Office	A	
A			Yard	LY	5.4	LYNDEN	0.0	0.0		8.00 AM to 5.00 PM Except Sat. & Sun.	L	

Trains must not exceed a maximum speed of 20 miles per hour. Over Slade Crossing 1.3 miles east of Lynden 3 miles per hour.

EASTWARD TRAINS ARE SUPERIOR TO WESTWARD TRAINS OF THE SAME CLASS

Rule 83(B) does not apply at Hampton and does not apply at Lynden when operator not on duty.

		Capacity in cars		Telegraph calls	Distance from Port Townsend	Time Table No. 1 DECEMBER 1, 1959		Distance from Port Angeles	See Rule 6-A	Office Hours Also See Page 18 for Other Assigned Hours		
		Sidings	Other tracks			STATIONS						
L					0.0	PORT TOWNSEND	50.8	BVX		8.00 AM to 5.00 PM Except Sat. & Sun.	A	
		23			12.3	DISCOVERY JCT.	38.5	VX		No Office		
			10		13.5	MAYNARD	37.3	X		No Office		
		19			24.7	BLYN	26.1			No Office		
		34	8		31.5	SEQUIM	19.3			8.00 AM to 5.00 PM Except Sat. & Sun.		
			7		35.1	CARLSBORG	15.7	X		No Office		
			7		38.9	AGNEW	11.9			No Office		
			12		42.4	CRANE	8.4			No Office		
		23			48.0	ENNIS CREEK	2.8	X		No Office		
A			Yard		50.8	PORT ANGELES	0.0	BKORXYZ		8.00 AM to 5.00 PM Except Sunday	L	

Trains must not exceed a maximum speed of 15 miles per hour between Port Townsend and Discovery Jct., 25 miles per hour between Discovery Jct. and Port Angeles.

**EASTWARD TRAINS ARE SUPERIOR TO WESTWARD TRAINS OF THE SAME CLASS**

**INDUSTRIAL TRACKS NOT SHOWN AS STATIONS**

Name	Miles	Direction	Station
Bekkrvar	2.2	East	Blyn

Rule 83(B) does not apply at Port Townsend.

C. P. MILES,  
W. H. SMITH,  
A. D. BRUNEAU,  
L. H. BAILLY,

R. H. KOUBE,  
F. B. CEDERHOLM,  
G. C. COOPER,  
Train Dispatchers.

R. E. BECK,  
Chief Dispatcher.

R. L. MARTIN,  
Trainmaster.

C. W. McMILLAN,  
C. L. SHAW,  
Travelling Engineers and  
Assistant Trainmasters.

**OFFICE HOURS NOT OTHERWISE SHOWN**

STATION	SATURDAY	SUNDAY	MONDAY	HOLIDAY
Manito				9:30 PM to 1:30 PM
Malden			Continuous	12:01 AM to 5:00 PM
Beverly	12:01 AM to 8:00 AM	12:01 AM to 8:00 AM		
Ellensburg	6:00 PM to 8:00 PM	6:00 PM to 8:00 PM		6:00 PM to 8:00 PM
Cedar Falls	12:01 AM to 3:00 PM	1:00 AM to 4:00 AM	7:00 AM to 11:59 PM	7:00 AM to 3:00 PM
		7:00 AM to 10:00 AM		
Chehalis	7:00 AM to 9:00 AM			
Raymond				8:00 AM to 5:00 PM
Bellingham				8:00 AM to 5:00 PM
Port Angeles				8:00 AM to 5:00 PM

At stations where office hours are shown as continuous, such stations will be open continuous daily including Holidays. At all other stations the office will be closed on Holidays unless hours are assigned as specified above or by bulletin. Holidays include New Years, Washington's Birthday, Decoration Day, Fourth of July, Labor Day, Thanksgiving Day, and Christmas on day set by Proclamation.

## YARD LIMITS AT

- Avery—Extend from 662 ft. east of east switch of yard to 3659 ft. west of west switch of yard.
- St. Maries—Extend from 4339 ft. east of Milwaukee Lbr. Co. spur switch to 2427 ft. west of west switch on First Subdivision, and to 7500 ft. west of west wye switch on Seventh Subdivision.
- Plummer Jct.—Extend from 4591 ft. east of Junction switch to 1655 ft. west of west switch on First Subdivision, and to 2084 ft. west of west wye switch on Second Subdivision.
- Malden—Extend from 3099 ft. east of east switch to 5028 ft. west of west switch.
- Manito—Extend from 2445 ft. east of east switch to Union Pacific Junction switch.
- Clarkia—Extend from 1060 ft. east of east switch to 2000 ft. west of west switch.
- Purdue-Bovill—Extend from 800 ft. east of Purdue to 2279 ft. west of west switch Bovill.
- Elk River—Extend from 3409 ft. east of east switch to end of track.
- Dishman—Extend from 5448 ft. west of west switch to Union Pacific R. R. connection.
- McGuire-Grand Jct.—Extend from 2004 ft. east of east switch McGuire to 1500 ft. west of west switch Grand Jct. on Ninth Subdivision and to 4342 ft. west of junction switch on Eighth Subdivision.
- Newport—Extend from 3348 ft. east of east switch to 3365 ft. west of west switch.
- Usk-Cusick—Extend from 2010 ft. east of east switch Usk to 1754 ft. west of planer track switch Cusick.
- Metaline Falls—Extend from 1946 ft. east of east wye switch to end of track.
- Huetter-Couer d'Alene—Extend from 2000 ft. east of east switch Huetter to end of tracks at Coeur d'Alene including joint track to Rutledge Mill.
- Spokane Bridge—Extend from 3600 ft. east of east switch to 3100 ft. west of west switch.
- Marengo—Extend from 3032 ft. east of east switch to 4976 ft. west of west switch.
- Othello—Extend from 3503 ft. east of east switch to 1000 ft. west of west switch of U and I Sugar Co. track.
- Moses Lake—Extend from 2000 ft. east of east wye switch to Airbase.
- Tifis—Extend from 500 ft. west of west wye switch on Tenth Subdivision to 500 ft. east of east wye switch and from east wye switch to 500 ft. west of west siding switch on Eleventh Subdivision.
- Warden—Extend from wye switches to 3000 ft. west of industry track switch on Tenth Subdivision.
- Beverly and Beverly Jct.—Extend from 3700 ft. east of east switch Beverly to 245 ft. west of junction switch Beverly Jct. on Fourth Subdivision, and 5000 ft. west of junction switch Beverly Jct. on Twelfth Subdivision.
- Kittitas—Extend from 3005 ft. east of east switch to 2989 ft. west of west switch.
- Cle Elum—Extend from 2613 ft. east of east switch to 4314 ft. west of west switch.
- Hyak-Rockdale—Extend from 3069 ft. east of east switch Hyak to 103 ft. west of west portal of Snoqualmie Tunnel.
- Cedar Falls—Extend from 2670 ft. east of east switch to 3895 ft. west of west switch on Fifth Subdivision, and 2900 ft. west of west switch of Log Loading track on Thirteenth Subdivision.
- Maple Valley—Extend from 3000 ft. east of east switch to Pacific Coast R. R. yard limits.
- Black River—Extend from 3063 ft. west of Northern Pacific Railway crossing to Pacific Coast R. R. and Union Pacific R. R. yard limits.
- Kent—Extend from 3000 ft. east of east switch to 1847 ft. west of west switch.
- Auburn—Extend from 3007 ft. east of east switch to 2600 ft. west of west switch connection to Government Yard.
- Sumner—Extend from 3088 ft. east of east switch to 2994 ft. west of west switch.
- Tacoma-Tacoma Jct.-Hillsdale—Extend from 3500 ft. east of east siding switch at Tacoma Jct. to end of track at Tacoma and Tide Flats Yard on Sixth Subdivision and to 1608 ft. west of west switch Hillsdale on Seventeenth Subdivision.
- Priest Rapids—Extend from 2000 ft. east of east switch to 2000 ft. west of west switch.
- Hanford—Extend from Hanford Station Sign (MP 20.79) to 3000 ft. west of west switch Hanford Yard.
- North Bend—Extend from east switch to 3500 ft. west of west switch.
- Snoqualmie Falls—Extend 3100 ft. east of east switch to 2692 ft. west of west switch.
- Monroe Jct.—Extend from 5300 ft. east of junction switch to Monroe Jct.
- Everett-Belt Yard—Extend from Lowell Jct. to end of track Everett, and Belt Yard N. P. Ry. connection to end of track.
- Bagley Jct.—Extend from Bagley Jct. switch to 800 ft. west of switch on Fourteenth Subdivision.
- Selleck—Extend from 2263 ft. east of east switch to 3120 ft. west of west switch.
- Bayne—Extend from 2774 ft. east of Occidental spur switch to 2627 ft. west of Bayne Mine switch.
- Enumclaw—Extend from 1288 ft. east of east wye switch to 2025 ft. west of west switch of Northern Pacific siding and to 1300 ft. east of interchange east switch White River Lbr. Co. R. R.
- Frederickson—Extend from 493 ft. east of east switch to 3250 ft. west of west switch on Sixteenth Subdivision, and 2672 ft. west of west switch on Seventeenth Subdivision.
- Eatonville Jct.-Eatonville—Extend from 2500 ft. east of east switch to 2500 ft. west of west switch Eatonville Jct., and to end of track west of Eatonville.
- New Reliance—Extend from 1000 ft. east of east switch to 2500 ft. west of west switch.
- Park Jct.—Extend from 3060 ft. east of east switch to 2360 ft. west of west switch on Sixteenth Subdivision, and 6468 ft. west of west switch on Fifteenth Subdivision.
- Mineral—Extend from 1438 ft. east of east switch to 1473 ft. west of west switch.
- Divide—Extend from 2500 ft. east of east switch to 3500 ft. west of west switch.
- Morton—Extend from 2578 ft. east of east switch to Kosmos Logging Co. interchange.
- Ashford—Extend from 242 ft. east of east switch to end of track.
- Maytown—Extend from 2874 ft. east of east switch to 1347 ft. west of west switch on Seventeenth Subdivision, and to 3279 ft. west of west switch on Eighteenth Subdivision.
- Blakeslee Jct.-Centralia-Chehalis-Chehalis Jct.—Extend from 512 feet east of N. P. R. R. crossing at Blakeslee Jct. to end of track on C. C. & C. R. R. at Chehalis Jct.
- Dryad Jct.—Extend from junction switch to 1500 feet west of junction switch.
- Hilda—Extend from 1500 feet east of east switch to 1500 feet west of west switch.
- MacPhail—Extend from 2476 ft. east of east switch to 2000 ft. west of west switch.
- Firdale—Extend from 3500 feet west of M.P. 56 to 1000 ft. east of east switch at Sutico.
- Raymond—Extend from 4230 ft. east of east switch to end of track.
- Port Angeles-Ennis Creek—Extend from 2500 ft. east of east switch at Ennis Creek to 1500 ft. west of Bayside yard switch.
- Carlsborg—Extend from 2500 ft. east of east switch to 2500 ft. west of west switch.
- Maynard-Discovery Jct.—Extend from 1500 ft. west of switch Maynard to 1000 ft. east of east switch Discovery Jct.
- Port Townsend—Extend from 2500 ft. west of west main line switch, east to end of yard tracks.
- Bellingham—Extend from 2000 ft. west of Cement Plant switch to end of tracks, including Lake Line, Bellingham.
- Everson-Hampton—Extend from 2000 ft. east of east switch Everson to 2008 ft. west of west wye switch Hampton.
- Sumas—Extend from 1954 ft. east of east wye switch to 2000 ft. west of west wye switch.

## LOCATION OF EMERGENCY TELEPHONES AT AND BETWEEN STATIONS

## FIRST SUBDIVISION:

- Between Ethelton and Pocono—Booth Mile Post 1782.
- Herrick—Box on pole M.P. 1791.
- Between Calder and St. Joe—Booth Mile Post 1801.3.
- St. Maries—At east head block, east yard switch, west end of yard, and west switch.
- Benewah Bridge—West end.
- Little Plummer—Box on post at Signal 59-4.
- Sorrento—Pole just west of road crossing at spur.
- Wallner—Box on pole.
- Lone Pine—Pole opposite spur.
- Swan—Booth west end warehouse.

## SECOND SUBDIVISION:

- Setters—Pole north side of track.

## THIRD SUBDIVISION:

- Malden—Room East of waiting room and on pole at west switch.
- Pine City—Section house.
- Kenova—East switch.
- Rock Lake—Station board.

- LaVista—East and west switches.
- Ewan—Elevator.
- Between Ewan and Revere—Mile Post 1908.
- Revere—East and west switches.
- Paxton—West switch south side.
- Between Paxton and Marengo—Mile Post 1922.
- Marengo—Section house.
- Hillcrest—Station board.
- Ralston—Depot baggage room and west switch.
- Pizarro—Station board.
- Vassar—East and west switch.
- Lind—East switch and depot baggage room.
- Servia—East and west switch.
- Roxboro—East switch and west switch.
- Warden—Section house, depot baggage room and west switch.
- Novara—East and west switch.

## FOURTH SUBDIVISION:

- Othello—East and west switch at roundhouse and car department.
- Taunton—Substation.

## LOCATION OF EMERGENCY TELEPHONES AT AND BETWEEN STATIONS—Continued

M.P. 1999.6—Phone box, Slide area.  
 Corfu—East switch phone box and section house.  
 Smyrna—East switch phone box, section house and depot.  
 M.P. 2023—18 pole lengths east of M.P. 2023.  
 Beverly—East switch phone box, section house and cafe.  
 Columbia River Bridge—West end phone box.  
 M.P. 2029—6 pole lengths west phone box.  
 Doris—Substation and west switch phone box.  
 Rye—West switch phone box.  
 M.P. 2043—8 pole lengths east phone box.  
 Boylston—Section house and west switch phone box.  
 M.P. 2049—12 pole lengths west phone box.  
 East Kittitas—Scale house.  
 Kittitas—Substation.  
 Ellensburg—Baggage Room.  
 Thorp—East switch and west switch phone boxes.  
 Taneum—Watchman's shanty, ½ mi. west of M.P. 2070.  
 Tunnel 47—Just east of M.P. 2073 phone booth.  
 Horlick—East switch and west switch phone boxes and section house.  
 Riverside—Just east M.P. 2079 and M.P. 2080 phone boxes.  
 Cle Elum—Section house, substation, and west switch phone box.

## FIFTH SUBDIVISION:

Signal 5-7—10 pole lengths west of M.P. 2091 phone box.  
 Easton—East switch, baggage room and section house.  
 Bridge 18—M.P. 2100 phone booth.  
 M.P. 2104—6 pole lengths east phone box.  
 Whittier—East switch phone booth, west switch phone box and section house.  
 Meadow Creek—Signal 23-0 phone box.  
 Roaring Creek—¼ mi. west of M.P. 2110.  
 Keecheilus Snow Shed—West end phone booth.  
 Hyak—East switch phone box, section house, substation, baggage room and Signal Mtr.'s house.  
 Rockdale—East switch phone box and west switch phone booth.  
 Humpback Snow Shed—100 feet west phone box.  
 Windy Point—½ mi. west M.P. 2120 watchman's shanty.  
 Bandera—East switch watchman's shanty, west switch phone box.  
 Harris Creek—Phone booth Signal 42-3, M.P. 2124.5.  
 Minot—Watchman's shanty.  
 Garcia—Section house, depot and west switch phone booth.  
 Hull Creek—3 pole lengths east of Change Creek Bridge.  
 Ragnar—East switch and west switch phone booths.  
 Cedar Falls—Substation, waiting room and west switch phone booth.  
 Bagley Jct.—Phone booth.  
 Barneston—West switch phone booth.  
 Trude—East switch and west switch phone booths.  
 Landsburg—½ mi. west M.P. 2148.  
 Maple Valley—Section house, east switch phone box and 2 mi. west near M.P. 2156 phone box.  
 Cedar Mountain\*—Overhead highway crossing phone box.  
 Indian\*—East switch and west switch phone boxes.  
 Elliot\*—Phone box, 1 mi. east phone box, Bridge 14-2 1 mi. west, 13-4 Old Bridge 7 phone box.  
 Renton\*—East switch and west switch phone boxes, outside depot in box.  
 Black River\*—East switch yard phone box, N.P. transfer phone box.  
 Boeing Bridge\*—Signal 7-2 phone box.  
 Davis Crossing\*—Phone box.  
 Van Asselt\*—East end yard.  
 \*—These phones connected to the Pacific Coast Dispatcher at Maple Valley only.

## SIXTH DIVISION:

Black River Intg. Plant—W.B. home signal.  
 Black River Jct.—Yard office.  
 Black River—N.P. crossover phone box.  
 Orilla—Highway crossing phone box.  
 Kent—East switch and west switch phone boxes and freight house.  
 Auburn—East switch phone box freight house east siding switch, and west Army point switch phone box.  
 Benroy—East switch phone box.  
 Sumner—Freight house.  
 Puyallup—East and west switch.

## SEVENTH SUBDIVISION:

M.P. 565—In box.

## EIGHTH AND NINTH SUDIVISIONS:

Vera—Box on pole.  
 Post Falls—Engine house.

Gibbs—Section house.  
 Sachwell—Box on pole.  
 Seasons—Pole box.  
 Jenida—Pole box.  
 Ruby—Box on pole.  
 Vail Tunnel—Booth west end.

## TENTH SUBDIVISION:

Tiflis—East junction switch.  
 Sieler—Pole box east switch.  
 Scalley Spur—Switch.  
 MacDonald—Pole box east switch.  
 Moses Lake—Section Foreman's House.

## TWELFTH SUBDIVISION:

M.P. 9—2 pole lengths east phone box.  
 Priest Rapids—Station house.

## THIRTEENTH SUBDIVISION:

Tanner—In box on pole just west main highway crossing.  
 North Bend—Section house.  
 Snoqualmie Falls—East switch phone booth and baggage room.  
 Fall City—Phone box.  
 Carnation—East switch phone booth and section house.  
 Duvall—Phone box.  
 Monroe Jct.—G.N. phone booth.  
 Everett—Roundhouse.

## FOURTEENTH SUBDIVISION:

Selleck—Phone booth.  
 Kanasket Jct.—Phone booth.  
 Bayne Jct.—Phone booth.  
 Veazie—N.P. booth, also N.P. phone.  
 Enumclaw—Baggage room.

## SIXTEENTH SUBDIVISION:

Frederickson—Depot.  
 Thrift—In building near west switch.  
 Tanwax—On pole at east switch.  
 Kapowsin—Section house.  
 Clay City—Box on pole near loading platform.  
 Eatonville Jct.—Depot.  
 New Reliance—Phone booth near west switch at highway crossing.  
 Elbe—Freight house.  
 Park Jct.—Phone booth near east switch.  
 Old Burt—On pole in box.  
 Mineral—Depot waiting room and section house.  
 Divide—Phone booth near east switch.  
 19 Creek—Phone booth near east switch.  
 Coal Canyon—Phone box on pole near east switch.

## SEVENTEENTH SUBDIVISION:

Tacoma—On pole east end of Bridge C Street.  
 Hillsdale—Phone booths near 60th, 64th and 72nd Streets.  
 Bridge GG-46—Small building.  
 Allison—Booth near west switch.  
 Greendale—Phone box near west switch.  
 McKenna—West switch.  
 Rainier—Freight house.  
 Offut Lake—Phone box on pole near west switch.  
 Maytown—Freight house and section house.  
 Essex—Phone booth near west switch.  
 Centralia—Freight house.  
 Chehalis—Section House.

## EIGHTEENTH SUBDIVISION:

Rochester—In Tool house, near R. R. crossing.

## NINETEENTH SUBDIVISION:

Doty—City phone in section house.  
 Firdale—City phone in section house.

## TWENTIETH SUBDIVISION:

Wahl—Middle of siding.  
 Everson—Freight house.  
 Hampton—Freight house.  
 Sumas—Freight house.

## LOCATION OF PORTABLE TELEPHONES ON FOLLOWING TRAINS:

Nos. 15 and 16—In locker baggage end of dormitory car.

## TONNAGE CHART

TONNAGE RATING—WEST	EP-2	EF-1	EF-2 EF-3	EF-5	TONNAGE RATING—EAST	EP-2	EF-1	EF-2 EF-3	EF-5
Othello to Beverly	CL	CL	CL	CL	Tacoma to Black River	3450	CL	CL	CL
Beverly to Boylston	980	1400	2100	2800	Black River to Cedar Falls	2000	4100	5500	8200
Boylston to Kittitas	1400R	3100R	4650R	6200R	Cedar Falls to Hyak	1250	1700	2550	3400
Kittitas to Cle Elum	3700	5000	7000	10000	Hyak to Cle Elum	CL	CL	CL	CL
Cle Elum to Hyak	3200	4000	5500	8000	Cle Elum to Kittitas	4000	6000	7500	12000
Hyak to Cedar Falls	1250R	2800R	4000R	5600R	Kittitas to Boylston	1300	1670	2500	3340
Cedar Falls to Black River	CL	CL	CL	CL	Boylston to Beverly	1300R	1670R	2500R	3340R
Black River to Tacoma	3450	CL	CL	CL	Beverly to Othello	3200	5000	7000	10000

Dispatcher may increase or decrease above tonnage ratings as may be necessary.

## SURGEONS MILWAUKEE HOSPITAL ASSOCIATION

Dr. J. F. DePree	Chief Surgeon	Seattle
Dr. W. F. Hoffman	Oculist	Seattle
Dr. E. DeMar Anderson	Oculist	Seattle
Dr. J. M. Shiach	Oculist	Seattle
Dr. D. G. Willard	District Surgeon	Tacoma
Dr. A. W. Howe	Oculist	Tacoma
Dr. S. S. Thordarson	Oculist	Tacoma
Dr. Robert F. Kaiser	Oculist	Bellingham
Dr. H. D. Waltz	Oculist	Everett
Dr. W. W. Hicks	Oculist	Ellensburg
Dr. J. M. Nelson	District Surgeon	Spokane
Dr. Carroll Smith	Oculist	Spokane
Dr. R. L. Pohl	Asst. Oculist	Spokane

## HOSPITALS

St. Maries	St. Maries Hospital
Ellensburg	Ellensburg General Hospital
Cle Elum	Roslyn Cle Elum Hospital
Everett	Providence Hospital
Seattle	Providence Hospital
Port Angeles	Olympic Memorial Hospital
Tacoma	St. Joseph's Hospital
Tacoma	Doctors' Hospital
Hoquiam	Hoquiam Hospital
Chehalis	St. Helen's Hospital
Bellingham	St. Luke's Hospital
Spokane	Deaconess Hospital
	St. Luke's Hospital
	Sacred Heart Hospital

Stretchers are located as follows: Avery, St. Joe, Elk River, Bovill, St. Maries, Plummer Jct., Spirit Lake, Malden, Spokane, Lind, Othello, Beverly, Ellensburg, Cle Elum, Hyak, Cedar Falls, Tacoma, Morton, Mineral, Black River.

LOCATION	NAME	TITLE	OFFICE TELEPHONE	RESIDENCE TELEPHONE
Spokane	*Dr. J. M. Nelson	Dist. Surgeon	MAdison 4-5351	KEystone 4-8200
Spokane	*Dr. C. L. Kyle	Local Surgeon	MAdison 4-7744	FAirfax 8-7581
Spokane	*Dr. E. G. Peacock	" "	MAdison 4-2136	MAdison 4-6880
Rosalia	Dr. O. I. Lowry	" "	J3-2061	J3-2066
Spirit Lake	Dr. L. C. Frederickson	" "	MUtual 7-2483	MUtual 7-2496
Newport	Dr. R. E. Morrow	" "	GIbson 7-3139	GIbson 7-4206
Coeur d'Alene	Dr. W. T. Wood	" "	MOhawk 4-2213	MOhawk 4-5632
Ione	Dr. G. M. Richards	" "	HIckman 2-3371	HIckman 2-3571
St. Maries	*Dr. B. A. Rapp	" "	CHerry 5-3511	CHerry 5-5441
St. Maries	Dr. E. M. Sullivan	Asst. Surgeon	CHerry 5-3511	CHerry 5-3091
Moses Lake	Dr. K. P. Conklin	Local Surgeon	RO 5-3433	RO 5-5273
Ritzville	Dr. J. C. Lindsay	" "	" "	" "
Othello	Dr. K. Q. Pershall	" "	HU 8-3812	HU 8-3811
Othello	Dr. G. Love	Asst. Surgeon	" "	" "
Ellensburg	*Dr. Carl W. Olander	Local Surgeon	WOoland 2-1461	WOoland 2-4601
Ellensburg	Dr. R. M. Hill	Asst. Surgeon	WOoland 2-1461	WOoland 2-3327
Ellensburg	Dr. R. H. Welding	" "	WOoland 2-1461	WOoland 2-6651
Ellensburg	Dr. J. W. Devney	" "	WOoland 2-1461	WOoland 2-3657
Cle Elum	*Dr. J. P. Mooney	Local Surgeon	Roslyn 61	Roslyn 635
North Bend	Dr. J. O. Borgen	" "	88-1771	88-1381
Snoqualmie	Dr. F. R. Sutherland	" "	88-3352	88-3535
Snoqualmie	Dr. J. L. Whitaker	" "	88-3352	88-3423
Fall City	Dr. Irene C. Werthman	" "	" "	" "
Carnation	Dr. P. O. Hermann	" "	" "	" "
Monroe	Dr. P. P. Cooley	" "	PYramid 4-3931	PYramid 4-6931
Everett	*Dr. A. H. Gunderson	" "	ALPine 2-0123	ALPine 2-0123
Enumclaw	Dr. E. R. Tiffin	" "	TAylor 5-2222	TAylor 5-3809
Renton	Dr. F. W. Reeb	" "	ALPine 5-2451	" "
Renton	Dr. H. H. Adams	" "	ALPine 5-3232	" "
Seattle	*Dr. J. F. DePree	Local Surgeon	MAIn 3-3037	SUNset 4-3921
Seattle	Dr. H. M. Hackedorn	" "	MAIn 2-3003	GLencourt 4-3151
Seattle	*Dr. I. M. Cohn	Asst. Surgeon	MAIn 3-2839	ATwater 2-9414
Seattle	*Dr. Wm. C. Speidel	Local Surgeon	MAIn 2-1291	PArkway 2-0240
Kent	Dr. J. O. Taylor	" "	ULrick 2-3700	ULrick 2-0568
Auburn	Dr. John Darst	" "	TEmples 3-1680	TEmples 3-3354
Auburn	Dr. R. I. Shapard	" "	TEmples 3-3260	" "
Puyallup	Dr. E. F. McCabe	" "	THorndyke 5-6682	THorndyke 5-8176
Sumner	Dr. J. M. Kanda	" "	UNiversity 3-4162	UNiversity 3-4436
Tacoma	*Dr. D. G. Willard	" "	BRoadway 2-4197	MArket 7-0630
Tacoma	*Dr. S. E. Adams	Asst. Surgeon	FUItone 3-1559	SKYline 2-1492
Tacoma	*Dr. G. G. McBride	" "	BRoadway 2-5385	SKYline 9-7564
Tacoma	*Dr. A. J. Hermann	" "	BRoadway 2-1419	SKYline 9-4632
So. Tacoma	Dr. F. P. Hoskins	" "	GReenfield 4-9300	SKYline 9-0924
Eatonville	Dr. D. M. Nevitt	Local Surgeon	TErrace 2-3111	TErrace 2-3116
Aberdeen	Dr. K. D. Graham	" "	407	3450
Chehalis	Dr. L. G. Steck	" "	SHERwood 8-7143	SHERwood 8-4332
South Bend	Dr. J. C. Proffitt	" "	TRinity 5-5614	TRinity 5-5722
Longview	Dr. J. L. Norris	" "	HAMilton 3-1510	HAMilton 5-4020
Port Townsend	Dr. H. G. Plut	" "	370	483
Port Angeles	*Dr. R. S. Hamilton	" "	GLencourt 7-9411	" "
Port Angeles	*Dr. Albert R. Mangan	" "	GLencourt 7-4761	GLencourt 7-4631
Bellingham	*Dr. W. C. Moren	" "	REgent 4-5990	" "
Bellingham	*Dr. M. E. Altman	" "	REgent 4-4380	REgent 4-0694
Everson	Dr. K. H. Spady	" "	WOodland 6-3441	" "

\*Examining Surgeons.

\*\*Re-examinations only.

## SPECIAL INSTRUCTIONS

## ALL SUBDIVISIONS

## G-1 Employes are prohibited from:

Removing any of the appliances of engines or cars that will endanger the safety of themselves or others.

Standing on top of high cars while passing under bridges or through tunnels.

Getting on the end of an engine or of a car as it approaches them.

Going between or running ahead of moving cars to couple, uncouple, open, close, or arrange knuckles of couplers.

Working on the side of cars or trains where there are buildings, sheds, cattle chutes, or other projections.

Kicking or holding drawbar in position to make a coupling with an approaching car or engine.

Following other dangerous practices.

## G-2 Employes are prohibited from riding:

On engine footboards or pilot steps between engine and car when cars are being pushed.

On leading footboard or pilot steps while coupling engine to cars.

On deadwoods, drawbars, brake beams, journal boxes and brake wheels.

On ends of cars containing lading which may shift.

On engine pilot or footboards, sides or ends of cars, while going in or out of depressed tracks.

On forward footboard or pilot steps of engine in direction the engine is moving except in cases where operating conditions make it necessary for safety and then only one employe must ride on the footboard.

## G-3 When, for any reason, adjustment is necessary to a drawbar, knuckle pin, or locking block prior to making coupling or when coupling does not make, the engine or cars must be separated not less than 20 feet and action taken to prevent the cars from moving before going between the cars to make the adjustments.

## G-4 Whenever a car without a drawbar or draft timber is to be moved by a train or engine and it is necessary to chain the car to other cars or engines, employes are prohibited from going between such car and other cars or engines until the persons performing the work have a thorough understanding with the engineer and other members of the train crew. During the process of chaining up the car, the car itself must be properly secured while being chained to other cars, and if the car is to be chained to the engine, then the car must be secured and the brakes on the engine set to avoid a movement of any kind. The engineer must not release the brakes until he has received verbal information that all employes are out from between the cars or engines, and under no circumstances must employes again go between such car or cars and engines until the engineer and other members of the train crew have been notified and the car properly secured and the engine brake set.

## G-5 Employes must not handle or board cars or engines that bear BAD ORDER cards without first ascertaining the nature of the defect so that they may guard against injury.

## G-6 When using hand holds and ladder or stirrup steps to descend from engines, cars, or other equipment, employes must face the equipment and be sure of a secure hand hold and footing.

## G-7 When run-ways, gang-planks or skids are used in handling freight to or from cars, they must be secured to prevent slipping.

## G-8 When necessary to go outside when engine is either standing or moving, extreme caution must be exercised to avoid slipping or falling from running board.

## G-9 Employes must not step on track rails nor other similar objects when it can be avoided.

## G-10 The use of gasoline stoves and burners in Company's buildings and equipment is prohibited.

The use of oil and bottled gas (Propane) stoves and burners for either cooking, heating or refrigeration is permitted only when authorized by the Company and when installation is made in accordance with Company standards.

The above does not apply to U.S. Army Field Ranges when installed under the supervision of a U.S. Army Commissioned Officer and operated by his men.

To avoid personal injuries and possible damage by fire, when lighting and operating Ajax Baughan caboose oil stoves, employes must be governed by the instructions which are posted in each caboose so equipped.

## G-11 The following cars, loaded or empty, will be handled next ahead of the caboose giving preference in the order shown, except that at least one car must be handled between a flat car loaded with rails and the caboose:

Bad order cars.

Switch rear "S.R." cars.

## G-12 Unoccupied outfit cars of steel underframe or steel center sill construction when inspected and passed by a Car Department inspector, may be hauled in any part of the train.

## G-13 In addition to Consolidated Code Rule 806 about handling of occupied outfit cars, the following will also apply on this Railroad:

When occupied outfit cars are set on a siding, the switches at each end should be spiked to prevent any possibility of a train striking the cars.

The same principle will also apply when such cars are placed on other side tracks; but when for operating reasons, it is not practicable to have the switches spiked, the train dispatcher must be notified.

When occupied outfit cars are standing on other than siding and the switches on each end are not spiked, a yellow signal must be displayed on each end of the outfit cars. Under such conditions, the cars must not be moved except when necessary and then only after the man in charge has given his permission. When other cars are placed on the same track, the yellow signal must be moved to the end of the string of cars on that track where it can be plainly seen.

## G-14 For the comfort of the passengers, the air-conditioning on our air-conditioned passenger trains should be kept operating as long as possible. When approaching stations where cars are to be picked up or set out between the engine and the rear car, the steam line must be blown out at the proper place and the steam shut off before the train stops. At the final terminal of the equipment, when no cars are to be set out between the engine and the rear car, the steam must be shut off as soon as the train stops in the station.

## G-15 When passenger trains are unusually delayed, passengers should be informed as to the cause and extent of delay.

Conductors will make suitable announcements to passengers on trains, or arrange for brakemen and sleeping or parlor car employes to do so.

Agents or Station Masters will see that such announcements are made to passengers in stations when waiting for delayed trains.

Public Address System should be utilized at stations when available.

## G-16 A yellow flag by day stenciled ELECTRIC CHARGE LINE and in addition a yellow light by night, placed at one end or both ends of a passenger car standing on a yard track, indicates that the battery of the car is connected to a charge line. When thus protected, it must not be coupled to or moved before the charge line has been removed. Other equipment must not be placed on the same track so as to intercept the view of the yellow signals without first notifying the workmen; in the absence of the workmen, the signals may be moved to the end of the equipment so placed to afford the necessary protection.

## G-17 The provisions of Rule 30 of the Manual of Rules and Instructions on Air Brake and Train Air Signals Form 2697 Revised, will apply as follows at the following points:

Aberdeen-Miles City-Deer Lodge-Othello.....All Trains  
St. Paul.....Freight Trains only  
Minneapolis.....Passenger Trains only

## G-18 In case of heavy rain or violent windstorm, the operator must notify the section foreman.

## G-19 When a train order office is closed during the period authorized by time-table or bulletin, the light in the train order signal will be extinguished.

## G-20 Excessive use of sand at any point is prohibited and its use must be restricted to actual necessity.

## G-21 In complying with Rule 3, of the Consolidated Code of Operating Rules, the prescribed form for yardmasters and foremen of yard engines to register the time when watches are compared will be the place provided on back of their time slip.

## G-22 When diesel-electric or electric engines are handled dead in train, the following will apply:

When engine handling the train is of the wagon type:—Single unit diesel-electric road switcher, yard switcher or wagon type units may be handled next behind the road engine.

When engine handling the train is of the road switcher or yard switcher type:—Wagon type units or series of such units may be handled next behind the road engine, but road switcher and yard switcher type engines must be separated from the road engine by at least one car and must be separated from each other by one or more cars.

Diesel-electric or electric engines will be handled dead in train on authority of Chief Dispatcher who will specify the train they are to be handled on and where they will be placed in the train.

When a 44 ton diesel engine is being handled dead in freight train, it must be placed at rear of train just ahead of the caboose and when a pusher engine is placed on the rear of the train, the 44 ton diesel engine must be placed behind the pusher. When there is a 44 ton diesel engine on the rear of the train, the train must not be pushed nor pulled from the rear and the dead diesel engine must not be handled in switching movements in conjunction with other cars.

## G-23 Diesel engines moving dead in train will come under the provisions of Rule 813 and when the doors of the engines are locked and the hand brake is not accessible, a freight car with operative hand brakes must be coupled to the diesel with uncoupling mechanism made inoperative.

## G-24 Passenger car equipment may be moved through water up to six inches above the top of rail without damage to the generators or battery and bearing boxes.

When necessary to move passenger car equipment through water from 3 to 6 inches above the rails, the equipment should be pushed through the water to a point where it can be reached from the opposite end by a power unit or other equipment and pulled on through the obstruction.

GENERAL SPEED RESTRICTIONS

G-25 Unless otherwise restricted, the following equipment must not be moved in excess of the maximum speed shown below and further reduction made where conditions require:

TYPE OF EQUIPMENT	M.P.H
Trains handling ore cars Loaded.....	35
Empty .....	40
Trains handling ore loaded in open top equipment other than ore cars .....	40
Trains handling loaded air dumps (must stop when meeting trains on double track).....	25
Work trains with workmen or occupied outfit cars.....	25
Scale test cars On Branch Lines.....	20
On Main Lines.....	25
The following diesel engines either dead in train or operating under own power:	
1670 and 1671, 2000 to 2006 AB, new Nos. 820 and 821, 690 AB to 696 AB .....	50
1610 to 1635 new Nos. 960 to 985.....	45
1600 to 1603 new Nos. 980 to 983.....	40
1699 to 1709 new Nos. 990 to 997.....	30

G-26 When freight cars (except cars that are equipped for passenger train service) are hauled in a passenger train, the maximum speed of that train will be that prescribed for freight trains in that territory unless a different speed is authorized by bulletin or train order.

G-27 Diesel or electric engines with unobstructed view in either direction may be operated at permissible speeds in either direction. Diesel or electric engines with restricted view in one direction must, when operated in that direction, reduce speed to the extent necessary for safe operation.

G-28 Unless otherwise specified, the speed of all trains or engines approaching interlocked railroad crossings must be reduced, and passenger trains must not exceed 45 miles per hour and other trains or engines 25 miles per hour when passing over such crossing. The stated speed must be further reduced where conditions require. This does not apply to railroad crossings protected by automatic signals or gates; trains and engines will approach such crossings at restricted speed and if proper proceed indication is received, may pass over the crossing at the speed prescribed by Special instructions or bulletin.

The speed of all trains must not exceed 20 miles per hour while passing over railroad crossings protected by signals or gates unless otherwise specified.

G-29 The speed of trains handled by Gas-Electric or other similar type power, when consisting of power unit only, must not exceed 10 miles per hour when approaching and passing over railroad crossings protected by automatic signals.

G-30 When flat spots develop enroute on car or engine wheels, speed of train must be reduced to not exceed forty (40) MPH to the first available point of communication, where Conductor or Engineer will notify Chief Dispatcher and be governed by his instructions. If in the judgment of the Conductor or Engineer a lesser speed is deemed advisable, speed of train will be reduced in line with their judgment.

From tests made it develops that it is desirable, in order to reduce the impact, to operate cars or engine with flat spots at a speed either under seventeen (17) MPH or in excess of twenty-three (23) MPH as the most severe impact occurs at speeds seventeen (17) to twenty-three (23) MPH.

X1 Trains handling wrecker derricks must not exceed the following speed limitations. The indicated maximum speeds must be further reduced on tangents and on curves where track is not in proper condition for the specified maximum speeds.

	On Tangent Track	On Curves
First Subdivision.....	35 MPH	25 MPH
Second Subdivision.....	35 MPH	25 MPH
Third Subdivision.....	35 MPH	25 MPH
Fourth Subdivision.....	35 MPH	25 MPH
Fifth Subdivision.....	35 MPH	25 MPH
Sixth Subdivision.....	35 MPH	25 MPH
Seventh Subdivision.....	20 MPH	15 MPH
Eighth Subdivision.....	20 MPH	15 MPH
Ninth Subdivision.....	25 MPH	20 MPH
Tenth Subdivision.....	20 MPH	15 MPH
Eleventh Subdivision.....	20 MPH	15 MPH
Twelfth Subdivision.....	20 MPH	15 MPH
Thirteenth Subdivision.....	25 MPH	15 MPH
Fourteenth Subdivision.....	20 MPH	10 MPH
Fifteenth Subdivision.....	15 MPH	10 MPH
Sixteenth Subdivision.....	25 MPH	20 MPH
Seventeenth Subdivision.....	25 MPH	20 MPH
Eighteenth Subdivision.....	25 MPH	20 MPH
Nineteenth Subdivision.....	20 MPH	15 MPH
Twentieth Subdivision.....	15 MPH	10 MPH
Twenty-first Subdivision.....	15 MPH	10 MPH
Twenty-second Subdivision.....	15 MPH	10 MPH

X2 Trains handling snow plows of all types, locomotive cranes, Jordan spreaders, shovels, pile drivers and ditching machines must not exceed speed limitations shown below. The indicated maximum speeds must be further reduced on tangents and curves where track conditions do not justify the specified maximum speeds. Engine and train crews will make frequent observations of how these machines are riding and when in damaged or questionable condition, or when this equipment is hauled in trains with heavy end trailing, the speed must be further reduced to insure safe movement.

	On Tangent Track	On Curves
First Subdivision.....	35 MPH	25 MPH
Second Subdivision.....	35 MPH	25 MPH
Third Subdivision.....	35 MPH	25 MPH
Fourth Subdivision.....	35 MPH	25 MPH
Fifth Subdivision.....	35 MPH	25 MPH
Sixth Subdivision.....	35 MPH	25 MPH
Seventh Subdivision.....	15 MPH	15 MPH
Eighth Subdivision.....	20 MPH	15 MPH
Ninth Subdivision.....	25 MPH	20 MPH
Tenth Subdivision.....	20 MPH	15 MPH
Eleventh Subdivision.....	20 MPH	15 MPH
Twelfth Subdivision.....	20 MPH	15 MPH
Thirteenth Subdivision.....	20 MPH	15 MPH
Fourteenth Subdivision.....	20 MPH	15 MPH
Fifteenth Subdivision.....	15 MPH	10 MPH
Sixteenth Subdivision.....	20 MPH	15 MPH
Seventeenth Subdivision.....	25 MPH	20 MPH
Eighteenth Subdivision.....	25 MPH	15 MPH
Nineteenth Subdivision.....	20 MPH	15 MPH
Twentieth Subdivision.....	15 MPH	10 MPH
Twenty-first Subdivision.....	15 MPH	10 MPH
Twenty-second Subdivision.....	15 MPH	10 MPH

X3 The speed of all trains or engines passing through turnouts must not exceed 13 miles per hour, except those turn-outs laid with long frogs and designated by Special Instructions or bulletin where the speed may be increased to 25 miles per hour, unless otherwise authorized.

Turnouts laid with long frogs are located at:

Station	Location
Maple Valley	Turnout from CMSStP&P to PCRR track
Tacoma Jct.	Turnout from CMSStP&P to UPRR track

X3 (a) SPRING SWITCHES

Movement in facing point direction over a spring switch not equipped with a facing point lock must not exceed 25 miles per hour. When switch is equipped with a facing point lock, movement may be made at normal speed. If switch is lined for the turnout, the allowable turnout speed must be observed.

Movement in tralling point direction over a spring switch on track for which the switch is lined may be made at normal speed.

Movement in tralling point direction which springs the points must not exceed 40 miles per hour.

If movement is through the turnout, the allowable turnout speed must be observed.

All spring switches except those indicated below are equipped with facing point locks. The speed must not exceed 25 miles per hour when moving against the points at the following spring switches:

Ragnar.....	West siding switch
Tacoma Jct.....	East End of double track
Frederickson.....	Junction switch
Maytown.....	Junction Switch

Signals at spring switches at Tacoma Jct., Frederickson and Maytown indicate only the position of the spring switch.

X3 (b) Speedometers on road engines in main line service must be checked by observing time between "Speed Test Section" signs.

Where there are no "Speed Test Section" signs in use, the check must be made between mile posts at first opportunity after departure from point where engineer takes charge of engine.

The location where test was made, speed at time of check and any variation must be shown on the work report.

"Speed Test Section" signs are located as follows:

First Subdivision.....	Westbound at MP 1776 and 1779
	Westbound at MP 1844 and 1847
	Eastbound at MP 1869 and 1866
Second Subdivision.....	Westbound at MP 1841 and 1844
	Eastbound at MP 1853 and 1850
Third Subdivision.....	Eastbound at MP 1967 and 1970
Fourth Subdivision.....	Westbound at MP 1991 and 1994
Fifth Subdivision.....	Eastbound at MP 2186 and 2189

X3 (c) Under Rule 922, the engineer may permit the fireman, when competent, to handle the engine with the engineer being responsible.

X4 Electric freight engines class EF-1, EF-2, EF-3, and EF-5 must not exceed a speed of 45 MPH.

- X5 Ten minute fuses should be used on First, Second, Third, Fourth, Fifth and Sixth Subdivisions. Five minute fuses should be used on all other Subdivisions except where operating under the rules of another railroad requiring the use of ten minute fuses.
- X6 When any type of engine is used in helper service on passenger trains, the helper engine should be placed on the head end.
- X7 Trains handling logs must come to a stop while passenger trains are being met or are passing.
- X8 The wires on the trolley and transmission line poles and supports carry high voltage. Contact with them either by person or equipment is liable to cause fatal injury or damage to property. **THEY MAY BE HANDLED ONLY BY THOSE WHO HAVE RECEIVED SPECIFIC AUTHORITY TO DO SO.**

If wires are found hanging down or any part of the trolley or transmission system deranged in such a way that a person might come in contact with the wires, the train dispatcher must be notified from the first point of communication.

If conditions are such that train or equipment is unable to pass without touching the wires, the train dispatcher must be notified and he will give necessary instructions.

In case of fire, extinguishers filled with carbon tetrachloride only should be used if it is possible for the extinguishing liquid to come in contact with the wires.

In case of electric shock, resulting in apparent unconsciousness, application of the Back Pressure, Arm Lift Method of resuscitation must proceed immediately; the knowledge of this method is required of all persons having duties within the electrified zone.

Freight trainmen will not be required to ride on top of train in electrified territory unless some real emergency condition exists, which, in the judgment of the conductor of the train, would require special attention from some member of the crew located on top of the car. These instructions are not to be considered as relieving trainmen from the necessity of getting on top of cars while switching operations are carried on when conditions require. However, in no case must trainmen get on top of cars where, on account of lack of clearance, there is danger of contacting any part of energized trolley system.

Due to settling of trolley poles on fills, raising of track when ballast is applied and other similar causes over a period of years, the height of trolley wire above top of rail is variable; and in some locations, it is less than standard height of 24'2".

- X9 At the following stations, the siding is also used as a house track; the train dispatcher need not be notified when cars are left on any of these sidings:

First Subdivision	-----	Seabury
Third Subdivision	-----	Ewan
Seventh Subdivision	-----	All Stations
Eighth Subdivision	-----	All Stations
Ninth Subdivision	-----	All Stations
Tenth Subdivision	-----	All Stations
Eleventh Subdivision	-----	All Stations
Twelfth Subdivision	-----	All Stations
Thirteenth Subdivision	-----	All Stations
Fourteenth Subdivision	-----	All Stations
Sixteenth Subdivision	-----	Thrift, Tanwax, Eatonville Jct., Elbe, Mineral, Morton
Seventeenth Subdivision	-----	Allison, Frederickson, Greendale, McKenna, Rainier, Ofutt Lake, Mayton
Eighteenth Subdivision	-----	All Stations
Nineteenth Subdivision	-----	All Stations
Twentieth Subdivision	-----	All Stations
Twenty-first Subdivision	-----	All Stations
Twenty-second Subdivision	-----	All Stations

- X10 Operation of trains on mountain grades.—In addition to instructions contained in Manual of Rules and Instructions on Air Brake and Train Air Signals, Form 2697 Revised effective Jan. 1, 1958, in which reference is made to rules and paragraph numbers, the following will govern:

- (a) When there is no helper on the rear, the rear car must be one that is equipped with a good hand brake. Conductors are responsible for having trainmen properly stationed.
- (b) When a helper is used on the rear of a freight train, it must be cut in ahead of outfit cars, or cars of insufficient strength to safely resist the push of such helper. (Also see last paragraph of G-22).
- (c) All eastward trains handling loaded log cars and all other trains which, in the engineer's judgment, require increased braking power, will raise air brake train line pressure to 100 lbs. at Hillsdale.  
Feed valve should be set at normal pressure after arrival at Tide Flats Yard.
- (d) Before commencing descent of grade from New Reliance to Eatonville Junction, brake pipe test as per Rule 128 must be made at New Reliance, and retainers must be turned up between New Reliance and Eatonville Junction as per Rule 107. Does not apply to trains handled by diesel electric engines equipped with regenerative braking.
- (e) Before commencing descent of grade from MacPhall to Sutco and from Hillsdale to C Street, Tacoma, a sufficient number of retainers as determined by the engineer handling the train will be turned up to insure proper control of train speed. (See Rules 107 and 130.) When engineer handling train is not familiar with this portion of the railroad, retainers must be turned up on all cars in the train.

- (f) When trains are descending mountain grades and the air brakes are being used, trainmen must watch closely for excessive heating of the wheels and if any are found, the train must be brought to a stop and remain standing a sufficient length of time to permit the wheels to cool.
- (g) Rule 49 (Inoperative Air Brakes) does not apply on mountain grade.
- (h) In electrified territory, the use of retaining valves and the testing of brakes before starting descent is not required providing there has been no change in position of hose cocks or double heading cocks since last test, EXCEPT when necessary to hold train with air brakes, in which case Rules 107, 129 and 130 will govern.
- (i) If regeneration fails while descending mountain grade, the following will apply:  
On freight trains, trains must be brought to a stop immediately, all available retainers turned up as outlined in Rule 130 and the brake pipe pressure fully restored before proceeding.  
On passenger trains, Rule 107 will apply and retainers will be used only when requested by the engineer.

- (j) Engineers on freight trains must adjust the brake pipe feed valve pressure to 90 lbs. and have brake pipe charged to this pressure before commencing descent of mountain grade as per Rule 129. When there is no stop to be made at summit of mountain grade, engineers will adjust the brake pipe pressure to 90 lbs. four miles before reaching summit and trainmen on rear must note that pressure is being raised as indicated by caboose gauge as per Rule 82.

- (k) Whenever the engine handling a freight train is to be detached on a mountain grade, in addition to the use of hand brakes, the engineer on the helper engine will cut in the brake valve on his engine and keep the brake pipe fully charged. If two helpers are used, the one nearest the head end will cut in the brake valve on his engine. When the road engine is again attached to the train, the helper engineer will cut out the brake valve on his engine. Brake pipe test as per Rule 128 must be made before proceeding.

- (l) All trains descending the grade Boylston to Beverly and Rockdale to Cedar Falls with air brakes only, will stop at Rye and Garcia for inspection and to permit wheels to cool.

When air brakes are used in conjunction with regeneration, stop will not be required, but trainmen and enginemens must be governed by Paragraph (f).

- (m) On descending grade when power goes off the line, train must be immediately brought to a stop. If power does not come on the line again within one minute, engineer will notify trainmen who will immediately set enough hand brakes to alone hold the train. When power again comes on the line, engineer will recharge the brake pipe. Hand brakes must not be released until it is known that the air brake system has been fully recharged and the brakes operative.

- (n) All trains descending grade designated as mountain grade in electrified territory with a power unit that will not regenerate, must, upon request of the engineer, turn up all available retainer valve handles just before passing over the summit of such grades and turn them down when foot of grade has been reached. See Rules 107, 129 and 130.

- (o) With no helper at the rear of the train and a backing movement is made during the ascent of the grade, the brake pipe test as per Rule 128 must be made before the backing movement begins; the brake pipe pressure must be fully restored, a sufficient number of hand brakes applied on the rear of the train to properly control the slack, and a man stationed within reach of the Conductor's valve in order to stop the train promptly in case of emergency. If there is a helper in the train when the backing movement is to be made, the following will govern:

When the engineer on the road engine applies the brakes for brake-pipe test, he will cut out the brake valve on his engine and when the test has been completed, the engineer on the helper engine nearest the rear end will cut in the brake valve on his engine, fully recharge the brake pipe and control the air brakes during the backing movement; electric locomotives should be operated in series regeneration during the backing movement.

When the backing movement has been completed, the engineer on the helper engine will make a full service application of the train brakes and cut out the brake valve on his engine; the engineer on the road engine will cut in the brake valve on his engine and release the brakes. Trainmen must know that the brakes on the rear end of the train are released before the train starts.

- X11 In placing passenger equipment with buffers in freight trains, such cars must not be placed between freight cars equipped with top pin lifter couplers unless the top pin lifter couplers have a direct connected uncoupling rod (not a chain) and provided the coupler heights are such that the buffer will not come in contact with the lock lifter or the uncoupling rod.

Express refrigerators or passenger cars equipped with U. C. brake equipment, when handled in freight trains, should be handled on the head end of the train.

Passenger cars equipped with L. N. brakes can be hauled in either head or rear end of freight trains.

- X12 When safe operation of trains will permit, brakes should not be applied on engine or cars during dry weather while passing over Bridge EE-384-B, four and one-half miles west of Ellensburg; Bridge EE-386-B, five and one-half miles west of Ellensburg, or other open deck trestles or bridges between Malden and Tacoma.



- X13 At Tacoma Jct., when there are train orders affecting yard movements or westward trains moving to Tide Flats Yard or Tacoma on the Sixth Subdivision, Train Dispatcher will instruct the Operator to stop such movements before making delivery of the train orders.
- X14 The following passenger cars are equipped with Waukesha or similar type engines and come under the provisions of Rule 892:

Touralux sleepers	5752, 5753 and 5754
Diner	114
P & B Cars	206 and 207
Coaches	454 to 478, inclusive
Coaches	649, 650 and 651
Super Dome Cars	50 to 59, inclusive
All Business Cars	

(Instructions for shutting off and turning on air conditioning will be found in electrical control locker in each car.)

Circulating fans must be shut down on all cars standing in the tunnel. Use of lights and other electrical equipment must be held to a minimum to prevent excessive discharge of batteries.

Blower fans on all steam jet air conditioned cars standing OUTSIDE the tunnel ONLY, may be used to keep the cars properly ventilated.

- X15 At Plummer Jct., Manito, Marengo, Maple Valley, Black River and Tacoma Jct., trains other than those displaying signals for a following section, may register by register ticket.

- X16 Seattle water shed extends from one mile east of Cedar Falls station to Landsburg, and from Cedar Falls station to one mile west of station on Thirteenth Subdivision. All toilets must be kept locked in trains in this district and in city limits Renton and Seattle. Refuse must not be thrown from private, dining, or other cars within these limits. Conductors will be held responsible for strict observance of this rule.

- X17 In addition to those designated in timetable, standard clocks are located in Tide Flats Yard Office, Train Dispatcher's Office, Tacoma Roundhouse Office, Spokane Roundhouse and Telegraph Office.

- X18 Manually controlled crossing signals are in use at D Street, Tacoma. Movement on team track over D Street must be protected by a member of the crew taking a position at the crossing to warn highway traffic of approaching trains.

- X19 If trolley wires are observed to be slack the pantograph should be lowered and Engine drifted by. If there is any question about low wires becoming entangled with Engine or cars, train should be brought to a stop immediately and actual condition with regard to clearance of wires above Engine and cars should be determined before proceeding.

- X20 Eastward second and inferior class trains and engines and yard movements must not enter upon the eastward main track between Depot Switch and Tacoma Jct. until it has first been determined that all eastward first class trains due at Tacoma Jct. have passed Tacoma Jct. Westward second and inferior class trains and engines and yard movements must not enter upon the westward main track between Tacoma Jct. and Depot Switch until it has first been determined that all westward first class trains due at Tacoma have arrived Tacoma.

- X21 Cle Elum Substation is operated automatically. Emergency switch is located in Cle Elum Depot just west of Operator's desk which may be opened in an emergency, but after doing so, Train Dispatcher must be notified so that proper protection will be provided in addition to flagging air gap.

**X22 CREWS HANDLING ELECTRIC ROTARY SNOW PLOWS WILL BE GOVERNED AS FOLLOWS:**

- (A) When moving to and from terminals, not in snow operation, pantograph must be locked down and secured to prevent coming in contact with trolley. Grounding switch must be in proper position.
- (B) Must have regular air gap order at all times.
- (C) When handled by diesel power and crew has air gap order, pantograph must be locked down and secured before passing air gap and order issued: "May pass air gap after it is known pantograph is locked down and secured."
- (D) Crews handling these machines are responsible for knowing pantograph is properly secured and grounding switch is in proper position.

- X23 The RS-12 sign located just east of Plummer Jct. governing westward trains, applies only to trains entering Second Subdivision.

- X24 The junction switch at Plummer Jct. is equipped with an electric lock. Instructions for operating switch are posted in back of lower door of the electric lock.

- X25 In the State of Idaho signal 14(1) must be sounded for private crossings the same as for public crossings.

- X25 (a) Under Rule 806 (A) the words "or other lading" will not apply to cars loaded with logs.

- X25 (b) Under Rule 852, when the control cab of an electric engine at the front of a freight train is not provided with a seat for the forward trainman, the forward trainman will ride in a trailing unit.

**X26 TROLLEY CUT-OUT SWITCHES**

All employes working in electrified territory must have a copy of Special Rules and Instructions covering Electrical Operation, Form 3170, in their possession while on duty.

MAIN LINE TROLLEY SECTIONALIZING SWITCHES AND AIR GAPS located between Othello-Seattle-Tacoma are shown on Pages 40-45 inclusive in Form 3170.

**FIRST SUBDIVISION**

- X27 Speed Restrictions (in addition to General Speed Restrictions)
- |  |                   |
|--|-------------------|
|  | Maximum Speed MPH |
|  | All Trains        |
| All trains must approach and leave passenger station at Avery at restricted speed. |                   |
| Over street crossings St. Maries.....  | 20                |
| Trains handling logs except when loaded on staked cars.....                        | 30                |
| Corporate Limits Town of Tekoa, Wash.....  | 40                |
| Corporate Limits Town of Rosalia, Wash.....  | 50                |
| Corporate Limits Town of Malden, Wash.....   | 35                |

- X28 At Avery, the cross-over switches between Nos. 1 and 2 yard tracks, west yard, except when being used, must be lined and locked for through movement on Nos. 1 and 2 track, respectively.

- X29 At St. Maries employes must be alert to the possibility of close side clearance when handling cars loaded with logs and when moving past cars loaded with logs on an adjacent track.

**SECOND SUBDIVISION**

- X30 Speed Restrictions (in addition to General Speed Restrictions)
- |   |                   |
|---|-------------------|
|   | Maximum Speed MPH |
|   | All Trains        |
| Trains handling logs except when loaded on staked cars.....   | 30                |
| Spokane passenger depot, trains handling Dome Car account depot platforms and girder encasements..... | 10                |

**THIRD SUBDIVISION**

- X32 Speed restrictions (in addition to General Speed Restrictions)
- |   |                   |        |
|---|-------------------|--------|
|   | Maximum Speed MPH |        |
|   | Psg.              | Other  |
|   | Trains            | Trains |
| Through City Limits at Malden, Wash.....  | 35                | 35     |
| Through City Limits at Lind, Wash.....    | 70                | 55     |
| Through City Limits at Warden, Wash.....  | 50                | 50     |
| Through City Limits at Othello, Wash..... | 40                | 40     |

- X33 All trains must approach and leave passenger station at Othello at restricted speed.

- X34 When there is a passenger train standing on the main track in the vicinity of the depot at Othello, unnecessary train, switch or engine movements should not be made on the lead track while carmen are between these two tracks watering passenger train.

When such movements are made, extreme caution should be used to avoid injury to these carmen.

- X35 At Novara when a westward train is holding main track to meet an eastward train there, it should stop back of battery box 1500 feet west of east siding switch until eastward train approaches.

- X36 Rock slide detector fences 657 feet in length located just east of tunnel 44 and 425 feet in length located 800 feet west of west switch Rock Lake siding, are in service.

The signals are of the semaphore type, displaying indications in accordance with Rules 240-A, 240-D and 240-G.

For westward trains, if one or both fences have been operated the westward signal located 3293 feet east of tunnel 44 will display approach indication 240-D, and next signal located 1077 feet east of tunnel 44 will display stop indication 240-A.

For eastward trains, if west slide fence is operated eastward signal located 6000 feet west of tunnel 44 will display stop indication 240-A. When fence east of tunnel 44 is operated eastward signal located 6000 feet west of tunnel 44 will display approach indication 240-D and next signal located 360 feet west of tunnel 44 will display stop indication 240-A.

When fences are normal, signals in either direction will display a proceed indication, Rule 240-G.

These signals are not controlled by track circuits and only indicate condition of the slide detector fences.

Trains must stop before passing a signal displaying a stop indication. After stopping, train may then proceed prepared to stop short of obstruction within the area protected by the slide fence and must know that track and bridge structures are in a safe condition.

**FOURTH SUBDIVISION**

- X37 Speed Restrictions (in addition to General Speed Restrictions)
- |  |                   |        |
|--|-------------------|--------|
|  | Maximum Speed MPH |        |
|  | Psg.              | Other  |
|  | Trains            | Trains |
| Corporate Limits Town of Othello, Wash.....    | 40                | 40     |
| Corporate Limits Town of Kittitas, Wash.....   | 65                | 50     |
| Corporate Limits City of Ellensburg, Wash..... | 50                | 35     |
| Corporate Limits Town of Cle Elum, Wash.....   | 60                | 50     |

## FIFTH SUBDIVISION

## X38 Speed Restrictions (in addition to General Speed Restrictions)

	Maximum Speed MPH	
	Psg. Trains	Other Trains
Corporate Limits Town of Cle Elum, Wash.....	60	50

X39 Trains handling logs loaded on flat cars without side stakes should not exceed a speed of 15 MPH when operating over bridge FF-120, one mile west of Cedar Falls Depot.

## SIXTH SUBDIVISION

## X40 Speed Restriction (in addition to General Speed Restrictions)

	Maximum Speed MPH	
	Psg. Trains	Other Trains
Over N.P. Crossing Black River.....	35	35
East Leg of Wye Black River.....	13	13

X41 At Tacoma, the normal position of the crossing gate over the N.P. crossing at Lincoln Avenue east of the roundhouse, is for movements on the CMST&P tracks.

X42 Manually controlled switches for operating traffic signal lights at the foot of west end of Eleventh Street Bridge Tacoma must be operated when switching movements are made over Eleventh Street.

X43 Manually controlled switches are installed to permit the starting or stopping by hand of crossing signals at Pacific Highway crossing at Sumner.

This switch consists of a knob, with a cover locked with a switch lock, on a box mounted on the instrument case for the crossing signals which is between the main track and siding and just east of the crossing. To operate, unlock cover, turn knob in one direction to stop signals, and opposite direction to start signals.

X44 At Tacoma, before a train or engine enters onto or makes a move over the crossing at Pacific Avenue, South 26th Street and Wakefield Drive, a trainman must first place the City Traffic lights at the crossing in a STOP position by operating switch located in box on either side of crossing.

After movement has been completed, the Traffic lights must be restored to normal position by operating switch located in box on opposite side of crossing.

X45 Union Pacific Class Engines 3800, 3900 and 4500 HP Alco-GE gas turbine electric engines are prohibited from using the following tracks between Black River and Tacoma Jct.:

Sumner: Associated Frozen Foods Track. Track over Stuck River Bridge serving Standard Brands, Fibreboard Products and Pacific Lumber Agency.

In addition to the above restrictions, the maximum speed permissible for this class engine between Tacoma Jct. and Black River is 60 MPH, subject to speed restrictions due to curvature and other time-table or special instructions.

D-12	D-45	D-15	D-38
D-16	D-24	D-10	D-48
D-30	D-20	D-6	D-60
D-40			

Note: The number following the D indicates the horsepower, in hundreds, and includes all engines of that horsepower.

X46 Eastward trains having authority to hold main track when meeting westward trains at Puyallup must not pass signal at west switch until westward train has arrived. A train on main track between switches will give a westward train a stop indication at the west switch at Sumner.

X47 The signal located 850 feet west of Tacoma Jct. office on Sixth Subdivision governs eastward movements from eastward track and will display indications in accordance with Rules 240-A Fig. 6, and 240-K Fig. 5.

The eastward signal located 225 feet west of Tacoma Jct. office on Seventeenth Subdivision governs eastward movements and will display indications in accordance with Rules 240-A Fig. 3, 240-D Fig. 3, 240-G Fig. 3, 240-K Fig. 1.

The three-unit westward signal located 550 feet east of Tacoma Jct. office governs westward movements as follows:

The top unit governs westward CMST&P movements to the Seventeenth Subdivision and will display indications in accordance with Rules 240-A Fig. 4 and 240-D Fig. 4.

The middle unit governs westward movements to the UP track and will display indications in accordance with Rules 240-A Fig. 4 and 240-J Fig. 2.

The lower unit governs westward CMST&P movements on Sixth Subdivision and will display indications in accordance with Rules 240-A Fig. 4 and 240-K Fig. 3.

The signal located 35 feet east of Tacoma Jct. office on the UP track governs movements to CMST&P track and will display indications in accordance with Rules 240-A Fig. 1, 240-D Fig. 1 and 240-G Fig. 1.

X48 All eastward trains from Tacoma Line, will, upon arrival at Black River Yard, register with operator Black River Tower by telephone unless register check has previously been left at Tower.

## SEVENTH SUBDIVISION

## X49 Speed Restrictions (in addition to General Speed Restrictions)

	Maximum Speed MPH All Trains
1750 HP four wheel truck diesel between MP 38.6 and Elk River....	15
Around all sharp curves.....	15
Over bridges EE-504 and EE-506 between MP 7 and Rover.....	15

X50 Tracks Nos. 2 and 3 in WI&M Yard at Bovill are not safe for engines.

## EIGHTH SUBDIVISION

## X51 Speed Restrictions (in addition to General Speed Restrictions)

	Maximum Speed MPH All Trains
Between McGuire and Coeur d'Alene 1000 HP, 1200 HP and 1750 HP 4-axle diesels.....	15

X52 Eastward Great Northern trains starting at Coeur d'Alene that are to enter the Eighth Subdivision at Gibbs must, unless otherwise provided, obtain CMST&P Clearance Form A at Coeur d'Alene.

X53 Connection switch with Northern Pacific RR Co. is located 2746 feet west of MP 22 at Huetter. Northern Pacific trains and engines may use joint CMST&P-GN main track between this connection and the connection switch to chip yard of the Ohio Match Co. in accordance with Rule 93.

## NINTH SUBDIVISION

## X54 Speed Restrictions (in addition to General Speed Restrictions)

	Maximum Speed MPH All Trains
Between Dishman and McGuire 1000 HP, 1200 HP and 1750 HP 4-axle diesels.....	15
On curve one and one-half miles west of Newport.....	20
Trains handling logs except when loaded on staked cars.....	25
Corporate Limits Town of Metaline Falls, Wash.....	25
Corporate Limits Town of Ione, Wash.....	25
Corporate Limits Town of Cusick, Wash.....	30

X55 Westward Great Northern trains starting at Spokane that are to enter the Ninth Subdivision at Spokane Bridge must obtain a CMST&P clearance Form A at the GN telegraph office at Spokane.

X56 CMST&P trains that are to enter the Union Pacific siding at Dishman, must stop before passing the stop sign at the junction switch and may then proceed, being governed by operating rules and existing conditions.

X57 Three yellow discs are mounted on uprights on the bents on north side of Bridge WN-100 over Box Canyon, located between MP 98 and MP 99, between Ione and Vail Tunnel, to act as a slide warning device.

If any of these signs are missing or disarranged, trains must stop and inspect bridge to know it is safe before passing over it.

Trains must not exceed 10 MPH over this bridge.

## TENTH AND ELEVENTH SUBDIVISIONS

## X58 Speed Restrictions (in addition to General Speed Restrictions)

	Maximum Speed MPH All Trains
Tiflis to M.P. 12.8 west of Goodrich 1000 HP, 1200 HP, GP-9 4-wheel truck 1750 HP and SD-7 6-wheel truck 1750 HP Diesels.....	35
M.P. 12.8 to Moses Lake 1000 HP, 1200 HP, GP-9 4-wheel truck 1750 HP and SD-7 6-wheel truck 1750 HP Diesels.....	15
Tiflis between switches on Moses Lake leg of wye.....	10
Corporate Limits Town of Moses Lake, Wash.....	25
Tiflis to Marcellus 1000 HP, 1200 HP and 1750 HP 4-wheel truck diesels.....	15

## TWELFTH SUBDIVISION

## X59 Speed Restrictions (in addition to General Speed Restrictions)

	Maximum Speed MPH All Trains
Beverly to Hanford 1000 and 1200 HP Diesels.....	25
1750 HP 4-wheel truck Diesels.....	15

## THIRTEENTH SUBDIVISION

X60 Speed Restrictions (in addition to General Speed Restrictions)

	Maximum Speed MPH All Trains
Monroe to Cedar Falls	
1000 and 1200 HP Diesels.....	25
1750 HP 4-wheel truck Diesels.....	15
1.5 miles west Cedar Falls to one-half mile east Tanner.....	15
Within Yard Limits Snoqualmie Falls.....	6
Trains handling logs:	
Over highway crossing at Tanner.....	10
2 miles east of Carnation to Carnation.....	15
On Curve just west MP 38, about 2 miles east Monroe Jct.....	25
Over Bridge FF-962 between MP 39 and 40, about one-half mile east Monroe Jct.....	15
Corporate Limits Town of North Bend, Wash.....	15
Corporate Limits Town of Carnation, Wash.....	20
Corporate Limits Town of Duvall, Wash.....	20

## FOURTEENTH SUBDIVISION

X61 Speed Restrictions (in addition to General Speed Restrictions)

	Maximum Speed MPH All Trains
Bagley Jct. to Enumclaw	
1750 HP 4-wheel truck Diesels.....	15
Corporate Limits Town of Enumclaw, Wash.....	25
Between Kanaskat Jct. and Bagley Jct., trains handling wrecking derrick, pile driver or locomotive crane.....	10
X62 Between Bayne Jct. and Bagley Jct. via joint track, Northern Pacific wrecking derricks 41 to 48, inclusive, Pile Driver 25 not permitted.	
X63 At Seleck the Cascade Timber Company's tracks may be used to a point 250 feet beyond the east switch. All movements must be made at restricted speed, looking out for engines and cars of the Cascade Timber Company. Deraill is located on west end of Northern Pacific siding and on Cascade Timber Company's track 1000 feet west of west yard switch.	

## FIFTEENTH SUBDIVISION

## SIXTEENTH SUBDIVISION

X64 Speed Restrictions (in addition to General Speed Restrictions)

	Maximum Speed MPH All Trains
Eastward trains New Reliance and Eatonville Jct.....	20
Over Nisqually River Bridge.....	15
On curve 1 mile east Mineral.....	15
2 miles west of Divide and Coal Canyon.....	15
Coal Canyon and Morton.....	25
Corporate Limits, Town of Eatonville, Wash.....	20
Corporate Limits, Town of Morton, Wash.....	15
From St. Paul Reload track switch to west end interchange at Morton.....	15
X65 When shoving cars over highway crossings on Kosmos Logging Line between Morton and Interchange Track, trains must come to a full stop and flag the crossing. During the night the crossing floodlight must be lighted for all trains while passing over crossing.	

## SEVENTEENTH SUBDIVISION

X66 Speed Restrictions (in addition to General Speed Restrictions)

	Maximum Speed MPH All Trains
Over C and D Streets, Tacoma.....	10
Between Tacoma Jct. and Hillsdale.....	15
Over RR Crossings Blakeslee Jct.....	20
Over RR Crossings Chehalis Jct.....	10
Through spring switch turnout and around curve to interchange switch at Frederickson.....	20
X67 Chehalis and Western Ry. Co. trains will not register at Maytown.	
X68 At Chehalis the normal position of the crossing gates over the NP crossings is for movements on the CMStP&P tracks.	
X69 Eastward trains and engines moving between Hillsdale and Tacoma Jct. must stop before passing stop board located just west of C Street.	
X70 Trains handling logs must not move over bridge FF-276B located 3500 feet west of Tacoma Jct. when trains are passing underneath bridge on Northern Pacific tracks.	

## EIGHTEENTH SUBDIVISION

X71 Speed Restrictions (in addition to General Speed Restrictions)

	Maximum Speed MPH All Trains
Maytown to Helsing Jct.	
1000 and 1200 HP Diesels.....	25
1750 HP 4-wheel truck Diesels.....	15

## NINETEENTH SUBDIVISION

X72 Speed Restrictions (in addition to General Speed Restrictions)

	Maximum Speed MPH All Trains
Dryad to Raymond	
1750 HP 4-wheel truck Diesels.....	15

## TWENTIETH SUBDIVISION

X73 Speed Restrictions (in addition to General Speed Restrictions)

	Maximum Speed MPH All Trains
Bellingham to Glacier	
1750 HP 4-wheel truck Diesels not permitted.	
1000 and 1200 HP Diesels.....	15
On OPC track between east wye switch and end of track Limestone Jct.....	10
Limestone Jct. to Glacier.....	10
X74 At Bellingham, the normal position of the crossing gates over the crossing of the GN track in the yard, is for movements on the GN track.	
X75 When trains operating on the Twentieth Subdivision are double-headed, there must be at least 8 cars between engines.	

## TWENTY-FIRST SUBDIVISION

## TWENTY-SECOND SUBDIVISION

X76 Speed Restrictions (in addition to General Speed Restrictions)

	Maximum Speed MPH All Trains
Port Angeles to Discovery Jct.	
1750 HP 4-wheel truck Diesels.....	15
Discovery Jct. to Port Townsend	
Only 600 HP and 6-wheel truck Diesels may be operated.	
Over Morse Creek Bridge at MP 45 to 1/2 mile west of MP 50.....	10
On curves and slide areas.....	15
X77 CMStP&P Engines are prohibited from using east leg of old wye at Port Townsend.	