



M & E DEPT  
MILWAUKEE R. R.  
DATE 9-19-67

13400-13799 - BARBER S2C SIDE SPRINGS 3235# SOLID CAPY.

13800-14199 - BARBER S2C SIDE SPRINGS 4712# SOLID CAPY

Cascade Rail Foundation milwelectric.org

REV. A

UNDERFRAME RIGID TYPE CENTER SILL 41.2#

DRAFT GEARS 430 c/s MINER RF361, 350 c/s CARD. WEST. R500, 10 c/s NATL. NC440

COUPLERS BE 60 A HT

YOKES BY 40

AIR BRAKES ABD 1012 WESTINGHOUSE

SLACK ADJUSTER 400 c/s SAB 400 c/s ELLCON NAT'L.

HAND BRAKES AAR VERTICAL NON SPIN

TRUCKS 70 TON BARBER S2C STABILIZED

BOLSTERS 450 c/s A.S.F. 22053-I, 350 c/s SCULLIN 7976B, AAR# B75-05EB-BN

SIDE FRAMES 450 c/s A.S.F. 21982-E, 350 c/s SCULLIN 7900B, AAR# F75-04BN-UA

SIDE BEARINGS PULLMAN STD. ROLLER TYPE 4'-2" CENTERS

SPRINGS D-5 3 1/16" SPRING TRAVEL 28 O.C. 20 I.C.

JOURNALS 6"x11" 375 c/s TIMKEN, 225 c/s BRENCO, 200 c/s HYATT

WHEELS 33" DIA. 200 c/s ROLLED STEEL 2W, 600 c/s CAST STEEL 2W

BRAKE BEAMS # 24 UNIT TYPE

NOM. CAPY. 154,000

LT. WT. 65,000

LIMIT LOAD 155,000

CU. CAPY. 4952 CU. FT.

BUILT PULLMAN MICH. CITY IND.

YEAR 1967

LOT NO. 91734A, A.F.E. 07523

MECH. DESIG. "X M"

70 TON 50'-6" BOX CARS

SERIES